



Tiger Lake-LP Intel® Converged Security and Management Engine Firmware 15.0

Consumer Firmware Bring Up Guide

February 2020

| Revision 1.2

Intel Confidential



By using this document, in addition to any agreements you have with Intel, you accept the terms set forth below. You may not use or facilitate the use of this document in connection with any infringement or other legal analysis concerning Intel products described herein. You agree to grant Intel a non-exclusive, royalty-free ITigernse to any patent claim thereafter drafted which includes subject matter disclosed herein.

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH Intel® PRODUCTS. NO LTigerNSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

A "Mission Critical Application" is any application in which failure of the Intel Product could result, directly or indirectly, in personal injury or death. SHOULD YOU PURCHASE OR USE INTEL'S PRODUCTS FOR ANY SUCH MISSION CRITICAL APPLICATION, YOU SHALL INDEMNIFY AND HOLD INTEL AND ITS SUBSIDIARIES, SUBCONTRACTORS AND AFFILIATES, AND THE DIRECTORS, OFFTigerRS, AND EMPLOYEES OF EACH, HARMLESS AGAINST ALL CLAIMS COSTS, DAMAGES, AND EXPENSES AND REASONABLE ATTORNEYS' FEES ARISING OUT OF, DIRECTLY OR INDIRECTLY, ANY CLAIM OF PRODUCT LIABILITY, PERSONAL INJURY, OR DEATH ARISING IN ANY WAY OUT OF SUCH MISSION CRITICAL APPLICATION, WHETHER OR NOT INTEL OR ITS SUBCONTRACTOR WAS NEGLIGENT IN THE DESIGN, MANUFACTURE, OR WARNING OF THE INTEL PRODUCT OR ANY OF ITS PARTS.

Intel may make changes to specifications and product descriptions at any time, without notTiger. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined". Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notTiger.

The Tiger Lake Platform and Tiger Lake PCH products may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Intel® AMT should be used by a knowledgeable IT administrator and requires enabled systems, software, activation, and connection to a corporate network. Intel AMT functionality on mobile systems may be limited in some situations. Your results will depend on your specific implementation. Learn more by visiting [Intel® Active Management Technology](#).

Intel® Small Business Technology (Intel® SBT) requires an Intel® Small Business Technology enabled system and proper configuration. Availability of features will depend upon the setup and configuration by your PC manufacturer. Consult your system manufacturer.

Intel® vPro™ Technology requires setup and activation by a knowledgeable IT administrator. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment. Learn more at: <http://www.intel.com/technology/vpro>.

Any software source code reprinted in this document is furnished under a software ITigernse and may only be used or copied in accordance with the terms of that ITigernse.

64-bit computing on Intel architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel® 64 architecture. Processors will not operate (including 32-bit operation) without an Intel® 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. Consult with your system vendor for more information.

Intel processor numbers are not a measure of performance. Processor numbers differentiate features within each processor family, not across different processor families. See http://www.intel.com/products/processor_number for details. I2C is a two-wire communications bus/protocol developed by Philips. SMBus is a subset of the I2C bus/protocol and was developed by Intel. Implementations of the I2C bus/protocol may require ITigernses from various entities, including Philips Electronics N.V. and North American Philips Corporation.

Microsoft*, Windows* and the Windows* logo are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries.

Intel, Celeron, Pentium, Intel Xeon, Intel Core, Intel vPro™, and the Intel logo are trademarks of Intel Corporation in the United States and/or other countries. *Other names and brands may be claimed as the property of others.

KVM Remote Control (Keyboard, Video, Mouse) is only available with Intel® Core™ i5 vPro™ and Core™ i7 vPro™ processors with integrated graphics and Intel® Active Management technology activated. Discrete graphics are not supported.

Copyright © 2014-2020, Intel Corporation. All rights reserved.



Contents

1	Introduction	6
1.1	Related Documentation	6
1.2	Prerequisites	6
1.3	Acronyms and Definitions	7
1.3.1	General	7
1.3.2	Intel® Converged Security and Management Engine	8
1.3.3	System States and Power Management	9
1.4	Reference Documents	10
1.5	Format and Notation	10
1.6	Kit Contents	11
1.7	External Hardware Requirements for Bring Up	20
2	Image Creation: Intel® Flash Image Tool	21
2.1	Start Intel® FIT	21
2.2	Step-by-Step Guide to Build SPI Flash Image with Intel® FIT Interface	21
3	Programming SPI Flash Devices and Checking Firmware Status	139
3.1	Flash Burner/Programmer	139
3.1.1	In-Circuit SPI Flash Programming for CRB	139
3.2	Flash Programming Tool (Intel® FPT)	139
3.2.1	Intel® FPT Windows* Version	140
3.3	Checking Intel® ME Firmware Status	140
3.4	Common Bring Up Issues and Troubleshooting Table	142
A	Appendix — Flash Configurations	143
B	Appendix — Intel® ICCS SKU Support Matrix	144
C	Appendix — Boot Guard Configuration	145
D	Appendix — Intel® Platform Trust Technology	147
E	Appendix — Integrated Sensor Hub (ISH) Public Key Settings	148
F	Appendix — RVP Platform Specific Settings	150



Figures

Tables

1-1	Number Format Notation.....	10
1-2	Data Format Notation	10
1-3	Kit Contents	11
2-1	- Initial Screen Layout	22
2-2	- Build Settings.....	31
2-3	- Flash Layout	33
2-4	- Flash Settings	39
2-5	- Intel® ME Kernel	49
2-6	- Intel® AMT	53
2-7	- Platform Protection	61
2-8	- Integrated Clock Controller	67
2-9	- Networking & Connectivity	73
2-10	- Internal PCH Buses	78
2-11	- Power	83
2-12	- Integrated Sensor Hub	85
2-13	- Camera	87
2-14	- Debug.....	88
2-15	- CPU Straps	93
2-16	- Flex I/O Straps.....	95
2-17	- GPIO.....	110
2-18	- Intel® Precise Touch and Stylus.....	130
2-19	- Download and Execute	131
2-20	- FW Update Image Build	133
2-21	- Intel® FIT - Build Image	138
3-1	- Common Bring Up Issues and Troubleshooting Table	142



Revision History

Document Number	Revision Number	Description	Revision Date
	0.5	Initial Release	March 2018
	0.51	Updated Tiger Lake and Intel® CSME references	February 2019
	0.7	Synced to the latest FIT UI layout	February 2019
	0.71	Updated to latest RVP defaults	June 2019
	0.8	Updated for Alpha release	August 2019
	0.81	Added GBST settings	September 2019
	0.82	Added Version to IUNIT, PCHC and GBST entries in Flash Layout eSPI / EC Bus Frequency listed 40MHz should have been 48MHz Updated USB2 Port Configuration screen capture Updated OPI Link volt recommended default	October 2019
	0.83	Added missing 1.05v value to OPI Link Voltage	November 2019
	1.0	Updated to revision 1.0	December 2019
	1.1	Updated screen capture and settings information to latest UI layout Added Platform Appendix section	February 2020
	1.2	Added note to USB3 Port Speed Capability settings.	February 2020

§ §



1 Introduction

This document covers the Intel® Converged Security and Management Engine Firmware (Intel® ME) 15.0 - Consumer / Consumer Firmware bring up procedure. Intel® ME is tied to essential platform functionality — this dependency cannot be avoided for engineering reasons.

The bring up procedure primarily involves building a Serial Peripheral Interface (SPI) Flash image that will contain:

- **[required]** Descriptor region — Contains sizing information for all other SPI Flash image regions, SPI settings (including Vendor Specific Configuration - or VSCC - tables, SPI device parameters), and region access permissions.
- **[required]** BIOS region — Contains firmware for the processor (or host) and/or Embedded Controller (EC).
- **[required]** Intel® CSME FW region — Contains firmware for the Intel® Converged Security and Management Engine.
- **[optional]** GbE region — Contains firmware for Intel LAN solution.

For more details on SPI Flash layout, see the document **Tiger Lake-H / LP SPI Programming Guide** SPI Programming Guide and [Appendix A](#). Once the SPI Flash image is built, it will be programmed to the target based platform and the platform will be booted. This document also covers any tests and checks required to ensure that this boot process is successful and that Intel® ME Consumer FW is operating as expected.

1.1 Related Documentation

VIP: Kit# WIP - Intel® Ethernet Network Connections (xx.x OEM Gen) - LAN Software

CDI # WIP Intel® Ethernet Connection i2xx

Intel® CSME FW Features

This firmware release includes the following applications:

- Platform Clocks – Tune clock silicon to the parameters of a specific board, configure clocks at run time, and power management clocks. **Benefit:** Allows extensive customization and soft control of “Third generation” clock solution and makes clocks available before CPU powers up.
- Silicon Workaround Capability – Intel® CSME FW will have limited capabilities to perform targeted workarounds for silicon issues. **Benefit:** Allows Intel® CSME FW to address some issues that otherwise would require a new silicon stepping.

1.2 Prerequisites

Before this document is read and utilized, it is essential that the reader first review the Consumer FW Release Notes (included with this Intel® ME Consumer FW kit).



This document is constructed so that the reader can complete the bring up steps as given for the Intel Customer Reference Board (CRB). However, in the case that bring up is being performed on a different Intel® x based platform, this document will highlight any changes that must be imposed onto the bring up steps accordingly.

This document makes only the following limited assumptions regarding hardware:

- The platform is Tiger Lake LP/H based
- The platform is equipped with one or more SPI Flash devices with a total capacity sufficient for storing all relevant firmware images.

1.3 Acronyms and Definitions

1.3.1 General

Acronym or Term	Definition
BIOS	Basic Input Output System
DIMM	Dual In-line Memory Module
DMI	Direct Media Interface
EC	Embedded Controller
FPF	Field Programmable Fuses
FW	Firmware
GbE	Gigabit Ethernet
HECI	Host Embedded Controller Interface (aka Intel® MEI)
Intel® ICCS	Intel® Integrated Clock Controller Service
Intel® CSME	Intel® Converged Security and Management Engine (Intel® ME)
Intel® MEI	Intel® Converged Security and Management Engine Interface (Intel® MEI) (renamed from HECI)
Intel® PTT	Intel® Platform Trusted Technology (Intel® PPT)
Intel® MSS	Intel® Management and Security Status Application
KVM	Keyboard, Video, Mouse
LAN	Local Area Network
MCP	Multi-Chip Package (Central Processing Unit / Platform Controller Hub)
NVM	Non-Volatile Memory
OOB	Out-of-Band
OS	Operating System
PAVP	Protected Audio and Video Path
PCI	Peripheral Component Interconnect
PCIe*	Peripheral Component Interconnect Express
PHY	Physical Layer (Networking)
RTC	Real Time Clock
SBT	Intel® Small Business Technology
SMBus	System Management Bus



Acronym or Term	Definition
SPI Flash	Serial Peripheral Interface Flash
TPM	Trusted Platform Module
VSCC	Vendor Specific Configuration

1.3.2 Intel® Converged Security and Management Engine

Acronym or Term	Definition
3PDS	3rd Party Data Storage
Agent	Software that runs on a client PC with OS running
End User	The person who uses the computer (either Desktop or Mobile). In corporate, the user usually does not have administrator privileges.
Host or Host CPU	The processor that is running the operating system. This is different than the management processor running the Intel® Converged Security and Management Engine Firmware.
Host ServTiger/Application	An application that is running on the host CPU
INF	An information file (.inf) used by Microsoft* operating systems that supports the Plug & Play feature. When installing a driver, this file provides the OS the necessary information about driver filenames, driver components, and supported hardware.
Intel® Converged Security and Management Engine Interface (Intel® MEI)	Interface between the Converged Security and Management Engine and the Host system
Intel® MEI driver	Intel® ME host driver that runs on the host and interfaces between ISV Agents and the Intel® ME HW.
IT User	Information Technology User. Typically very technical and uses a management console to ensure functionality of multiple PCs on a network.
LMS	Local Management ServTiger: A SW application which runs on the host machine and provide a secured communication between the ISV agent and the Intel® Converged Security and Management Engine Firmware.
Intel® ME	Intel® Converged Security and Management Engine: The embedded processor residing in the chipset MCP
MECI	ME-VE Communication Interface
NVM	Non-Volatile Memory: A type of memory that will retain its contents even if power is removed. In the Intel® AMT current implementation, this is achieved using a FLASH memory device.
OOB Interface	Out Of Band interface: This is WSMAN interface over secure or non-secure TCP protocol.
OS not Functional	The Host OS is considered non-functional in Sx power state and any one of the following cases when system is in S0 power state: <ul style="list-style-type: none"> • OS is hung • After PCI reset • OS watch dog expires • OS is not present
System States	Operating System power states such as S0. See detailed definitions in System States and Power Management section.



1.3.3 System States and Power Management

Acronym or Term	Definition
G3	A system state of Mechanical Off where all power is disconnected from the system. G3 power state does not necessarily indicate that RTC power is removed.
CM0	Intel® Converged Security and Management Engine firmware power state where all hardware power planes are activated. The host power state is S0.
CM3	Intel® Converged Security and Management Engine power state where the host is in Sx. The processor DRAM Controller is turned off and DRAM power stays in off/self refresh mode. There is no UMA usage in CM3 state. Less than 1MB of SRAM used for code and data. Code is executed off of flash takes ~1mS.
CM0-PG	Core Well Powered; Intel® ME Well Powered; (Intel® ME core not consuming power) DRAM available.
CM3-PG	An Intel® ME Firmware power state where no power is applied to the Converged Security and Management Engine subsystem. (Intel® ME firmware is shut down).
OS Hibernate	System state where the OS state is saved on the hard drive.
S0	A system state where power is applied to all HW devices and the system is running normally.
S1, S2, S3	A system state where the host CPU is halted but power remains available to the memory system (memory is in self-refresh mode).
S4	A system state where the host CPU and memory are not active.
S5	A system state where all power to the host system is off, however the power cord (and/or battery in mobile designs) is still connected.
Shut Down	Equivalent to the S5 state.
Snooze Mode	Intel® Converged Security and Management Engine activities are mostly suspended to save power. The Intel® Converged Security and Management Engine monitors HW activities and can restore its activities depending on the HW event.
Standby	System state where the OS state is saved in memory and resumed from the memory when mouse/keyboard is clicked.
Sx	All S states which are different than S0.

1.4 Reference Documents

Document	Doc Number/ Location*
<i>Tiger Lake Intel® Converged Security and Management Engine (Intel® CSME) and Embedded Controller Interaction Product Specification Revision 0.5</i>	549024 / CDI
<i>Intel® Converged Security and Management Engine BIOS Writers Guide</i>	TBD / *
<i>Intel® Converged Security and Management Engine (Intel® CSME) 15 SKU Firmware Consumer Compliance Guide for Tiger Lake PCH-H/LP Chipset Family - Tiger Lake Platform Compliancy and Testing Guide - Revision x.x</i>	TBD / CDI

Note: * Unless specified otherwise, a document can be ordered by providing its reference number to your Intel Field Applications Engineer.



1.5 Format and Notation

The formats and notations used within this document model are those typically used by BIOS vendors. This section describes the formatting and the notations that will be followed in this document.

Table 1-1. Number Format Notation

Number Format	Notation	Example
Decimal (default)	d	14d. Note that any number without an explicit suffix can be assumed to be decimal.
Binary	b	1110b
Hex	h	0Eh
Hex	0x	0x0E

Table 1-2. Data Format Notation

Data Type	Notation	Size
Bit	b	Smallest unit, 0 or 1
Byte	B	8 bits
Word	W	16 bits or 2 bytes
Double-word	DW	32 bits or 4 bytes
Quad-word	QW	8 bytes or 4 words
Kilobyte	KB	1024 bytes
Megabit	Mb	1,048,576 bits or 128 KB
Megabyte	MB	1,048,576 bytes or 1024 KB
Gigabit	Gb	1,073,741,824 bits
Gigabyte	GB	1024 MB



1.6 Kit Contents

The Intel® CSME Consumer FW kit can be downloaded from VIP (<https://platformsw.intel.com/>). The contents of this kit are detailed below (Note that only key files are listed).

Table 1-3. Kit Contents (Sheet 1 of 8)

File or [Directory]	Content Description
[root]	Root directory
[Installers]	
[3rd party Licenses in Security SW]	
ACE-TAO-CIAO.pdf	Copyright and Licensing Information for ACE(TM), TAO(TM), and CIAO(TM)
Apache-Xerces-C++-XML-Parser.txt	Apache license for C++ XML parser
Inno Setup License.txt	Inno Setup License
LICENSE.libmei	libmei BSD License
Microsoft Windows Classic Samples.txt	Microsoft Windows Classic Samples License
Microsoft winfile MIT.txt	Microsoft winfile MIT License
openwsman.pdf	Intel openwsman License
Windows driver samples.txt	Microsoft driver samples License
WixLicenseNote.txt	Microsoft Wix License
[ME_SW_DCH]	
IntelMEFWVer.dll	DLL file containing software version information
mup.xml	XML file containing software version and driver information
SetupME.exe	DCH software installer executable
[ME_SW_MSI]	
IntelMEFWVer.dll	DLL file containing software version information
mup.xml	XML file containing software version and driver information
SetupME.exe	MSI software installer executable
[MEI-Only Installer MSI]	
IntelMEFWVer.dll	DLL file containing MEI version information
mup.xml	XML file containing MEI software version and driver information
SetupME.exe	Intel® MEI software installer executable
[WindowsDriverPackages]	
[iCLS]	Intel® Capability Licensing Service folder
iclsClient.cat	iCLS CAT file
iclsClient.inf	UWD iCLS Client INF
[JHI]	
[IoTCorePackages]	
Intel.Drivers.DAL.cab	Intel® Dynamic Application Loader CAB file
[Win10]	
DAL.cat	Intel® Dynamic Application Loader CAT file



Table 1-3. Kit Contents (Sheet 2 of 8)

File or [Directory]		Content Description
	DAL.inf	Intel® Dynamic Application Loader INF file
	JHI.dll	Intel® Dynamic Application Loader 32bit DLL file
	jhi_service.exe	Intel® Dynamic Application Loader Windows Services executable file
	JHI64.dll	Intel® Dynamic Application Loader 64bit DLL file
	SpoolerApplet.dalp	Intel® Dynamic Application Loader Spooler Applet
	TEEManagement.dll	Intel® Dynamic Application Loader TEE Management 32bit DLL
	TEEManagement64.dll	Intel® Dynamic Application Loader TEE Management 64bit DLL
	[LMS]	
	[Certificates]	
	B2C067A6568D27791074C3F5C5A58966D6F12E36.cer	LMS Certificates files
	BBAF7E023DFAA6F13C848EADDEE3898ECD93232D4.cer	
	BF4E419CC0A20D33947C2A04867B27DE63A2174F.cer	
	SFIP Production SHA256.cer	
	[Templates]	
	5710ABF3E156BFE90FD5C8E21606788DA4D69ADD.data	LMS Template file



Table 1-3. Kit Contents (Sheet 3 of 8)

File or [Directory]	Content Description
1200_PD_PFU.BIN	Intel® CSME 12.x Firmware Update binaries
1200_PP_PFU.BIN	
1300_PD_PFU.BIN	Intel® CSME 13.x Firmware Update binaries
1300_PP_PFU.BIN	
1400_PD_PFU.BIN	Intel® CSME 14.x Firmware Update binaries
1400_PP_PFU.BIN	
1500_PD_PFU.BIN	Intel® CSME 15.x Firmware Update binaries
1500_PP_PFU.BIN	
ACE.dll	ADAPTIVE Communication Environment ^(TM) DLL
ComEventHandler.dll	COM Event Handler DLL
Common.dll	Common DLL
Configurator.dll	Configurator DLL
EventManager.dll	Windows Event Manager DLL
FWUpdateLib_10.dll	Firmware Update Library DLL for Intel® ME 10.x
FWUpdateLib_11.dll	Firmware Update Library DLL for Intel® ME 11.x
FWUpdateLib_12.dll	Firmware Update Library DLL for Intel® ME 12.x - 15.x
GmsCommon.dll	GMS Common DLL
HistoryEventHandler.dll	History Event Handler DLL
HostChangesNotificationService.dll	Host Changes Notification Service DLL
IPRefreshService.dll	IP Refresh Service DLL
LMS.cat	LMS CAT file
LMS.exe	LMS Service executable
LMS.inf	LMS INF file
Log.txt	LMS Log file
PartialFWUpdateService.dll	Partial Firmware Update Service DLL
PortForwardingService.dll	Port Forwarding Service DLL
PowerOperationsService.dll	Power Operation Service DLL
SharedStaticIPService.dll	Shared Static IP Service DLL
SoapServerService.dll	Soap Server Service DLL
StatusEventHandler.dll	Status Event Handler DLL
TimeSyncService.dll	Time Sync Service DLL
WiFiProfileSyncService.dll	WiFi Profile Sync Server DLL
WinLogEventHandler.dll	Windows Log Event Handler DLL
WMIEventHandler.dll	WMI Event Handler DLL
WsmanClient.dll	WSMAN Client DLL
[MEI]	
[Win7]	
[x64]	
TeeDriverx64.sys	Windows 7 64bit MEI TeeDriver file
[x86]	



Table 1-3. Kit Contents (Sheet 4 of 8)

File or [Directory]	Content Description
TeeDriver.sys	Windows 7 32bit MEI TeeDriver file
heci.cat	Windows 7 MEI TeeDriver CAT file
heci.inf	Windows 7 MEI TeeDriver INF file
[Win8]	
[x64]	
TeeDriverW8x64.sys	Windows 8 64bit MEI TeeDriver file
[x86]	
TeeDriverW8.sys	Windows 8 32bit MEI TeeDriver file
heci.cat	Windows 8 MEI TeeDriver CAT file
heci.inf	Windows 8 MEI TeeDriver INF file
[Win10]	
[x64]	
TeeDriverW10x64.sys	Windows 10 64bit MEI TeeDriver file
[x86]	
TeeDriverW10.sys	Windows 10 32bit MEI TeeDriver file
heci.cat	Windows 10 MEI TeeDriver CAT file
heci.inf	Windows 10 MEI TeeDriver INF file
[MEI_ICLS]	
ReleaseNotes.txt	iCLS Client release notes
[SOL]	
mesrl.cat	Serial Over LAN CAT file
mesrl.inf	Serial Over LAN INF file
[TGP-LP]	
[3rd party Licenses in Security FW]	
Apache Harmony Apache Version 2.0, January 2004 w header.txt	Apache Harmony Apache Version 2.0 License
Apache-Xerces-Java-XML-Parser.txt	Apache Xerces Java XML Parser License
ConvertUTF unicode license.txt	Convert UTF Unicode License
CxImage license complete.txt	CxImage License
HTTP Client C MIT license.txt	HTTP Client MIT License
Ilvm.org University of Illinois_NCSA.txt	Compiler_RT MIT License
Microsoft TPM 2.0 BSD Two Clause License.txt	TPM 2.0 BSD Two Clause Microsoft License
Minix 3.pdf	Minix 3 operating system License
MIT Kerberos for Windows.pdf	Kerberos for Windows MIT License
newlib_licenses.txt	Newlib License
Synopsys UFS Host Controller OS.pdf	Synopsys UFS Host Controller OS License
wpa supplicant license.txt	WPA Supplicant License
zlib license.txt	Zlib compression library License
[FWU_Prestitched]	
Cons_Prestitched_FWUpdate.bin	Consumer Firmware Updated Pre-stitched binary
Corp_Prestitched_FWUpdate.bin	Corporate Firmware Updated Pre-stitched binary



Table 1-3. Kit Contents (Sheet 5 of 8)

File or [Directory]	Content Description
[Image Components]	
[CSME]	
[Silicon]	
[LP]	
[A0]	
[PreProduction]	
CSME_FW_Consumer_TGP-LP_A0.bin	Intel® CSME firmware image (Non-Production FW) - supports un-fused Tiger Lake PCH-LP Platform I/O MCP stepping: <ul style="list-style-type: none"> • Un-fused (Super SKU) Note: For PAVP Testing, you must match Production FW with Production Part and Non-Production FW with Non-Production Parts.
[PCHC]	
pchc_TGL_PCHC_15.0.0.xxxx.bin	Un-signed PCH Configuration binary
pchc_TGL_PCHC_15.0.0.xxxx_signed.bin	Signed PCH Configuration binary
[PMC]	
TGPLP_Z0_PMC_FW_150.01.00.xxxx.bin	PMC firmware binary
[TCSS]	
[IOM]	
iomfw_v10.000c.0.0_signed.bin	IOM firmware binary
[PHY]	
TcssPartition_v2.1017.bin	PHY firmware binary
[Retimer]	
BBR_CDR_A1_TGL_PORTS_0_1_rev2_2_sign.bin	Retimer firmware binary for TCSS Ports 0 and 1
BBR_CDR_A1_TGL_PORTS_2_3_rev2_2_sign.bin	Retimer firmware binary for TCSS Ports 2 and 3
[TBT]	
TBT_TGL_A0_REV1_PRE16_signed.bin	Thunderbolt™ firmware binary
TGL-LP Consumer Bring Up Guide.pdf	This document
TGL-LP Corporate Bring Up Guide.pdf	
Tigerlake-LP Client SPI Programming Guide.pdf	
[Tools]	
[ICC Tools]	
[ICC SDK]	
[Windows64]	
icc_sdk_api.h	Integrated Clock Controller SDK API .H file
sdkLib.lib	Integrated Clock Controller SDK Library file
[WDT Driver]	
[ICCWDT_11.7.0.1000_19H1_Cert]	
[Win7]	
[ICCWDT.Dev.Install]	



Table 1-3. Kit Contents (Sheet 6 of 8)

File or [Directory]	Content Description
[ICCWDT_Driver]	
[x64]	
iccwdt.sys	
WdfCoInstaller01009.dll	
iccwdt.cat	
iccwdt.inf	
iccwdt.sys	
WdfCoInstaller01009.dll	
[x64]	
DIFxAPI.dll	ICC Watch Dog Timer 64bit driver install frameworks API DLL
Drv64.exe	
DIFxAPI.dll	ICC Watch Dog Timer 32bit driver install frameworks API DLL
license.txt	ICC Watch Dog Timer SDK License
Readme.txt	ICC Watch Dog Timer Readme file
Setup.cfg	ICC Watch Dog Timer Setup configuration file
setup.exe	ICC Watch Dog Timer Setup executable
Setup.if2	ICC Watch Dog Timer IF2 file
[ICCWDT.Install]	
[Win10]	
[ICCWDT.Dev.Install]	
[ICCWDT.Install]	
Intel(R) ME Firmware ICC Tools User Guide.pdf	Integrated Clock Controller Tools User guide
[System Tools]	
[Documentation]	
Signing and Manifesting User Guide.pdf	Signing and Manifest Users Guide
SLA_TOOLS.PDF	MEInfo and FWUpdLcl Redistribution License
TGL_System_Tools_UG.pdf	System Tools User guide
VSCCommn_bin Content.pdf	List of supported SPI Flash devices with specific Flash parameters.
[FIT]	
Windows32]	
fit.exe	Intel® Flash Image Tool
vsccommn.bin	Binary containing the supported SPI parts.
[FPT]	
[Efi64]	
Fpt.efi	64bit uEFI Intel® Flash Programming Tool executable.
[Windows64]	
FPTW64.exe	Windows 64bit Intel® Flash Programming Tool executable.



Table 1-3. Kit Contents (Sheet 7 of 8)

File or [Directory]	Content Description
IdrvdII32e.dll	Windows DLL files for Intel® Flash Programming Tool.
PmxdII32e.dll	
[FWUpdate]	
[Efi64]	
errorlist.c	64bit uEFI C Source and Library files for Firmware Update.
errorlist.h	
fwudef.h	
FwUpdateEfiLib.lib	
fwupdatelib.h	
fwupdatelibdeprecated.h	
FWUpdLcl.efi	64bit uEFI Firmware Update executable.
[Windows64]	
errorlist.c	Windows 64bit C Source and Library and Sample code files for Firmware Update.
errorlist.h	
fwudef.h	
FwUpdateEfiLib.lib	
fwupdatelib.h	
fwupdatelibdeprecated.h	
FWUpdateSample.c	
FWUpdLcl64.exe	Windows 64bit Firmware Update executable.
[FWUpdate_RS]	
[Efi64]	
errorlist.c	Reduced size 64bit uEFI C Source and Library files for Firmware Update.
errorlist.h	
fwudef.h	
FwUpdateEfiLib.lib	
fwupdatelib.h	
fwupdatelibdeprecated.h	
FWUpdLcl.efi	Reduced size 64bit uEFI Firmware Update executable.
FWUpdLclApp.c	Reduced size 64bit uEFI Firmware Update Application sample.
FWUpdLclAppDeprecated.c	
[MEInfo]	
[Efi64]	
MEInfo.efi	64bit uEFI Intel® ME Information executable.
[Windows64]	
MEInfoWin64.exe	Window 64bit Intel® ME Information executable.
IdrvdII32e.dll	Windows DLL files for Intel® ME Information Tool.
PmxdII32e.dll	
[MEManuf]	
[Efi64]	







Table 1-3. Kit Contents (Sheet 8 of 8)

File or [Directory]		Content Description
	MEManuf.efi	64bit uEFI Intel® ME Manufacturing test tool executable.
	[Windows64]	
	MEManufWin64.exe	Windows 64bit Intel® ME Manufacturing test tool executable.
	IdrvdII32e.dll	Windows DLL files for Intel® ME Information Tool.
	PmxdII32e.dll	
	[MEU]	
	[Windows32]	
	meu.exe	Windows 32bit Intel® Manifest Extension Utility executable.

1.7 External Hardware Requirements for Bring Up

Acquire the following hardware tools before moving on to the next step.

Windows* OS System	Flash Burner	DOS Bootable USB Key
		
<p>Equipment:</p> <ul style="list-style-type: none"> Laptop or desktop that supports win32 applications <p>Purpose:</p> <ul style="list-style-type: none"> Will run firmware image assembly and build process software. 	<p>Equipment:</p> <ul style="list-style-type: none"> (Optional) For platforms that don't boot, a Flash Chip Programmer will be required For platforms that can boot to DOS or Windows*, a Intel® FPT is provided in this kit <p>Purpose:</p> <ul style="list-style-type: none"> Will burn firmware images onto the target system Flash device(s). 	<p>Equipment:</p> <ul style="list-style-type: none"> A DOS Bootable USB Key (Size > 512 MB) <p>Purpose:</p> <ul style="list-style-type: none"> Acting as a bootable device and will be used to run Intel® FPT (fpt.exe) directly on the system that is undergoing Bring Up process. Or will be used to transfer a firmware image onto a Flash burner.

§ §



2 Image Creation: Intel® Flash Image Tool

Intel® Flash Image Tool (Intel® FIT) can be used to generate either a full SPI Flash binary image with Descriptor, GbE, BIOS, and Intel® ME Regions. Additionally, it can be used to create a simple image containing only the Intel® ME Region only for use with custom SPI Flash binary image assembly solutions. Use the steps shown in following sections.

After this image has been created, it will need to be burned onto the target platform's SPI Flash device(s). [Section 3, "Programming SPI Flash Devices and Checking Firmware Status"](#) later in this document provides steps to do this.

Note: The Flash Image Tool may be updated throughout the release cycles. As a general rule, please ensure you use the tools, images and other content from the same kit and refrain from using different version tools.

2.1 Start Intel® FIT

1. Invoke Intel® Flash Image Tool. Using Explorer*, navigate to **[root]\Tools\System Tools\Flash Image Tool**. Verify that the directory contents are correct (see [Section 1.6](#)). Double-click **FIT.exe**.
2. **NOTE:** In the tables below, where default settings are listed for TGL LP/H, if the value is the same one value will be listed. If there is a different default value when the program loads with either platform, both values will be listed to show the difference.

2.2 Step-by-Step Guide to Build SPI Flash Image with Intel® FIT Interface



Table 2-1. - Initial Screen Layout (Sheet 1 of 9)

#	Label	Contents
1	New	This button labeled 'New' on rollover allows opening of a new session with default values
2	Open	This button labeled 'Open' on rollover allows opening of an xml or bin file
3	Save	This button labeled 'Save' on rollover allows saving of xml file
4	Clear Console	This button labeled 'Clear Console' clears the console area (see page 23)
5	Build Settings	This button labeled 'Build Settings' brings up the build settings popup Window see (Table 2-2)
6	Build Image	This button labeled 'Build Image' on rollover allows build of the image
7	Build Image For FWUpdate	This button labeled 'Build Image For FWUpdate' allows the user to build separate firmware update binaries.



Table 2-1. - Initial Screen Layout (Sheet 2 of 9)

#	Label	Contents
8	Drop Down Selector	This drop down allows selection of platform
9	Drop Down Selector	This drop down allows selection of SKU within platform selected
10	Indicator	This displays the type of Boot Media Target based on FW being used



Table 2-1. - Initial Screen Layout (Sheet 3 of 9)

#	Label	Contents
	Flash Layout	11
	Flash Settings	12
	Intel (R) ME Kernel	13



Table 2-1. - Initial Screen Layout (Sheet 4 of 9)

#	Label	Contents
11	Flash Layout Tab	Flash Layout which contains (see Table 2-3): <ul style="list-style-type: none"> • Descriptor Region • BIOS Region • IFWI: Intel® ME and PMC Region • EC Region • GBE Region • SubPartitions • PDR Region
12	Flash Settings Tab	Flash Settings which contains (see Table 2-4): <ul style="list-style-type: none"> • Flash Components • Host CPU/ BIOS Master Access • Intel® ME Master Access • GBE Master Access • EC Master Access • Flash Configuration • Legacy VSCC Table - VSCC Entries • BIOS Configuration • FPF Configuration
13	Intel® ME Kernel Tab	Intel® ME Kernel which contains (see Table 2-5): <ul style="list-style-type: none"> • Processor • Intel® ME Firmware Update • Image Identification • Firmware Diagnostics • End of Manufacturing Configuration • MCTP Configuration • Intel® ME Boot Configuration • Intel® ME Assisted Boot Configuration • Reserved



Table 2-1. - Initial Screen Layout (Sheet 5 of 9)

#	Label	Contents
14	Intel® AMT Tab	Intel® AMT which contains (see Table 2-6): <ul style="list-style-type: none"> • Intel® AMT Configuration • KVM Configuration • Provisioning Configuration • OEM Customizable Certificates (1, 2, 3) • OEM Default Certificates (1, 2, 3, 4, 5) • Redirection Configuration • TLS Configuration
15	Platform Protection Tab	Platform Protection which contains (see Table 2-7): <ul style="list-style-type: none"> • Content Protection • Graphics uController • Hash Key Configuration for Bootguard / ISH • Boot Guard Configuration • Type-C Firmware Anti-Rollback Configuration • Intel® PTT Configuration • TPM Over SPI Bus Configuration • BIOS Guard Configuration • TXT Configuration • Crypto Hardware Support • Platform Trusted Device Setup Support • Intel FPF Anti-Rollback Configuration
16	Integrated Clock Controller Tab	Integrated Clock Controller which contains (see Table 2-8): <ul style="list-style-type: none"> • Integrated Clock Controller Policies • Profiles




Table 2-1. - Initial Screen Layout (Sheet 6 of 9)

#	Label	Contents
17	Networking & Connectivity Tab	Networking & Connectivity which contains (see Table 2-9): <ul style="list-style-type: none">• Platform vPro NIC• Docking Station• Wired LAN Configuration• Wireless LAN Configuration• Time Sensitive Networking Configuration



Table 2-1. - Initial Screen Layout (Sheet 7 of 9)

#	Label	Contents
18	Internal PCH Buses Tab	Internal PCH Buses which contains (see Table 2-10): <ul style="list-style-type: none"> PCH Timer Configuration SMBus / SMLink Configuration DMI Configuration OPI /DMI Configuration eSPI Configuration
19	Power Tab	Power which contains (see Table 2-11): <ul style="list-style-type: none"> Platform Power Deep Sx PCH Thermal Reporting
20	Integrated Sensor Hub Tab	Integrated Sensor Hub which contains (see Table 2-12): <ul style="list-style-type: none"> Integrated Sensor Hub ISH Image ISH Data
21	Camera	<ul style="list-style-type: none"> IPU Security (see Table 2-13):



Table 2-1. - Initial Screen Layout (Sheet 8 of 9)

#	Label	Contents
22	Debug Tab	Debug which contains (see Table 2-14): <ul style="list-style-type: none"> IDLM Delayed Authentication Mode Configuration Intel® Trace Hub Technology Intel® ME Firmware Debugging Overrides Direct Connection Interface Configuration eSPI Feature Overrides Early USB DBC over Type-A Configuration TRC Emulation
23	CPU Straps Tab	CPU Straps which contain a detailed list of parameters (see Table 2-15) <ul style="list-style-type: none"> CPU Straps
24	Flex I/O Tab	Flex I/O which contains (see Table 2-16): <ul style="list-style-type: none"> PCIe Lane Reversal Configuration PCIe Port Configuration SATA / PCIe Combo Port Configuration USB3 Port Configuration USB2 Port Configuration Type-C Subsystem Configuration Thunderbolt Configuration
25	GPIO Tab	GPIO which contains (see Table 2-17): <ul style="list-style-type: none"> ME Feature Pins Touch Controller Pins GPIO VCCIO Voltage Control Thunderbolt LSx/BSSB-LS Configuration



Table 2-1. - Initial Screen Layout (Sheet 9 of 9)

#	Label	Contents
26	Intel® Precise Touch and Stylus	Intel® Precise Touch and Stylus which contains (see Table 2-18): <ul style="list-style-type: none"> • Integrated Touch Configuration • Intel® Integrated Touch and Stylus Configuration
27	Download and Execute	Download and Execute which contains (see Table 2-19): <ul style="list-style-type: none"> • DnX Configuration • USB Descriptor
28	FW Update Image Build	FW Update Image Build which contains (see Table 2-20): <ul style="list-style-type: none"> • ME Image • PMC Image • OEM KM Image • IOM Image • NPHY Image • TBT Image • ISH Image • INUIT Image • PCHC Image
	Console Window Area	Displays opening messages, log file entries, and build activity messages



Table 2-2. - Build Settings (Sheet 1 of 2)

Click on Build Button in the top menu bar> Build Settings window pop up is displayed:			
#	Parameter	CRB	Values
1	Output Path		Double click to the right of outimage.bin and click to get browse button to specify path and name of file to create for the build - default is outimage.bin in the same folder as Intel® FIT tool
2	FWUpdate Output Path		Double click to the right of FWUpdate.bin and click to get browse button to specify path and name of file to create for the build - default is FWUpdate.bin in the same folder as Intel® FIT tool
3	Build FWUpdate With Full Image	No	Yes/No - No is default



Table 2-2. - Build Settings (Sheet 2 of 2)

Click on Build Button in the top menu bar> Build Settings window pop up is displayed:			
4	Generate Intermediate Files	Yes	Yes/No - Yes is default
5	Enable Boot Guard warning message at build time	Yes	Yes/No - Yes is default
6	Enable Intel (R) Platform Trust Technology warning message at build time	Yes	Yes/No - Yes is default
7	Region Order	Yes	53241 - is default
8	IFWI Build Version	Yes	32-bit value to use as the IFWI build version number.
9	Redundancy Enabled	Yes	This setting enabled Redundancy support for critical layout components.
10	MRP Enabled	false	Enable MRP support for critical layout components.
11	Read-Only protection for Minimal Recovery code	No	Set this to Yes if you want to have the start of the Intel® CSE to be read-only at boot.
12	Default Data Partition Enabled	Yes	Enable Intel® CSME Default Data partition
13	Intel® Manifest Extension Utility Path	Yes	
14	Signing Tool Path	Yes	
15	Signing Tool	Yes	
16			\$WorkingDir and \$DestDir can be left at the default '.' Click on \$SourceDir Value field and type in path where the Image Components are located for the Manageability Engine kit



Table 2-3. - Flash Layout (Sheet 1 of 6)

Click on Flash Layout in the left tabs menu> Descriptor Region is expanded by default:

▼

Descriptor Region

1

Parameter	Value	
OEM Section Binary		This loads the OEM Sec

#	Parameter	Platform	Settings
1	OEM Section Binary This loads the OEM Section binary that will be merged into the output image generated by the Intel® FIT tool.	UP4 UP3	OEM Binary (optional)

Click on Flash Layout in the left tabs menu> BIOS Region is expanded by default:

▼

BIOS Region

2

Parameter	Value	Help Text
Length	0	-
BIOS Binary File		This loads the BIOS binary that will be merged

#	Parameter	Platform	Settings
2	BIOS Region		
	BIOS Region - Length -This displays the length of the BIOS binary. Note: This value will be automatically populated by Intel® FIT during image build.		
	BIOS Binary File Navigate to path to load bios.rom file. This loads the BIOS binary that will be merged into the output image generated by the Intel® FIT tool.	UP4 UP3	biosimage.bin biosimage.bin

Click on Flash Layout in the left tabs menu> Ifw: Intel® ME and PMC Region is expanded by default:



Table 2-3. - Flash Layout (Sheet 2 of 6)

▼ Ifwi: Intel(R) Me and Pmc Region 3			
Parameter	Value	Help T	
Intel(R) ME Binary File		This loads the Intel(R) ME binary that will be merge	
Major Version	0	This displays Major revision number of the current	
Minor Version	0	This displays Minor revision number of the currentl	
Hotfix Version	0	This displays Hot-Fix revision number of the current	
Build Version	0	This displays Build version number of the currentl	
Chipset Initialization Version		This displays the current Chipset Initialization versio	
Chipset Initialization Binary		This loads the Chipset Initialization binary that will l	
ChipsetInit Override Version		This displays the version of the Chipset Initializtion	
PMC Binary File		This loads the PMC binary that will be merged into	
PMC Length	0x20000	-	
Version		-	

#	Parameter	Platform	Settings
3	Ifwi: Intel® ME and PMC Region		
	Intel® CSME Binary File Navigate to your Source Directory (as specified in Table 2-2) and switch to the Intel® CSME subdirectory. Choose the appropriate Intel® CSME Firmware binary image. This loads the Intel® CSME binary that will be merged into the into the output image generated by the Intel® FIT tool. Note: You may choose to build the Intel® CSME Region only. To do so, the Number of Flash Components in Flash Settings> Flash Components must be set to 0. Note: If loading meimage.bin file, check that the ME region is enabled in tool before building image.	UP4 UP3	meimage.bin meimage.bin
	Major Version - This displays Major revision number of the currently loaded Intel® CSME binary.		
	Minor Version - This displays Minor revision number of the currently loaded Intel® CSME binary.		
	Hotfix Version - This displays Hot-Fix revision number of the currently loaded Intel® CSME binary.		
	Build Version - This displays Build version number of the currently loaded Intel® CSME binary.		
	Chipset Initialization Version - This displays the current Chipset Initialization version contained in the currently loaded Intel® CSME binary.		



Table 2-3. - Flash Layout (Sheet 3 of 6)

	Chipset Initialization Binary - This loads the Chipset Initialization binary that will be merged into the output image generated by the Intel® FIT. If specified, this will override the version contained in the Intel® CSME binary to align with the values programmed by BIOS. Note: When BIOS passes new Chipset Initialization settings to ME, a Global Reset is initiated (only required on the first boot, subsequent boots will not incur a global reset). This allows for the new settings to be stored in the ME Region and programmed into the PCH. This global reset can be avoided by loading the proper chipset initialization binary in to the ME Region when building the image that aligns with the values in BIOS. The Chipset Initialization Binary will be included in BIOS RC package. If BIOS contains an older version of Chipset Initialization settings ME will be updated at boot with the older settings regardless of any newer settings being present in firmware. In order to avoid this problem and the additional Global Reset customers should ensure that both BIOS and ME are updated with same Chipset Initialization binary.	UP4 UP3	Chipset.bin (Optional) Chipset.bin (Optional)															
	ChipsetInit Override Version - This displays the version of the Chipset Initialization Binary override if specified.																	
	PMC Binary File - This loads the PMC binary that will be merged into the output image generated by the Intel® FIT tool.	UP4 UP3	PMC.bin PMC.bin															
	PMC Length - This displays the length of the PMC binary. Note: This value will be automatically populated by Intel® FIT during image build.																	
	Version - This displays the version of PMC																	
Click on Flash Layout in the left tabs menu> EC Region is expanded by default:																		
<div>▼ EC Region</div> <div>4</div>																		
<table><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr><tr><td>Length</td><td>0</td><td>-</td></tr><tr><td>EC Binary File</td><td></td><td>This loads the Embedded Controller binary used for eSPI that will</td></tr><tr><td>EC Region Enable</td><td>Disabled</td><td>This option allows the user to enable or disable the Embedded Co</td></tr><tr><td>EC Region Pointer File</td><td></td><td>This loads a binary containing the 16 byte value to be written in th</td></tr></table>				Parameter	Value	Help Text	Length	0	-	EC Binary File		This loads the Embedded Controller binary used for eSPI that will	EC Region Enable	Disabled	This option allows the user to enable or disable the Embedded Co	EC Region Pointer File		This loads a binary containing the 16 byte value to be written in th
Parameter	Value	Help Text																
Length	0	-																
EC Binary File		This loads the Embedded Controller binary used for eSPI that will																
EC Region Enable	Disabled	This option allows the user to enable or disable the Embedded Co																
EC Region Pointer File		This loads a binary containing the 16 byte value to be written in th																
#	Parameter	Platform	Settings															
4	EC Region	UP4 UP3	0 0															
	EC Region - Length Note: This value will be automatically populated by Intel® FIT during image build.																	
	EC Binary File Navigate to path to load EC bin file. This loads the Embedded Controller binary used for eSPI that will be merged into the output image generated by the Intel® FIT tool.	UP4 UP3	EC Binary EC Binary															
	EC Region Enable Values: Enabled/Disabled This option allows the user to enable or disable the Embedded Controller data region.	UP4 UP3	Enabled Enabled															
	EC Region Pointer File This loads a binary file containing the 16 byte Embedded Controller pointer value at the start of the flash descriptor	UP4 UP3	EC Pointer Binary EC Pointer Binary															
Click on Flash Layout in the left tabs menu> GbE Region is expanded by default:																		



Table 2-3. - Flash Layout (Sheet 4 of 6)

<div> <div>▼ GbE Region</div> <div>5</div> </div>			
Parameter	Value	Help Text	
Length	0	-	
GbE Binary File		This loads the Intel(R) Integrated LAN binary that will be merged into the output image generated by the Intel® FIT tool.	
GbE Region Enable	Enabled	This option allows the user to enable or disable the Gigabit Ethernet Region.	
Image Id	0	This displays Image ID of the currently loaded Intel (R) Integrated LAN binary.	
Major Version	0	This displays Major revision number of the currently loaded Intel (R) Integrated LAN binary.	
Minor Version	0	This displays Minor revision number of the currently loaded Intel (R) Integrated LAN binary.	
#	Parameter	Platform	Settings
5	GbE Region This loads the Intel® Integrated LAN binary that will be merged into the output image generated by the Intel® FIT tool.		
	GbE Region - Length Note: This value will be automatically populated by Intel® FIT during image build.		
	GbE Binary File Navigate to your Source Directory (as specified in Table 2-2) and switch to the GbE subdirectory. Choose the appropriate Intel GbE LAN Firmware binary image. If not using Intel LAN then load the GbE image before disabling the region along with changing additional settings below. This loads the Intel® Integrated LAN binary that will be merged into the output image generated by the Intel® FIT tool. Note: If loading gbeimage.bin file, check that the GbE region is enabled in tool before building image.	UP4 UP3	gbeimage.bin gbeimage.bin
	GbE Region Enable Values: Enabled/Disabled - This option allows the user to enable or disable the Gigabit Ethernet Region. NOTE: If choosing a configuration that does not include the GbE LAN the following settings need to be adjusted:	UP4 UP3	Enabled Enabled
	Image Id - This displays the Image ID of the currently loaded Intel® Integrated LAN binary.		
	Major Version - This displays the Major revision number of the currently loaded Intel® Integrated LAN binary.		
	Minor Version - This displays the Minor revision number of the currently loaded Intel® Integrated LAN binary.		
Click on Flash Layout in the left tabs menu> IUnit Sub-Partition is expanded by default:			
<div> <div>▼ IUnit Sub-Partition</div> <div>6</div> </div>			
Parameter	Value	Help Text	
IUnit Binary File		This loads the IUnit binary that will be merged into the output image generated by the Intel® FIT tool.	
Length	0xA000	-	
Version		-	



Table 2-3. - Flash Layout (Sheet 5 of 6)

#	Parameter	Platform	Settings												
6	IUNIT Sub-Partition Binary This loads the IUnit Sub Partition binary that will be merged into the output image generated by the Intel® FIT tool.	UP4 UP3	Iunit.bin (Optional) Iunit.bin (Optional)												
	Length - This displays the length of the IUNIT Sub-Partition. Note: This value will be automatically populated by Intel® FIT during image build.														
	Version - This displays the version number of the IUNIT Sub-Partition														
Click on Flash Layout in the left tabs menu> PCH Configuration Sub-Partition is expanded by default:															
▼ PCH Configuration Sub-Partition 7															
<table><tr><th>Parameter</th><th>Value</th><th></th></tr><tr><td>PCH Configuration File</td><td></td><td>This loads the PCH Configuration binary th</td></tr><tr><td>Version</td><td></td><td>-</td></tr><tr><td>Length</td><td>0x1000</td><td>-</td></tr></table>				Parameter	Value		PCH Configuration File		This loads the PCH Configuration binary th	Version		-	Length	0x1000	-
Parameter	Value														
PCH Configuration File		This loads the PCH Configuration binary th													
Version		-													
Length	0x1000	-													
#	Parameter	Platform	Settings												
7	PCH Configuration Sub-Partition This loads the PCH Configuration binary that will be merged in the output image generated by the Intel® FIT tool.														
	PCH Configuration File Navigate to path to load PCHC.bin file. This loads the PCH Configuration binary.	UP4 UP3	PCHC.bin PCHC.bin												
	Version - This displays the version number of the PCHC Configuration Sub-Partition														
	Length - This displays the length of the PCH Configuration Sub-Partition. Note: This value will be automatically populated by Intel® FIT during image build.														
Click on Flash Layout in the left tabs menu> GBST Configuration Sub-Partition is expanded by default:															
▼ GBST Configuration Sub-Partition 8															
<table><tr><th>Parameter</th><th>Value</th><th>Help</th></tr><tr><td>GBST Configuration File</td><td></td><td>This loads the GBST Configuration binary that w</td></tr><tr><td>Version</td><td></td><td>-</td></tr><tr><td>Length</td><td>0x1000</td><td>-</td></tr></table>				Parameter	Value	Help	GBST Configuration File		This loads the GBST Configuration binary that w	Version		-	Length	0x1000	-
Parameter	Value	Help													
GBST Configuration File		This loads the GBST Configuration binary that w													
Version		-													
Length	0x1000	-													
#	Parameter	Platform	Settings												
8	GBST Configuration Sub-Partition This loads the GBST Configuration binary that will be merged in the output image generated by the Intel® FIT tool. Note: The GBST sub-partition is used to enabling FuSa safety standards and is not applicable for client platforms.														
	GBST Configuration File Navigate to path to load GBST.bin file. This loads the GBST Configuration binary.	UP4 UP3	GBST.bin (Optional)												



Table 2-3. - Flash Layout (Sheet 6 of 6)

	Version - This displays the version number of the GBST Configuration Sub-Partition		
	Length - This displays the length of the GBST Configuration Sub-Partition. Note: This value will be automatically populated by Intel® FIT during image build.		

Click on Flash Layout in the left tabs menu> PDR Region is expanded by default:

▼ PDR Region

9

Parameter	Value	Help Text
Length	0	-
PDR Binary File		This loads the Platform Data region binary tha
PDR Region Enable	Disabled	This option allows the user to enable or disab

#	Parameter	Platform	Settings
9	PDR Region - This loads the Platform Data region binary that will be merged into the output image generated by the Intel® FIT tool.		
	PDR Region - Length Region is disabled by default. Displays Region size information when Binary input file is specified.		
	PDR Binary File Navigate to path to load pdrimage.bin file if required and available.	UP4 UP3	PDR.bin (Optional) PDR.bin (Optional)
	PDR Region Enable Values: Enabled/Disabled - This option allows the user to enable or disable the Platform Data Region. Note: If loading PDR.bin file, check that the PDR region is enabled in tool before building image.	UP4 UP3	Disabled Disabled



Table 2-4. - Flash Settings (Sheet 1 of 10)

Click on Flash Settings in the left tabs menu> Flash Components is expanded by default:			
<div> <div>Flash Components</div> <div>1</div> </div>			
Parameter	Value		
Number of Flash Components	1	Specifies the number of Flash components	
Flash component 1 Size	16MB	This field identifies the size of the 1st Flash component	
Flash component 2 Size	8MB	This field identifies the size of the 2nd Flash component	
SPI Global Protected Range	0x0	Sets the default value of the Global Protected Range register in the SPI Flash Controller.	
SPI Idle to Deep Power Down Timeout Default	0x5	Specifies the time in microseconds that the Flash Controller waits after all activity is idle before commanding the flash devices to Deep Power down, time = 2^N microseconds.	
SPI Out of Order operation Enabled	Yes	When this setting is enabled priority operations may be issued while waiting for write / erase operations to complete on the flash device. When this setting is disabled all write / erase type operations in order.	
SPI Resume Hold-off Delay	4us	This specifies the time after the completion of a pri_op before the flash controller sends the resume instruction. If a new pri_op is eligible to be issued prior to the end of this delay time then the pri_op is issued and the timer is reinitialized to tRHD. 3-bit field encodes count with range 0-7. tRHD = count * 2us.	
SPI Max write / erase Resume Delay	No Ceiling	This setting specifies the maximum value for the resume delay	
SPI Suspend / Resume Enabled	Yes	When this setting is enabled writes and erases are suspended when the flash device is in a suspend state	
Software Re-Binding Enabled	No	When enabled this settings will allow for S	

#	Parameter	Platform	Settings
1	Flash Components		
	Number of Components Values: 0, 1, 2 - This setting configures the total number of flash components for the platform. Note: Choosing a selection of '0' part will cause the Intel® FIT tool to build an output image containing only the Intel® ME region.	UP4 UP3	1 1
	Flash component 1 Size Values: 512KB, 1MB, 2MB, 4MB, 8MB, 16MB, 32MB, 64MB - This setting determines the size of Flash component 1 for the platform image.	UP4 UP3	32MB 32MB
	Flash component 2 Size Values: 512KB, 1MB, 2MB, 4MB, 8MB, 16MB, 32MB, 64MB - This setting determines the size of Flash component 2 for the platform image. Note: This setting is only applicable when the Number of Flash Components option is set to '2'.	UP4 UP3	Greyed Out Greyed Out
	SPI Global Protected Range - This sets the default value of the Global Protected Range register in the SPI Flash Controller.	UP4 UP3	0x0 0x0
	SPI Idle to Deep Power Down Timeout - This sets SPI Idle to Deep Power Down Timeout Default Specifies the time in microseconds that the Flash Controller waits after all activity is idle before commanding the flash devices to Deep Power down, time = 2^N microseconds.	UP4 UP3	0x5 0x5
	SPI Out of Order operation Enabled - When this setting is enabled priority operations may be issued while waiting for write / erase operations to complete on the flash device. When this setting is disabled all write / erase type operations in order.	UP4 UP3	Yes Yes
	SPI Resume Hold-off Delay - This specifies the time after the completion of a pri_op before the flash controller sends the resume instruction. If a new pri_op is eligible to be issued prior to the end of this delay time then the pri_op is issued and the timer is reinitialized to tRHD. 3-bit field encodes count with range 0-7. tRHD = count * 2us.	UP4 UP3	4us 4us



Table 2-4. - Flash Settings (Sheet 2 of 10)

	SPI Max write / erase Resume to Suspend intervals - This setting specifies the maximum value for the write and erase Resume to Suspend intervals.	UP4 UP3	No Ceiling No Ceiling															
	SPI Suspend / Resume Enabled - When this setting is enabled writes and erases may be suspended to allow a read to be issued on the flash device. When this setting is disabled no transaction will be allowed to the busy flash device.	UP4 UP3	Yes Yes															
	Software Re-Binding Enabled Values: Yes / No When enabled this settings will allow for SPI re-binding to a new PCH during manufacturing and re-manufacturing flows prior to platform EOM. Note: Re-binding to a replacement PCH can only be done a maximum of 5 times before the SPI part needs to be re-flashed.	UP4 UP3	No No															
Click on Flash Layout in the left tabs menu> BIOS Region is expanded by default:																		
<div>▼ Host CPU / BIOS Master Access <div>2</div></div> <table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>Host CPU / BIOS Write Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines write access control</td></tr><tr><td>Host CPU / BIOS Write Access Custom</td><td>0x0</td><td>This setting determines write access control</td></tr><tr><td>Host CPU / BIOS Read Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines read access control f</td></tr><tr><td>Host CPU / BIOS Read Access Custom</td><td>0x0</td><td>This setting determines read access control f</td></tr></tbody></table>				Parameter	Value	Help Text	Host CPU / BIOS Write Access Intel Recommended	0xFFFF	This setting determines write access control	Host CPU / BIOS Write Access Custom	0x0	This setting determines write access control	Host CPU / BIOS Read Access Intel Recommended	0xFFFF	This setting determines read access control f	Host CPU / BIOS Read Access Custom	0x0	This setting determines read access control f
Parameter	Value	Help Text																
Host CPU / BIOS Write Access Intel Recommended	0xFFFF	This setting determines write access control																
Host CPU / BIOS Write Access Custom	0x0	This setting determines write access control																
Host CPU / BIOS Read Access Intel Recommended	0xFFFF	This setting determines read access control f																
Host CPU / BIOS Read Access Custom	0x0	This setting determines read access control f																
#	Parameter	Platform	Settings															
<div>2</div>	Host CPU / BIOS Master Access																	
	Host CPU / BIOS Write Access Intel Recommended Values: 0xFFFF, 0x000A, 0x001A, 0x010A, 0x011A - This setting determines write access control for the BIOS region. 0xFFFF = Debug/Manufacturing 0x000A = Production 0x001A = Production with access to PDR (should ONLY be used if PDR region is implemented). 0x010A = Production with access to EC 0x011A = Production with access to EC and PDR Custom = User custom Host / BIOS Write Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0xFFFF 0xFFFF															
	Host CPU / BIOS Write Access Custom - This setting allows free form user customized Host CPU / BIOS Write Access regions permissions Note: This setting is grayed out unless Custom is selected under the Host CPU / BIOS Write Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input															



Table 2-4. - Flash Settings (Sheet 3 of 10)

	Host CPU / BIOS Read Access Values: 0xFFFF, 0x00F, 0x01F, 0x10F, 0x11F - This setting determines read access control for the BIOS region. 0xFFFF = Debug/Manufacturing 0x00F = Production 0x01F = Production with access to PDR (should ONLY be used if PDR region is implemented). 0x10F = Production with access to EC 0x11F = Production with access to EC and PDR Custom = User custom Host / BIOS Read Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide.	UP4 UP3	0xFFFF 0xFFFF															
	Host CPU / BIOS Read Access Custom - This setting allows free form user customized Host CPU / BIOS Read Access regions permissions Note: This setting is grayed out unless Custom is selected under the Host CPU / BIOS Read Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input															
Click on Flash Settings in the left tabs menu> Intel® ME Master Access is expanded by default:																		
<div><div>Intel(R) ME Master Access</div><div>3</div></div> <table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>Intel(R) ME Write Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines write access control for the ME region.</td></tr><tr><td>Intel(R) ME Write Access Custom</td><td>0x0</td><td>This setting determines read access control for the ME region.</td></tr><tr><td>Intel(R) ME Read Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines read access control for the ME region.</td></tr><tr><td>Intel(R) ME Read Access Custom</td><td>0x0</td><td>This setting determines read access control for the ME region.</td></tr></tbody></table>				Parameter	Value	Help Text	Intel(R) ME Write Access Intel Recommended	0xFFFF	This setting determines write access control for the ME region.	Intel(R) ME Write Access Custom	0x0	This setting determines read access control for the ME region.	Intel(R) ME Read Access Intel Recommended	0xFFFF	This setting determines read access control for the ME region.	Intel(R) ME Read Access Custom	0x0	This setting determines read access control for the ME region.
Parameter	Value	Help Text																
Intel(R) ME Write Access Intel Recommended	0xFFFF	This setting determines write access control for the ME region.																
Intel(R) ME Write Access Custom	0x0	This setting determines read access control for the ME region.																
Intel(R) ME Read Access Intel Recommended	0xFFFF	This setting determines read access control for the ME region.																
Intel(R) ME Read Access Custom	0x0	This setting determines read access control for the ME region.																
#	Parameter	Platform	Settings															
3	Intel® ME Master Access																	
	Intel® ME Write Access Intel Recommended Values: 0xFFFF, 0x0004 - This setting determines write access control for the ME region. 0xFFFF = Debug/Manufacturing 0x0004 = Production Custom = User custom Intel® ME Write Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0xFFFF 0xFFFF															
	Intel® ME Write Access Custom - This setting allows free form user customized Intel® ME Write Access regions permissions Note: This setting is grayed out unless Custom is selected under the Intel® ME Write Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input															



Table 2-4. - Flash Settings (Sheet 4 of 10)

	Intel® ME Read Access Intel Recommended Values: 0xFFFF, 0x000D - This setting determines read access control for the ME region. 0xFFFF = Debug/Manufacturing 0x000D = Production Custom = User custom Intel® ME Read Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0xFFFF 0xFFFF															
	Intel® ME Read Access Custom - This setting allows free form user customized Intel® ME Read Access regions permissions Note: This setting is grayed out unless Custom is selected under the Intel® ME Read Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input															
Click on Flash Settings in the left tabs menu> GbE Master Access is expanded by default:																		
<div><div>▼ GbE Master Access</div><div>4</div></div> <table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>GbE Write Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines read access control for the GB</td></tr><tr><td>GbE Write Access Custom</td><td>0x0</td><td>This setting determines read access control for the GB</td></tr><tr><td>GbE Read Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines read access control for the GB</td></tr><tr><td>GbE Read Access Custom</td><td>0x0</td><td>This setting determines read access control for the GB</td></tr></tbody></table>				Parameter	Value	Help Text	GbE Write Access Intel Recommended	0xFFFF	This setting determines read access control for the GB	GbE Write Access Custom	0x0	This setting determines read access control for the GB	GbE Read Access Intel Recommended	0xFFFF	This setting determines read access control for the GB	GbE Read Access Custom	0x0	This setting determines read access control for the GB
Parameter	Value	Help Text																
GbE Write Access Intel Recommended	0xFFFF	This setting determines read access control for the GB																
GbE Write Access Custom	0x0	This setting determines read access control for the GB																
GbE Read Access Intel Recommended	0xFFFF	This setting determines read access control for the GB																
GbE Read Access Custom	0x0	This setting determines read access control for the GB																
#	Parameter	Platform	Settings															
4	GbE Master Access																	
	GbE Write Access Intel Recommended Values: 0xFFFF, 0x0008 - This setting determines write access control for the Gigabit Ethernet Region. 0xFFFF = Debug/Manufacturing 0x0008 = Production Custom = User custom GbE Write Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0xFFFF 0xFFFF															
	GbE Write Access Custom - This setting allows free form user customized GbE Write Access regions permissions Note: This setting is grayed out unless Custom is selected under the GbE Write Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input															



Table 2-4. - Flash Settings (Sheet 5 of 10)

	GbE Read Access Intel Recommended Values: 0xFFFF, 0x0009 - This setting determines read access control for the Gigabit Ethernet Region. 0xFFFF = Debug/Manufacturing 0x0009 = Production Custom = User custom GbE Read Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0xFFFF 0xFFFF															
	GbE Read Access Custom - This setting allows free form user customized GbE Read Access regions permissions Note: This setting is grayed out unless Custom is selected under the GbE Read Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input															
Click on Flash Settings in the left tabs menu> EC Master Access is expanded by default:																		
<div><div>▼ EC Master Access</div><div>5</div></div> <table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>Embedded Controller Read Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines read access control</td></tr><tr><td>Embedded Controller Read Access Custom</td><td>0x0</td><td>This setting determines read access control</td></tr><tr><td>Embedded Controller Write Access Intel Recommended</td><td>0xFFFF</td><td>This setting determines write access control</td></tr><tr><td>Embedded Controller Write Access Custom</td><td>0x0</td><td>This setting determines write access control</td></tr></tbody></table>				Parameter	Value	Help Text	Embedded Controller Read Access Intel Recommended	0xFFFF	This setting determines read access control	Embedded Controller Read Access Custom	0x0	This setting determines read access control	Embedded Controller Write Access Intel Recommended	0xFFFF	This setting determines write access control	Embedded Controller Write Access Custom	0x0	This setting determines write access control
Parameter	Value	Help Text																
Embedded Controller Read Access Intel Recommended	0xFFFF	This setting determines read access control																
Embedded Controller Read Access Custom	0x0	This setting determines read access control																
Embedded Controller Write Access Intel Recommended	0xFFFF	This setting determines write access control																
Embedded Controller Write Access Custom	0x0	This setting determines write access control																
#	Parameter	Platform	Settings															
5	EC Master Access																	
	EC Write Access Intel Recommended Values: 0xFFFF, 0x0100 - This setting determines write access control for the Embedded Controller Region. 0xFFFF = Debug/Manufacturing 0x0100 = Production Custom = User custom EC Write Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0xFFFF 0xFFFF															
	EC Write Access Custom - This setting allows free form user customized EC Write Access regions permissions Note: This setting is grayed out unless Custom is selected under the EC Write Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input															



Table 2-4. - Flash Settings (Sheet 6 of 10)

	EC Read Access Intel Recommended Values: 0xFFFF, 0x0101, 0x0103 - This setting determines read access control for the Embedded Controller Region. 0xFFFF = Debug/Manufacturing 0x0101 = Production 0x0103 = Production with EC BIOS Read Access Custom = User custom EC Read Access values For further details on Region Access Control see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0xFFFF 0xFFFF
	EC Read Access Custom - This setting allows free form user customized EC Read Access regions permissions Note: This setting is grayed out unless Custom is selected under the EC Read Access Intel Recommended drop down menu. Warning: Setting region access permission values outside of Intel recommendation could result in compromised platform security	UP4 UP3	Hex Input

Click on Flash Layout in the left tabs menu> IUnit Sub-Partition is expanded by default:

▼ Flash Configuration

6

Parameter	Value	Help Text
Dual I/O Read Enable	Yes	This soft-strap only has effect if Dual I/O Read is discovered as suppo
Dual Output Read Enable	Yes	This soft-strap only has effect if Dual Output Read is discovered as su
Fast Read Clock Frequency	50MHz	This setting allows customers to configure the flash component clock
Fast Read Supported	Yes	This setting allows customers to enable support for Fast Read capabil
Invalid Instruction 0	0x21	This setting allows customers to configure invalid instruction to protec
Invalid Instruction 1	0x42	This setting allows customers to configure invalid instruction to protec
Invalid Instruction 2	0x60	This setting allows customers to configure invalid instruction to protec
Invalid Instruction 3	0xAD	This setting allows customers to configure invalid instruction to protec
Invalid Instruction 4	0xB7	This setting allows customers to configure invalid instruction to protec
Invalid Instruction 5	0xB9	This setting allows customers to configure invalid instruction to protec
Invalid Instruction 6	0xC4	This setting allows customers to configure invalid instruction to protec
Invalid Instruction 7	0xC7	This setting allows customers to configure invalid instruction to protec
Quad I/O Read Enable	Yes	This soft-strap only has effect if Quad I/O Read is discovered as supp
Quad Output Read Enable	Yes	This soft-strap only has effect if Quad Output Read is discovered as si
Read ID and Read Status Clock Frequency	50MHz	This setting allows customers to configure the flash component clock
Write and Erase Clock Frequency	50MHz	This setting allows customers to configure the flash component clock

#	Parameter	Platform	Settings
6	Flash Configuration		



Table 2-4. - Flash Settings (Sheet 7 of 10)

	Dual I/O Read Enabled Values: Yes/No - This setting allows the customer to enable support for Dual I/O Read capabilities for flash components. See Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	Yes Yes
	Dual Output Read Enabled Values: Yes/No - This setting allows the customer to enable support for Dual Output Read capabilities for flash components. See Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	Yes Yes
	Fast Read Clock Frequency Values: 14MHz, 25MHz, 33MHz, 50MHz, 100MHz - This setting allows the customer to configure the flash component clock frequency setting for Fast Read. See Rocket Lake LP SPI Programming guide for further details. Note: The 100MHz frequency setting not valid on client platforms	UP4 UP3	50MHz 50MHz
	Fast Read Supported Values: Yes/No - This setting allows the customer to enable support for Fast Read capabilities for flash components. See Tiger Lake LP SPI Programming guide for further details. Note: If fast read supported is set to "No" any changes made to Dual I/O, Quad I/O, Dual Output, or Quad Output will not be affected if set to yes. Fast read supported should also be set to enable frequencies greater than 20MHz.	UP4 UP3	Yes Yes
	Invalid Instruction 0 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x00000021 0x00000021
	Invalid Instruction 1 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x00000042 0x00000042
	Invalid Instruction 2 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x00000060 0x00000060
	Invalid Instruction 3 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x000000AD 0x000000AD
	Invalid Instruction 4 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x000000B7 0x000000B7
	Invalid Instruction 5 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x000000B9 0x000000B9
	Invalid Instruction 6 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x000000C4 0x000000C4
	Invalid Instruction 7 - This setting allows the customer to configure invalid instruction to protect against Chip Erase. See Tiger Lake LP SPI Programming guide for further details. Note: This setting should be set to '0' if there are not Invalid instructions.	UP4 UP3	0x000000C7 0x000000C7
	Quad I/O Read Enabled Values: Yes/No - This setting allows the customer to enable support for Quad I/O Read capabilities for flash components. See Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	Yes Yes
	Quad Output Read Enabled Values: Yes/No - This setting allows the customer to enable support for Quad Output Read capabilities for flash components. See Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	Yes Yes



Table 2-4. - Flash Settings (Sheet 8 of 10)

	Read ID and Read Status clock frequency Values: 14MHz, 25MHz, 33MHz, 50MHz, 100MHz- This setting allows the customer to configure the flash component clock frequency setting for Read ID and Read Status clock. See Rocket Lake LP SPI Programming guide for further details. Note: The 100MHz frequency setting not valid on client platforms	UP4 UP3	50MHz 50MHz
	Write and Erase clock frequency Values: 14MHz, 25MHz, 33MHz, 50MHz, 100MHz- This setting allows the customer to configure the flash component clock frequency setting for Write and Erase. See Rocket Lake LP SPI Programming guide for further details. Note: The 100MHz frequency setting not valid on client platforms	UP4 UP3	50MHz 50MHz

Click on Flash Settings in the left tabs menu> Legacy VSCC Table is expanded by default:

Legacy VSCC Table7

VSCC Entries8

W25Q128BV9Add VSCC Entry

Parameter	Value	Help Text
Part Name	W25Q128BV	This setting allow the OEM input a name designation for each flash...
Vendor ID	0xEF	This configures the JEDEC vendor specific byte ID of the SPI flash ...
Device ID 0	0x40	This configures the JEDEC device specific byte ID 0 of the SPI flas...
Device ID 1	0x19	This configures the JEDEC device specific byte ID 1 of the SPI flas...

#	Parameter	Platform	Settings
7	Legacy VSCC Table VSCC Entries		
	W25Q128BV		
8	VSCC Entries	UP4 UP3	
	Name - This setting allow the OEM input a name designation for each flash component being used. Note: This is a free form entry field it does not affect actual flash component operation.	UP4 UP3	Winbond Winbond
	Vendor ID - This configures the JEDEC vendor specific byte ID of the SPI flash component. See Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	0xEF 0xEF
	device ID 0 - This configures the JEDEC device specific byte ID 0 of the SPI flash component. See Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	0x40 0x40
	device ID 1 - This configures the JEDEC device specific byte ID 1 of the SPI flash component. See Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	0x19 0x19
9	+ Add VSCC Entry		

Click on Flash Settings in the left tabs menu> BIOS Configuration is expanded by default:



Table 2-4. - Flash Settings (Sheet 9 of 10)

▼ Bios Configuration

10

Parameter	Value	Help
BIOS Redundancy Assistance	Disabled	In case of BIOS boot failure, CSME will configure
Top Swap Block Size	128KB	This configures the Top Swap Block size for the p
BIOS Boot Select	Boot from SPI	This setting determines if BIOS will be booted fro

#	Parameter	Platform	
10	BIOS Configuration		
	BIOS Redundancy Assistance Values: Enabled, Disabled In cases of BIOS boot failure, Intel®CSME will configure the platform to boot with backup BIOS using Top Swap when this setting is enabled. <i>Note: This option is only applicable when Boot Guard is enabled.</i>	UP4 UP3	Disabled Disabled
	Top Swap Block Size Values: 64KB, 128KB, 256KB, 512KB, 1MB - This configures the Top Swap Block size for the platform. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	128KB 128KB
	BIOS Boot Select Values: Boot from SPI / Boot from LPC This setting determines if BIOS will be booted from LPC or SPI.	UP4 UP3	Boot from SPI Boot from SPI

Click on Flash Settings in the left tabs menu> BIOS Configuration is expanded by default:

▼ FPF Configuration

11

Parameter	Value	Help
Hardware Binding Enabled	Disabled	This setting configures the FPF Hardware

11	FPF Configuration		
	Hardware Binding Enabled Values: Enabled / Disabled This setting configures the FPF Hardware binding behavior for the platform image. If this setting is enabled FPF Hardware binding will occur when platform close manufacturing flow is executed with Intel® FPT. If this setting is disabled FPF Hardware binding will not take place when close manufacturing flow is executed. For Revenue parts this setting will be ignored and FPF Hardware binding will take place when close manufacturing flow is executed.	UP4 UP3	Disabled Disabled

Click on Flash Settings in the left tabs menu> RPMC Configuration is expanded by default:



Table 2-4. - Flash Settings (Sheet 10 of 10)

<div> <div>▼ RPMC Configuration</div> <div>12</div> </div>			
Parameter		Value	
RPMC Supported		No	This setting determines if RPMC is enable
RPMC Rebinding Enabled		No	This setting determines if Rebinding of R
12	RPMC Configuration		
	RPMC Supported Values: Yes / No This setting determines if RPMC is enabled. <i>Note: The SPI parts being used need to support RPMC In order to use this feature.</i>		UP4 UP3 No No
	RPMC Rebinding Enabled Values: Yes / No This setting determines if Rebinding of RPMC enabled SPI parts is enabled.		UP4 UP3 No No



Table 2-5. - Intel® ME Kernel (Sheet 1 of 4)

Click on Intel® ME Kernel in the left tabs menu> Processor is expanded by default:

▼ Processor

1

Parameter	Value	Help Text
Processor Emulation	No Emulation	-

#	Parameter	Platform	Settings
1	Processor		
	Processor Emulation Values: No Emulation EMULATE Intel® vPro (TM) capable Processor EMULATE Intel® Core (TM) branded Processor EMULATE Intel® Celeron (R) branded Processor EMULATE Intel® Pentium (R) branded Processor EMULATE Intel® Xeon (R) branded Processor EMULATE Intel® Xeon (R) Manageability capable Processor This setting determines processor type to be emulated on pre-production silicon. Set this parameter to the type of processor that the target system will use during production. This field will emulate that processor class for pre-production silicon. It is necessary to set this to Emulate Intel® vPro™ Processor in order to enable Intel® AMT.	UP4 UP3	EMULATE Intel® Core (TM) branded Processor EMULATE Intel® Core (TM) branded Processor

Click on Intel® ME Kernel in the left tabs menu> Intel® ME Firmware Update is expanded by default:

▼ Intel (R) ME Firmware Update

2

Parameter	Value	Help Text
Firmware Update OEM ID	00000000-0000-0000-0000-000...	-
Hide MEBx Firmware Update ...	No	-
Intel(R) ME Region Flash Prot...	Yes	-

#	Parameter	Platform	Settings
2	Intel® ME Firmware Update		
	Firmware Update OEM ID - This setting allows configuration of an OEM unique ID to ensure that customers can only update their platform with images from the OEM of the platform.	UP4 UP3	0 string 0 string
	Hide Intel® MEBx Firmware Update Control Values: Yes/No - This setting allows the customer to hide the Firmware Update option in the Intel® MEBx interface.	UP4 UP3	No No
	Intel® ME Region Flash Protection Override Values: Yes/No - This setting enables descriptor unlock of the Intel® CSME Region when the HMRFP0 message is sent to firmware prior to BIOS End of POST.	UP4 UP3	Yes Yes

Click on Intel® ME Kernel in the left tabs menu> Image Identification is expanded by default:



Table 2-5. - Intel® ME Kernel (Sheet 2 of 4)

▼ Image Identification

3

Parameter	Value	Help Text
OEM Tag	0x00000000	-

#	Parameter	Platform	Settings
3	Image Identification		
	OEM Tag - This is a free form 32bit field that allows the OEM to configure their own unique identifier in the firmware image.	UP4 UP3	0x00000000 0x00000000

Click on Intel® ME Kernel in the left tabs menu> Firmware Diagnostics is expanded by default:

▼ Firmware Diagnostics

4

Parameter	Value	Help Text
Automatic Built in Self Test	Disabled	-

#	Parameter	Platform	Settings
4	Firmware Diagnostics		
	Automatic Built in Self Test Values: Enabled/Disabled This setting enables the firmware Automatic Built in Self Test which is executed during first platform boot after initial image flashing.	UP4 UP3	Disabled Disabled

Click on Intel® ME Kernel in the left tabs menu> End of Manufacturing Configuration is expanded by default:

▼ End of Manufacturing Configuration

5

Parameter	Value	Help Text
EOM on First Boot Enabled	No	This setting determines if End of Manufacturing will
Flexible EOM setting options	Lock Descriptor and OEM Configs	This setting determines which settings will be auto

#	Parameter	Platform	Settings
5	End of Manufacturing Configuration		
	EOM of First Boot Enabled Value: Yes/No This setting determines if End of Manufacturing will be triggered on first boot of the platform after flashing. Note: When this setting is enabled Intel® CSME will enter End of Manufacturing regardless of the descriptor settings.	UP4 UP3	No No



Table 2-5. - Intel® ME Kernel (Sheet 3 of 4)

Flexible EOM setting options

Value: Lock Descriptor and OEM Configs/Lock OEM Configs Only/Lock Descriptor Only/Do not lock Descriptor and OEM Configs

This setting determines which settings will be automatically committed during End of Manufacturing flows. Note: The FPFs, RPMB / RPMC and set manufacturing mode settings are mandatory and cannot be overridden revenue parts. Simulation can be done on non-revenue part with the Hardware binding set to disabled.

UP4

UP3

Lock Descriptor and OEM Configs

Click on Intel® ME Kernel in the left tabs menu> MCTP Configuration is expanded by default:

▼ MCTP Configuration

6

Parameter	Value	Help Text
MCTP Stack Configuration	0x920030	Defines the ME's 8-bits MCTP Endpoint IDs for each SMBus physical interface (SMBus, ...
MctpDevicePortEc	0x02	-
MctpDevicePortSio	0x00	-
MctpDevicePortIsh	0x00	-
MctpDevicePortBmc	0x00	-

#	Parameter	Platform	Settings
6	MCTP Configuration		
	MCTP Stack Configuration Defines the Intel® ME's 8-bits MCTP Endpoint ID's for each SMBus physical interface (SMBus, SMLink0, and SMLink1). These values are needed for FW to communicate with MCTP end points. For each of these 3 bytes, a value of 0x00 means not used, and values 0xFF or 0x01 - 0x07 or 0x20 - 0x2F are not allowed.	UP4 UP3	0x920030 0x920030
	MctpdevicePortEc	UP4 UP3	0x02 0x02
	MctpdevicePortSio	UP4 UP3	0x00 0x00
	MctpdevicePortIsh	UP4 UP3	0x00 0x00
	MctpdevicePortBmc	UP4 UP3	0x00 0x00

Click on Intel® ME Kernel in the left tabs menu> Intel® ME Boot Configuration is expanded by default:

▼ Intel (R) ME Boot Configuration

7

Parameter	Value	
Persistent PRTC Backup Power	Exists	FPF that indicates if the device is desig

#	Parameter	Platform	Settings
---	-----------	----------	----------



Table 2-5. - Intel® ME Kernel (Sheet 4 of 4)

7	Intel® ME Boot Configuration								
	<p>Persistent PRTC Backup Power Values: None / Exists</p> <p>FPF that indicates if the device is designed such that it may lose PRTC power more than 10 times throughout the normal life-cycle of the product and hence has no persistent time or AR protection. At EOM this value is burned to the FPF, and can never be changed</p>	UP4 UP3	Exists Exists						
Click on Intel® ME Kernel in the left tabs menu> Intel® ME Assisted Boot Configuration is expanded by default:									
▼ Intel(R) ME Assisted Boot Configuration 8									
<table><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr><tr><td>Intel(R) ME Assisted BIOS Boot</td><td>Normal</td><td>This setting configures Intel(R) ME Assisted BIOS</td></tr></table>				Parameter	Value	Help Text	Intel(R) ME Assisted BIOS Boot	Normal	This setting configures Intel(R) ME Assisted BIOS
Parameter	Value	Help Text							
Intel(R) ME Assisted BIOS Boot	Normal	This setting configures Intel(R) ME Assisted BIOS							
8	Intel® ME Assisted Boot Configuration								
	<p>Intel Values: Normal / Intel® ME Assisted</p> <p>This setting configures Intel® ME Assisted BIOS Boot capabilities.</p> <p><i>Note: Leave this setting configured to "Normal"</i></p>	UP4 UP3	Normal Normal						
Click on Intel® ME Kernel in the left tabs menu> Reserved is expanded by default:									
▼ Reserved 9									
<table><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr><tr><td>Reserved</td><td>No</td><td>-</td></tr></table>				Parameter	Value	Help Text	Reserved	No	-
Parameter	Value	Help Text							
Reserved	No	-							
9	Reserved								
	<p>Reserved Values: Yes/No</p>	UP4 UP3	No No						



Table 2-6. - Intel® AMT (Sheet 1 of 8)

Click on Intel® AMT in the left tabs menu> Intel® AMT is expanded by default:			
<div> <div>▼ Intel(R) AMT Configuration</div> <div>1</div> </div>			
Parameter	Value	Help Text	
Intel(R) AMT Supported	Yes	This setting allows customers to disable Intel(R) AMT on	
Manageability Hardware Status	Enabled	This setting will permanently disable Intel(R) AMT hardw	
Intel(R) ME Network Services S...	Yes	This setting allows customers to enable / disable Intel(R)	
Manageability Application Supp...	Yes	This setting allows customers to permanently disable Int	
Manageability Application initial...	Enabled	This setting allows customers to determine the power up	
Intel(R) AMT Idle Timeout	0xFFFF	This setting configures the idle timeout value before Inte	
Intel(R) AMT Watchdog Autom...	No	This setting allows customers to enable the Intel (R) ME	
#	Parameter	Platform	Settings
1	Intel® AMT Configuration		
	Intel® AMT Supported Values: Yes/No - This setting allows customers to disable Intel® AMT on the platform and force the platform into Standard Manageability mode. Note: If this setting has been set to disabled Intel® AMT cannot be re-enabled once the descriptor has been locked. This setting applies to Desktop and Workstation only.	UP4 UP3	No No
	Manageability Hardware Status Values: Enabled / Disabled - This setting will permanently disable Manageability hardware through platform FPFs. At End-of-Manufacturing (EOM), enable/disable policy value is committed to FPF and can never be changed. Permanently disabling Manageability hardware with this setting requires "Manageability Application Supported" and "Disabled" and "Intel® ME Network Services Supported" are set to "No". Note: When "Manageability Application Hardware Status" is Enabled but "Manageability Application Supported" and "Intel® ME Network Services Supported" are set to "No", Manageability Hardware will be disabled by the Intel® CSME through CVAR.	UP4 UP3	Enabled Enabled
	Intel® ME Network Services Supported Values: Yes/No - This setting allows customers to enable / disable Intel® ME Network Services on the platform. Note: This setting and TLS needs to be enabled for proper operation of Intel® Authenticate (Corporate Only). In addition if this setting is disabled Intel® AMT will also be disabled.	UP4 UP3	No No
	Intel® Manageability Application Supported Values: Yes/No - This setting allows customers to force Intel® AMT enabled platforms to operate in Standard Manageability mode. Note: This setting only applies to Desktop and Workstation platforms.	UP4 UP3	No No
	Manageability Application initial power-up state Values: Enabled/Disabled This setting allows customers to determine the power up state for Intel® AMT or Standard Manageability. Note: If this setting is disabled Intel® AMT or Standard Manageability can still be re-enabled through the Intel® MEBx interface.	UP4 UP3	Disabled Disabled



Table 2-6. - Intel® AMT (Sheet 2 of 8)

#	Parameter	Platform	Settings									
	Intel® AMT Idle Timeout Values: 0xFFFF - This setting configures the idle timeout value before Intel® AMT enters into an off state.	UP4 UP3	0xFFFF 0xFFFF									
	Intel® AMT Watchdog Automatic Reset Enabled Values: Yes/No - This setting allows customers to enable the Intel® ME firmware to trigger an automatic platform reset if either the MEI or Agent Presence are in a hung state. Note: This feature only allows one reset at a time when the watchdog expires. After this feature has triggered a reset, it must be re-armed for reuse via management console.	UP4 UP3	No No									
Click on Intel® AMT in the left tabs menu> KVM Configuration is expanded by default:												
<div><div>▼ KVM Configuration</div><div>2</div><table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>Firmware KVM Screen Blanking</td><td>No</td><td>-</td></tr><tr><td>KVM Redirection Supported</td><td>Yes</td><td>-</td></tr></tbody></table></div>				Parameter	Value	Help Text	Firmware KVM Screen Blanking	No	-	KVM Redirection Supported	Yes	-
Parameter	Value	Help Text										
Firmware KVM Screen Blanking	No	-										
KVM Redirection Supported	Yes	-										
#	Parameter	Platform	Settings									
2	KVM Configuration											
	Firmware KVM Screen Blanking Values: Yes/No - This setting enables KVM Screen blanking capabilities in the firmware image. Note: This feature is dependent on processor level support.	UP4 UP3	No No									
	KVM Redirection Supported Values: Yes/No - This setting allows OEMs to enable / disable the KVM Redirection capabilities of the firmware. Note: If this setting has been set to disabled it cannot be re-enabled once the descriptor has been locked.	UP4 UP3	No No									
Click on Intel® AMT in the left tabs menu> Provisioning Configuration is expanded by default:												
<div><div>▼ Provisioning Configuration</div><div>3</div><table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>Embedded Host Based Config...</td><td>No</td><td>-</td></tr><tr><td>PKI Domain Name Suffix</td><td></td><td>-</td></tr></tbody></table></div>				Parameter	Value	Help Text	Embedded Host Based Config...	No	-	PKI Domain Name Suffix		-
Parameter	Value	Help Text										
Embedded Host Based Config...	No	-										
PKI Domain Name Suffix		-										
#	Parameter	Platform										
3	Provisioning Configuration											



Table 2-6. - Intel® AMT (Sheet 3 of 8)

	Embedded Host Based Configuration Values: Yes/No - This setting allows customers to enable / disable Embedded Host Based Configuration. Important - EHBC is primarily intended for use in embedded systems as it offers less user privacy/security protection than may be appropriate for business client systems. Note: The Intel® FIT tool will not adjust the Redirection Privacy/Security value based on selection here. Please set security level as needed.	UP4 UP3	No No
	PKI Domain Name Suffix - This setting allow OEMs to pre-configure the Domain Name Suffix used for PKI provisioning in their firmware image. Note: For normal out-of-box provisioning functionality this setting should be left empty.	UP4 UP3	- -

Click on Intel® AMT in the left tabs menu> OEM Customizable Certificate 1 is expanded by default:

▼ OEM Customizable Certificate 1

4

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Custo...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...

#	Parameter	Platform	Settings
4	OEM Customizable Certificate 1		
	Certificate Enabled Values: Yes/No - This setting allows customers to enable PKI provisioning Custom Certificate 1.	UP4 UP3	No No
	Certificate Friendly Name - This setting allows customers to assign a user friendly name for PKI provisioning Custom Certificate 1. Maximum of 32 characters.	UP4 UP3	- -
	Certificate Stream - This setting allows customers to input hash stream for PKI provisioning Custom Certificate 1. If enabled the certificate will be used in addition to those already pre-loaded in base firmware during provisioning. Note: If the platform is un-configured the Custom Certificate Hash will be deleted.	UP4 UP3	- -

Click on Intel® AMT in the left tabs menu> OEM Customizable Certificate 2 is expanded by default:

▼ OEM Customizable Certificate 2

5

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Custo...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...

#	Parameter	Platform	Settings
5	OEM Customizable Certificate 2		



Table 2-6. - Intel® AMT (Sheet 4 of 8)

	Certificate Enabled Values: Yes/No - This setting allows customers to enable PKI provisioning Custom Certificate 2.	UP4 UP3	No No
	Certificate Friendly Name - This setting allows customers to assign a user friendly name for PKI provisioning Custom Certificate 2. Maximum of 32 characters.	UP4 UP3	- -
	Certificate Stream - This setting allows customers to input hash stream for PKI provisioning Custom Certificate 2. If enabled the certificate will be used in addition to those already pre-loaded in base firmware during provisioning. Note: If the platform is un-configured the Custom Certificate Hash will be deleted.	UP4 UP3	- -

Click on Intel® AMT in the left tabs menu> OEM Customizable Certificate 3 is expanded by default:

▼ OEM Customizable Certificate 3

6

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Custo...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...

#	Parameter	Platform	Settings
6	OEM Customizable Certificate 3		
	Certificate Enabled Values: Yes/No - This setting allows customers to enable PKI provisioning Custom Certificate 3.	UP4 UP3	No No
	Certificate Friendly Name - This setting allows customers to assign a user friendly name for PKI provisioning Custom Certificate 3. Maximum 32 characters.	UP4 UP3	- -
	Certificate Stream - This setting allows customers to input hash stream for PKI provisioning Custom Certificate 3. If enabled the certificate will be used in addition to those already pre-loaded in base firmware during provisioning. Note: If the platform is un-configured the Custom Certificate Hash will be deleted.	UP4 UP3	- -

Click on Intel® AMT in the left tabs menu> OEM Default Certificate 1 is expanded by default:

▼ OEM Default Certificate 1

7

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Default...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...

#	Parameter	Platform	Settings
7	OEM Default Certificate 1		



Table 2-6. - Intel® AMT (Sheet 5 of 8)

	Certificate Enabled Values: Yes/No - This setting allows customers to enable PKI provisioning Default certificate 1.	UP4 UP3	No No
	Certificate Friendly Name - This setting allows customers to assign a user friendly name for PKI provisioning Default Certificate 1. Maximum 32 characters.	UP4 UP3	- -
	Certificate Stream - This setting allows customers to input hash stream for PKI provisioning custom certificate 1. Note: Default Certificates if enabled will be used in addition to those already pre-loaded in firmware during provisioning. Unlike Customizable Certificates the Default Certificates are not deleted when the platform is un-provisioned.	UP4 UP3	- -

Click on Intel® AMT in the left tabs menu> OEM Default Certificate 2 is expanded by default:

▼ OEM Default Certificate 2

8

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Default...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...

#	Parameter	Platform	Settings
8	OEM Default Certificate 2		
	Certificate Enabled Values: Yes/No - This setting allows customers to enable PKI provisioning Default certificate 2.	UP4 UP3	No No
	Certificate Friendly Name - This setting allows customers to assign a user friendly name for PKI provisioning Default Certificate 2. Maximum 32 characters.	UP4 UP3	- -
	Certificate Stream - This setting allows customers to input hash stream for PKI provisioning custom certificate 2. Note: Default Certificates if enabled will be used in addition to those already pre-loaded in firmware during provisioning. Unlike Customizable Certificates the Default Certificates are not deleted when the platform is un-provisioned.	UP4 UP3	- -

Click on Intel® AMT in the left tabs menu> OEM Default Certificate 3 is expanded by default:

▼ OEM Default Certificate 3

9

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Default...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...

#	Parameter	Platform	Settings
---	-----------	----------	----------



Table 2-6. - Intel® AMT (Sheet 6 of 8)

9

OEM Default Certificate 3

Certificate Enabled

Values: Yes/No - This setting allows customers to enable PKI provisioning Default certificate 3.

UP4

No

Certificate Friendly Name

- This setting allows customers to assign a user friendly name for PKI provisioning Default Certificate 3. Maximum 32 characters.

UP4

-

Certificate Stream

- This setting allows customers to input hash stream for PKI provisioning custom certificate 3.

Note: Default Certificates if enabled will be used in addition to those already pre-loaded in firmware during provisioning. Unlike Customizable Certificates the Default Certificates are not deleted when the platform is un-provisioned.

UP4

-

UP3

No

UP3

-

UP3

-

Click on Intel® AMT in the left tabs menu> OEM Default Certificate 4 is expanded by default:

▼ OEM Default Certificate 4

10

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Default...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...

#	Parameter	Platform	Settings
10	OEM Default Certificate 4		
	<div>Certificate Enabled</div> <div>Values: Yes/No - This setting allows customers to enable PKI provisioning Default certificate 4.</div>	UP4 UP3	No No
	<div>Certificate Friendly Name</div> <div>- This setting allows customers to assign a user friendly name for PKI provisioning Default Certificate 4.</div>	UP4 UP3	- -
	<div>Certificate Stream</div> <div>- This setting allows customers to input hash stream for PKI provisioning custom certificate 4.</div> <div>Note: Default Certificates if enabled will be used in addition to those already pre-loaded in firmware during provisioning. Unlike Customizable Certificates the Default Certificates are not deleted when the platform is un-provisioned.</div>	UP4 UP3	- -

Click on Intel® AMT in the left tabs menu> OEM Default Certificate 5 is expanded by default:

▼ OEM Default Certificate 5

11

Parameter	Value	Help Text
Certificate Enabled	No	This setting allows customers to enable PKI provisioning Default...
Certificate Friendly Name		This setting allows customers to assign a user friendly name for...
Certificate Stream		This setting allows customers to input hash stream for PKI provi...



Table 2-6. - Intel® AMT (Sheet 7 of 8)

#	Parameter	Platform	Settings									
11	OEM Default Certificate 5											
	Certificate Enabled Values: Yes/No - This setting allows customers to enable PKI provisioning Default certificate 5.	UP4 UP3	No No									
	Certificate Friendly Name - This setting allows customers to assign a user friendly name for PKI provisioning Default Certificate 5.	UP4 UP3	- -									
	Certificate Stream - This setting allows customers to input hash stream for PKI provisioning custom certificate 5. Note: Default Certificates if enabled will be used in addition to those already pre-loaded in firmware during provisioning. Unlike Customizable Certificates the Default Certificates are not deleted when the platform is un-provisioned.	UP4 UP3	- -									
Click on Intel® AMT in the left tabs menu> Redirection Configuration is expanded by default:												
<div>▼ Redirection Configuration12</div> <table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>Redirection Localized Language</td><td>English</td><td>This setting allows customers to configure which localized langu...</td></tr><tr><td>Redirection Privacy / Security ...</td><td>Default</td><td>This setting allows customers to configure the Privacy and Secu...</td></tr></tbody></table>				Parameter	Value	Help Text	Redirection Localized Language	English	This setting allows customers to configure which localized langu...	Redirection Privacy / Security ...	Default	This setting allows customers to configure the Privacy and Secu...
Parameter	Value	Help Text										
Redirection Localized Language	English	This setting allows customers to configure which localized langu...										
Redirection Privacy / Security ...	Default	This setting allows customers to configure the Privacy and Secu...										
#	Parameter	Platform	Settings									
12	Redirection Configuration											
	Redirection Localized Language - This setting allows customers to configure which localized language will be used initially by firmware for user consent output information (Examples: May be displayed before SOL / KVM session starts).	UP4 UP3	English English									
	Redirection Privacy / Security Level - This setting allows customers to configure the Privacy and Security level for redirection operations. Default enables all redirection ports (User consent is configurable). Enhanced - Enables all redirection ports. (User consent is required and cannot be disabled). Extreme - Disables Redirection and Remote Configuration / Client Control Mode. Note: The Intel® FIT tool will not adjust the Embedded Host Based Configuration value based on selection here. Please set EHBC to yes or no as needed.	UP4 UP3	Default Default									
Click on Intel® AMT in the left tabs menu> TLS Configuration is expanded by default:												
<div>▼ TLS Configuration13</div> <table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>Transport Layer Security Supp...</td><td>Yes</td><td>This setting allows customers to enable / disable firmware Trans...</td></tr></tbody></table>				Parameter	Value	Help Text	Transport Layer Security Supp...	Yes	This setting allows customers to enable / disable firmware Trans...			
Parameter	Value	Help Text										
Transport Layer Security Supp...	Yes	This setting allows customers to enable / disable firmware Trans...										
#	Parameter	Platform	Settings									
13	TLS Configuration											

**Table 2-6. - Intel® AMT (Sheet 8 of 8)**

	Transport Layer Security Supported Values: Yes/No - This setting allows customers to enable / disable firmware Transport Layer Security support. Note: If this is disabled TLS will be permanently disabled in the firmware image. This setting needs to be enabled along with along with the Intel® ME Network Services Supported for proper operation of the Intel® Authenticate (Corporate Only) feature.	UP4 UP3	No No



Table 2-7. - Platform Protection (Sheet 1 of 6)

Click on Platform Protection in the left tabs menu> Content Protection is expanded by default:

▼ Content Protection

1

Parameter	Value	Help
PAVP Supported	Yes	This setting determines if the Protected Audio Video Path (PAVP) feature will be permanently disabled in the FW image.
HDCP Internal Display Port 1 - 5K	PortA	This setting determines which port is connected for 5K output on the Internal Display 1.
HDCP Internal Display Port 2 - 5K	None	This setting determines which port is connected for 5K output on the Internal Display 2.

#	Parameter	Platform	Settings
1	Content Protection		
	PAVP Supported Values: Yes/No This setting determines if the Protected Audio Video Path (PAVP) feature will be permanently disabled in the FW image.	UP4 UP3	Yes Yes
	HDCP Internal Display Port 1 - 5K Values: None, Port A, Port B, Port C, Port D This setting determines which port is connected for 5K output on the Internal Display 1. Note: Both Display Port 1 & 2 need to be configured for proper operation.	UP4 UP3	PortA PortA
	HDCP Internal Display Port 2 - 5K Values: None, Port A, Port B, Port C, Port D This setting determines which port is connected for 5K output on the Internal Display 2. Note: Both Display Port 1 & 2 need to be configured for proper operation.	UP4 UP3	None None

Click on Platform Protection in the left tabs menu> Graphics uController is expanded by default:

▼ Graphics uController

2

Parameter	Value	Help
GuC Encryption Key	00 00 00 00 00 00 00 00 00 00 ...	This option is for entering the raw hash 256 bit string or certificate file for the Graphics uController.

#	Parameter	Platform	Settings
2	Graphics UController		
	GuC Encryption Key Values: This option is for entering the raw hash 256 bit string or certificate file for the Graphics uController.	UP4 UP3	0x00000000 0x00000000

Click on Platform Protection in the left tabs menu> Hash Key Configuration for Bootguard / ISH is expanded by default:



Table 2-7. - Platform Protection (Sheet 2 of 6)

▼ Hash Key Configuration for Bootguard / ISH 3			
Parameter	Value	Help Text	
OEM Public Key Hash	00 00 00 00 00 00 00 00 00 00 ...	Raw hash string for the SHA-384 hash of the OEM public	
OEM Key Manifest Binary		Signed manifest file containing hashes of keys used for si	
Second OEM key hash	00 00 00 00 00 00 00 00 00 00 ...	-	
Oem Key Revocation Enable	No	Enabling the OEM key revocation mechanism requires 'OE	

#	Parameter	Platform	
3	Hash Key Configuration for Bootguard / ISH		
	OEM Public Key Hash Values: This option is for entering the raw hash string or certificate file for Boot Guard and ISH. This 384-bit field represents the SHA-384 hash of the OEM public key corresponding to the private key used to sign the BIOS-SM or ISH image. Please see Appendix F for further details.	UP4 UP3	0x00000000 0x00000000
	OEM Key Manifest Binary Signed manifest file containing hashes of keys used for signing components of image. This setting is only configurable when OEM signing is enabled (See PlatformIntegrity / OemPublicKeyHash).	UP4 UP3	
	Second OEM Key hash Values: This option is for entering a secondary raw hash string or certificate file for Boot Guard and ISH used in instances of OEM Key Revocation. This 384-bit field represents the SHA-384 hash of the OEM public key corresponding to the private key used to sign the BIOS-SM or ISH image. Please see Appendix F for further details. Note: This setting is greyed out and not configurable until the Second OEM Key Revocation Enable is set to Yes.	UP4 UP3	0x00000000 0x00000000
	OEM Key Revocation Enabled Values: Yes/No This setting enables firmware OEM Key Revocation capabilities. Note: This setting requires that both OEM Public Key Hash and Second OEM Key Hash are configured.	UP4 UP3	No No

Click on Platform Protection in the left tabs menu> Boot Guard Configuration is expanded by default:

▼ Boot Guard Configuration 4		
Parameter	Value	
Key Manifest ID	0	ODM identifier used during th
Boot Guard Profile Configuration	Boot Guard Profile 0 - No_FVME	Boot Guard Profile 0 - Legacy
CPU Debugging	Enabled	This setting determines if CPI
BSP Initialization	Enabled	This setting determines BSP I
S3 Optimization	Enabled	This setting overrides Boot G



Table 2-7. - Platform Protection (Sheet 3 of 6)

#	Parameter	Platform	Settings												
4	Boot Guard Configuration														
	Key Manifest ID Values: This option is for entering the hash of another public key, used by the ACM to verify the Boot Policy Manifest.	UP4 UP3	0x0 0x0												
	Boot Guard Profile Configuration Values: Boot Guard Profile 0 - No_FVME Boot Guard Profile 3 - VM Boot Guard Profile 4 - FVE Boot Guard Profile 5 - FVME This option configures which Boot Guard Policy Profile will be used.	UP4 UP3	Boot Guard Profile 0 - No_FVME Boot Guard Profile 0 - No_FVME												
	CPU Debugging Values: Enabled/Disabled This setting determines if CPU debug modes will be displayed. When set to 'Enabled' CPU debugging is enabled.	UP4 UP3	Enabled Enabled												
	BSP Initialization Values: Enabled/Disabled This setting determines BSP behavior when it receives an INIT signal. When set to 'Enabled' BSP will behave normally if it receives an INIT (Disabled BSP Initialization (DBI) bit=0). When set to 'Disabled' BSP will shutdown if it receives an INIT ("DBI" bit=1).	UP4 UP3	Enabled Enabled												
	S3 Optimization Values: Enabled/Disabled This setting overrides Boot Guard S3 optimization. Note: This setting is for testing purposes only.	UP4 UP3	Enabled Enabled												
Click on Platform Protection in the left tabs menu> Type-C Firmware Anti-Rollback Configuration is expanded by default:															
<div>▼ Type-C Firmware Anti-Rollback Configuration</div> <div>5</div> <table><tr><th>Parameter</th><th>Value</th><th>Help</th></tr><tr><td>IO Manageability Engine Manifest Anti-Rollback Enabled</td><td>Yes</td><td>This setting enables Anti-Roll back for I</td></tr><tr><td>NPHY Manifest Anti-Rollback Enabled</td><td>Yes</td><td>This setting enables Anti-Roll back for I</td></tr><tr><td>Thunerbolt(TM) Manifest Anti-Rollback Enabled</td><td>Yes</td><td>This setting enables Anti-Roll back for I</td></tr></table>				Parameter	Value	Help	IO Manageability Engine Manifest Anti-Rollback Enabled	Yes	This setting enables Anti-Roll back for I	NPHY Manifest Anti-Rollback Enabled	Yes	This setting enables Anti-Roll back for I	Thunerbolt(TM) Manifest Anti-Rollback Enabled	Yes	This setting enables Anti-Roll back for I
Parameter	Value	Help													
IO Manageability Engine Manifest Anti-Rollback Enabled	Yes	This setting enables Anti-Roll back for I													
NPHY Manifest Anti-Rollback Enabled	Yes	This setting enables Anti-Roll back for I													
Thunerbolt(TM) Manifest Anti-Rollback Enabled	Yes	This setting enables Anti-Roll back for I													
#	Parameter	Platform	Settings												
5	Type-C Firmware Anti-Rollback Configuration														
	IO Manageability Engine Manifest Anti-Rollback Enabled Values: Yes/No This setting enables Anti-Rollback for the Type-C Subsystem I/O Manageability Engine binary.	UP4 UP3	Yes Yes												
	NPHY Manifest Anti-Rollback Enabled Values: Yes/No This setting enabled Anti-Rollback for the Type-C Subsystem NPHY binary.	UP4 UP3	Yes Yes												



Table 2-7. - Platform Protection (Sheet 4 of 6)

	Thunderbolt ^(TM) Manifest Anti-Rollback Enabled Values: Yes/No This	UP4 UP3	Yes Yes												
Click on Platform Protection in the left tabs menu> Intel® PTT Configuration is expanded by default:															
<div>▼ Intel(R) PTT Configuration 6</div> <table><thead><tr><th>Parameter</th><th>Value</th><th></th></tr></thead><tbody><tr><td>Intel(R) PTT Supported</td><td>Yes</td><td>This setting permanently disables</td></tr><tr><td>Intel(R) PTT initial power-up state</td><td>Enabled</td><td>-</td></tr><tr><td>Intel(R) PTT Supported [FPF]</td><td>Yes</td><td>This setting will permanently disa</td></tr></tbody></table>				Parameter	Value		Intel(R) PTT Supported	Yes	This setting permanently disables	Intel(R) PTT initial power-up state	Enabled	-	Intel(R) PTT Supported [FPF]	Yes	This setting will permanently disa
Parameter	Value														
Intel(R) PTT Supported	Yes	This setting permanently disables													
Intel(R) PTT initial power-up state	Enabled	-													
Intel(R) PTT Supported [FPF]	Yes	This setting will permanently disa													
#	Parameter	Platform	Settings												
6	Intel® PTT Configuration														
	Intel® PTT Supported Values: Yes/No - This setting permanently disables Intel® PTT in the firmware image.	UP4 UP3	Yes Yes												
	Intel® PTT initial power-up state Values: Enabled/Disabled - This setting determines if Intel® PTT is enabled on platform power-up.	UP4 UP3	Enabled Enabled												
	Intel® PTT Supported [FPF] Values: Yes/No - This setting will permanently disable Intel® PTT through platform FPFs. Caution: Setting this option to Yes will permanently disable Intel® PTT on the platform hardware.	UP4 UP3	Yes Yes												
Click on Platform Protection in the left tabs menu> TPM Over SPI Bus Configuration is expanded by default:															
<div>▼ TPM Over SPI Bus Configuration 7</div> <table><thead><tr><th>Parameter</th><th>Value</th><th>Help Text</th></tr></thead><tbody><tr><td>TPM Clock Frequency</td><td>14MHz</td><td>This setting determines the clock frequency setting to be used fo</td></tr><tr><td>TPM Over SPI Bus Enabled</td><td>Yes</td><td>This setting determines the clock frequency setting to be used fo</td></tr></tbody></table>				Parameter	Value	Help Text	TPM Clock Frequency	14MHz	This setting determines the clock frequency setting to be used fo	TPM Over SPI Bus Enabled	Yes	This setting determines the clock frequency setting to be used fo			
Parameter	Value	Help Text													
TPM Clock Frequency	14MHz	This setting determines the clock frequency setting to be used fo													
TPM Over SPI Bus Enabled	Yes	This setting determines the clock frequency setting to be used fo													
#	Parameter	Platform	Settings												
7	TPM Over SPI Bus Configuration														
	TPM Clock Frequency Values: 14MHz, 25MHz, 48MHz - This setting determines the clock frequency setting to be used for the TPM over SPI bus.	UP4 UP3	14MHz 14MHz												
	TPM Over SPI Bus Enabled Values: Yes/No - This setting determines if TPM over SPI bus is enabled on the platform.	UP4 UP3	No No												
Click on Platform Protection in the left tabs menu> BIOS Guard Configuration is expanded by default:															



Table 2-7. - Platform Protection (Sheet 5 of 6)

<div> <div>▼ BIOS Guard Configuration</div> <div>8</div> </div>											
<table> <tr> <th>Parameter</th><th>Value</th><th colspan="2">Help Text</th></tr> <tr> <td>BIOS Guard Protection Override Enabled</td><td>No</td><td colspan="2">This setting allows BIOS Guard to bypass SPI flash c</td></tr> </table>				Parameter	Value	Help Text		BIOS Guard Protection Override Enabled	No	This setting allows BIOS Guard to bypass SPI flash c	
Parameter	Value	Help Text									
BIOS Guard Protection Override Enabled	No	This setting allows BIOS Guard to bypass SPI flash c									
#	Parameter	Platform	Settings								
8	BIOS Guard Configuration										
	BIOS Guard Protection Override Enabled This setting allows BIOS Guard to bypass SPI flash controller protections (i.e. Protected Range Registers and Top Swap).	UP4 UP3	No No								
Click on Platform Protection in the left tabs menu> TXT Configuration is expanded by default:											
<div> <div>▼ TXT Configuration</div> <div>9</div> </div>											
<table> <tr> <th>Parameter</th><th>Value</th><th colspan="2">Help Text</th></tr> <tr> <td>TXT Supported</td><td>No</td><td colspan="2">This setting determines is enabled for the platform.</td></tr> </table>				Parameter	Value	Help Text		TXT Supported	No	This setting determines is enabled for the platform.	
Parameter	Value	Help Text									
TXT Supported	No	This setting determines is enabled for the platform.									
#	Parameter	Platform	Settings								
9	TXT Configuration										
	TXT Supported This setting determines if enabled for the platform.	UP4 UP3	No No								
Click on Platform Protection in the left tabs menu> Crypto Hardware Support is expanded by default:											
<div> <div>▼ Crypto Hardware Support</div> <div>10</div> </div>											
<table> <tr> <th>Parameter</th><th>Value</th><th colspan="2">Help Text</th></tr> <tr> <td>Crypto HW Support</td><td>Yes</td><td colspan="2">This setting can be used to disable crypto</td></tr> </table>				Parameter	Value	Help Text		Crypto HW Support	Yes	This setting can be used to disable crypto	
Parameter	Value	Help Text									
Crypto HW Support	Yes	This setting can be used to disable crypto									
#	Parameter	Platform	Settings								
10	Crypto HW Support										
	Crypto HW Support Values: Yes/No - This setting can be used to disable Intel® CSME cryptographic functionality. Caution: Configuring this setting to "No" will disables all Intel® CSME cryptographic related features.	UP4 UP3	Yes Yes								
Click on Platform Protection in the left tabs menu> Platform Trusted Device Setup Support is expanded by default:											



Table 2-7. - Platform Protection (Sheet 6 of 6)

<div> ▼ Platform Trusted Device Setup Support <div>11</div> </div>			
Parameter		Value	
Enable TDS Capabilities		No	This setting enables Intel(R) Trusted Device
#	Parameter	Platform	Settings
11	Platform Trusted Device Setup Support		
	Enable TDS Capabilities Values: Yes/No - This setting enables Intel® Trusted Device Setup on the platform.	UP4 UP3	No No
Click on Platform Protection in the left tabs menu> FuSa Configuration is expanded by default:			
<div> ▼ FuSa Configuration <div>12</div> </div>			
Parameter		Value	
FuSa Proof Tests Reporting I2C Interface		SMLink0	This setting determines which SMBus inter
FuSa Proof Tests MCU I2C Address		0x50	This setting configures the FuSa Proof Test
FuSa Proof Test Components		0x1780	This setting determines which FuSa tests v
#	Parameter	Platform	Settings
12	FuSa Configuration Note: The GBST sub-partition is used to enabling FuSa safety standards and is not applicable for client platforms.		
	FuSa Proof Tests Reporting I2C Interface Values:	UP4 UP3	SMLink0 SMLink0
	FuSa Proof Tests MCU I2C Address Values:	UP4 UP3	0x50 0x50
	FuSa Proof Tests Components Values:	UP4 UP3	0x1780 0x1780



Table 2-8. - Integrated Clock Controller (Sheet 1 of 7)

Click on Integrated Clock Controller in the left tabs menu> Integrated Clock Controller Policies are expanded by default:

▼ Integrated Clock Controller Policies

1

Parameter	Value	Help Text
Boot Profile	Profile 0	Profile applied during each boot.
Failsafe Boot Profile	Profile 0	Boot profile used when system instability is detected.
Profile Changeable	true	Allows user to change boot profile via BIOS menu or 3rd party appli...

#	Parameter	Platform	Settings
1	Integrated Clock Controller Policies		
	Boot Profile <p>This parameter allows user to select default profile to be used by the final generated SPI Flash binary image for the target platform at boot time.</p> <p>Selection is limited to the profiles defined under "Integrated Clock Controller Profiles" up to maximum 16 profiles. Profiles can be added by clicking on "Add profile" button under "Integrated Clock Controller Profiles".</p> <p>The 'Record #' refers to profile created under the "Integrated Clock Controller Profiles".</p> <p>Default boot profile for system is Profile 0.</p> <p>Double click on value column of this parameter to choose from available options.</p>	UP4 UP3	Profile 0 Profile 0
	Failsafe Profile <p>This parameter specifies the profile index of the fail-safe profile. On boot failure detection or CMOS clear the Intel® ME Firmware will revert to this profile if "Integrated Clock Controller Integrated Clock Controller Policies - Profile Changeable " is set to True. If profile Changeable parameter is set to False, User can not select Failsafe Boot Profile and profile 0 will be selected as a fail safe boot profile by default.</p> <p>The 'Record #' refers to profile created under the "Integrated Clock Controller Profiles".</p> <p>Default Failsafe boot profile for system is Profile 0.</p> <p>Double click on value column of this parameter to choose from available options.</p>	UP4 UP3	Profile 0 Profile 0
	Profile Changeable <p>Possible configuration: True/False.</p> <p>This parameter controls if BIOS or 3rd party application can select boot profile or not. When set to true, it allows user to change boot profile via BIOS or 3rd party application. When set to false, Runtime change to boot profile is not allowed and boot profile selected by "Integrated Clock Controller Integrated Clock Controller Policies - Boot Profile " parameter will be used to boot platform.</p> <p>Double click on value column of this parameter to choose from available options.</p>	UP4 UP3	True True

Click on Integrated Clock Controller in the left tabs menu> Profiles >Profile> Bclk Clock Configuration is expanded by default:



Table 2-8. - Integrated Clock Controller (Sheet 2 of 7)

▼ BCLK Clock Configurations

2

Parameter	Value	
BCLK Clock Configuration Enabled	Disabled	Enables/disables BCLK Clock configuration
BCLK Clock Frequency	100.000 MHz	Displays the nominal frequency for the sel
BCLK Spread setting	0.45 %	Displays the percentage of Spread setting

#	Parameter	Platform	Settings
2	BCLK Clock Configuration		
	BCLK Clock Configuration Enabled Values: Enabled / Disabled This setting enables / disables BCLK Clock configuration values for Adaptive / Overclocking profiles	UP4 UP3	Disabled Disabled
	BCLK Clock Frequency This parameter allows user to select the nominal frequency for the selected clock. Range is limited based on the Clock Range Definition record and HW SKU. Standard Setting Profile Type - Option is grayed out. Adaptive Setting Profile Type - Option is able to be edited.	UP4 UP3	N/A N/A
	BCLK Spread Setting This parameter allows user to select the percentage of Spread setting for the selected clock. Range is limited based on the Clock Range Definition record and HW SKU. BCLK Clock Frequency Standard Setting Profile Type - Option is grayed out. Adaptive Setting Profile Type - Option is able to be edited.	UP4 UP3	N/A N/A

Click on Integrated Clock Controller in the left tabs menu> Profiles are expanded by default:

▼ Profiles

Profile 0

4

+ Add Profile

▼ Profile

3

Parameter	Value	Help Text
Profile Name	Profile 0	Editable text string.
Profile Type	Standard	Specifies the profile. Intel (R) ME image has to be loaded to enable other ICC profile settings.



Table 2-8. - Integrated Clock Controller (Sheet 3 of 7)

#	Parameter	Platform	Settings
3	<p>Profiles - Profile 0</p> <p>Note: Intel® ME image has to be loaded to enable other ICC profile settings.</p> <p>For UP4/U, Intel® FIT provides 2 pre-defined ICC profiles to choose from.</p> <ul style="list-style-type: none"> •Standard: This profile provides default settings for standard configuration, no adaptive clocking is allowed. Platform clocks output internal and external are driven from USB3PCIE clock. Default clock frequency is 100 MHz with 0.47%DownSpread. BCLK clock source should be turned off in this case to save power. •Adaptive: This profile provides Wimax/3G friendly configuration. This profile will configure the platform based on the Adaptive profile allowing adaptive clocking adjustment for BCLK clock source to reduce EMI interference. It supports default clock frequency of 98.875 MHz with 0.48% Downspread. <p>For TGL UP3/UP4, Intel® FIT provides 5 pre-defined ICC profiles to choose from.</p> <ul style="list-style-type: none"> •Standard •Adaptive <p>Note: User can select pre-defined profiles via “Integrated Clock Controller Profiles - Profile Type” parameter</p> <p>User can add up to maximum 16 profiles.To add new profile, please use “Integrated Clock Controller Profiles - + Add Profile Button”</p>	UP4 UP3	Standard Standard
	<p>Profile Name</p> <p>This parameter allows user to customize profile name for easy identification. By default it uses pre-defined profile name like Profile 0.</p>	UP4 UP3	Profile 0 Profile 0
	<p>Profile Type</p> <p>Available ICC profiles for TGL UP3/UP4 are Standard, Adaptive.</p> <p>This parameter indicates which pre- defined profile selected for each profile#.</p> <p>Double click on value column of this parameter to choose from available options.</p>	UP4 UP3	Standard Standard
4	<p>+ Add Profile Button</p> <p>This button is used to add new ICC profile. User can add up to maximum 16 profiles. New profile will be added under “Integrated Clock Controller Profiles” tab.</p>	UP4 UP3	
Click on Integrated Clock Controller in the left tabs menu> Profiles >Profile> Clock Range Definition Record is expanded by default:			



Table 2-8. - Integrated Clock Controller (Sheet 4 of 7)

▼ Clock Range Definition Record

5

Parameter	Value	
BCLK PLL Clock Source Maximu...	100 MHz	Specifies the maximum frequency that ca
BCLK PLL Clock Source Minimu...	100 MHz	Specifies the minimum frequency that ca
BCLK SSC Halt Allowed	No	If set to Yes, the spread generator can b
BCLK SSC Maximum Percentage	0.50 %	Specifies the maximum precentage of sp

#	Parameter	Platform	Settings
5	Clock Range Definition Record		
	BCLK PLL Clock Source Maximum Frequency - This parameter allows user to specify the maximum frequency that can be applied to BCLK clock source when overclocking the platform. Value is limited by divider/frequency limits determined by HW SKU, and cannot be less than 100 MHz. Standard Setting Profile Type - Option is grayed out. Adaptive Setting Profile Type - Option is able to be edited.	UP4 UP3	
	BCLK PLL Clock Source Minimum Frequency - This parameter allows user to specify the minimum frequency that can be applied to BCLK clock source when underclocking the platform. Value is limited by divider/frequency limits determined by HW SKU, and cannot be greater than 100 MHz. Standard Setting Profile Type - Option is grayed out. Adaptive Setting Profile Type - Option is able to be edited.	UP4 UP3	
	BCLK SSC Halt Allowed - This parameter allows user to select if the spread generator can be disabled at runtime or not.if set to "True" , the spread generator can be enabled and disabled at runtime. Standard Setting Profile Type - Option is grayed out. Adaptive Setting Profile Type - Option is able to be edited.	UP4 UP3	
	BCLK SSC Percentage - This parameter Specifies the maximum percentage of spread adjustment that can be applied to the clock. Value is specified in 1/100th of percent(50=0.5%) Standard Setting Profile Type - Option is grayed out. Adaptive Setting Profile Type - Option is able to be edited.	UP4 UP3	

Click on Integrated Clock Controller in the left tabs menu> Profiles >Profile> Clock Output Configuration is expanded by default:



Table 2-8. - Integrated Clock Controller (Sheet 5 of 7)

▼ Clock Output Configuration

6

Parameter	Value	
SRC0	Enabled	Enable/Disable the CLKOUT_SRC0
SRC1	Enabled	Enable/Disable the CLKOUT_SRC1
SRC2	Enabled	Enable/Disable the CLKOUT_SRC2
SRC3	Enabled	Enable/Disable the CLKOUT_SRC3
SRC4	Enabled	Enable/Disable the CLKOUT_SRC4
SRC5	Enabled	Enable/Disable the CLKOUT_SRC5
SRC6	Enabled	Enable/Disable the CLKOUT_SRC6

#	Parameter	Platform	Settings
6	Clock Output Configuration		
	SRC0[6:15] Values: Enabled/Disabled These parameters come under the Power Management section and they control Enabling /Disabling of specific Output Clocks at boot time. These settings should match with platform hardware design. For CRB, recommend keeping defaults for bring up with Intel® CSME FW. These parameters are specifically used to Enable/Disable the respective CLKOUT_XXX differential output buffers	UP4 UP3	Enabled Enabled
	SRC1 Values: Enabled/Disabled Enables or Disables the CLKOUT_SRC1 differential output buffer.	UP4 UP3	Enabled Enabled
	SRC2 Values: Enabled/Disabled Enables or Disables the CLKOUT_SRC2 differential output buffer.	UP4 UP3	Enabled Enabled
	SRC3 Values: Enabled/Disabled Enables or Disables the CLKOUT_SRC3 differential output buffer.	UP4 UP3	Enabled Enabled
	SRC4 Values: Enabled/Disabled Enables or Disables the CLKOUT_SRC4 differential output buffer.	UP4 UP3	Enabled Enabled
	SRC5 Values: Enabled/Disabled Enables or Disables the CLKOUT_SRC5 differential output buffer.	UP4 UP3	Disabled Disabled
	SRC6 Values: Enabled/Disabled Enables or Disables the CLKOUT_SRC6 differential output buffer.	UP4 UP3	Disabled Disabled



Table 2-8. - Integrated Clock Controller (Sheet 6 of 7)

Click on Integrated Clock Controller in the left tabs menu> Profiles >Profile> Power Management Configuration is expanded by default:			
<div> <div>▼ Power Management Configuration</div> <div>7</div> </div>			
Parameter		Value	
SRC0 CLKREQ# Mapping		GPP_D5	Assign the CLKREQ# signal associat
SRC1 CLKREQ# Mapping		GPP_D6	Assign the CLKREQ# signal associat
SRC2 CLKREQ# Mapping		GPP_D7	Assign the CLKREQ# signal associat
SRC3 CLKREQ# Mapping		GPP_D8	Assign the CLKREQ# signal associat
SRC4 CLKREQ# Mapping		GPP_H10	Assign the CLKREQ# signal associat
SRC5 CLKREQ# Mapping		GPP_H11	Assign the CLKREQ# signal associat
SRC6 CLKREQ# Mapping		GPPC_F19	Assign the CLKREQ# signal associat
#	Parameter	Platform	Settings
7	Profile Power Management Configuration Configuring CLKREQ# and assigning GPIO depends on how CLKOUT_SRCx configuration via FIT is done (Enabled or Disabled) and if CLKREQ is required or not. Please refer to Appendix B.3 (How to configure CLKREQ# parameters) for the detail of CLKREQ configuration for SRC Output clocks. Please configure CLKREQ parameters accordingly.		
	SRC0[5:0] CLKREQ# Mapping Possible configuration: Select one of the GPIOs from the list to map it as a CLKREQ# for specific SRC# Output clock. This parameter controls association of dynamic CLKREQ control with SRC (PCIe) clocks. SRC[15:6] CLKREQ# Mapping - TGL/CFL H/S Only Possible configuration: Select one of the GPIOs from the list to map it as a CLKREQ# for specific SRC# Output put clock. This parameter controls association of dynamic CLKREQ control with SRC (PCIe) clocks.	UP4 UP3	GPP_D5 GPP_D5
	SRC1 CLKREQ# Mapping Assign the CLKREQ# signal associated with CLKOUT_SRC1.	UP4 UP3	GPP_D6 GPP_D6
	SRC2 CLKREQ# Mapping Assign the CLKREQ# signal associated with CLKOUT_SRC2.	UP4 UP3	GPP_D7 GPP_D7
	SRC3 CLKREQ# Mapping Assign the CLKREQ# signal associated with CLKOUT_SRC3.	UP4 UP3	GPP_D8 GPP_D8
	SRC4 CLKREQ# Mapping Assign the CLKREQ# signal associated with CLKOUT_SRC4.	UP4 UP3	GPP_H10 GPP_H10
	SRC5 CLKREQ# Mapping Assign the CLKREQ# signal associated with CLKOUT_SRC5.	UP4 UP3	GPP_H11 GPP_H11



Table 2-8. - Integrated Clock Controller (Sheet 7 of 7)

	SRC6 CLKREQ# Mapping Assign the CLKREQ# signal associated with CLKOUT_SRC6.	UP4 UP3	GPP_F19 GPP_F19						
Click on Integrated Clock Controller in the left tabs menu> Profiles >Profile> PCIe RefClock Configuration is expanded by default:									
<div><div>▼ PCIe RefClock Configuration</div><div><div></div><table><tr><th>Parameter</th><th>Value</th><th></th></tr><tr><td>SSCEN</td><td>Enabled</td><td>-</td></tr></table></div></div>				Parameter	Value		SSCEN	Enabled	-
Parameter	Value								
SSCEN	Enabled	-							
#	Parameter	Platform	Settings						
<div>8</div>	PCIe RefClock Configuration								
	SSCEN Values: Enabled / Disabled	UP4 UP3	Enabled Enabled						

Table 2-9. - Networking & Connectivity (Sheet 1 of 5)

Click on Networking & Connectivity in the left tabs menu> Discrete vPro NIC is expanded by default:

▼ Platform vPro 2.5G Wired LAN (i.e. I225)

1

Parameter	Value	Help Text
Platform vPro 2.5G Wired LAN Enabled	No	YES = Discrete NIC enabled in platform NC
Platform vPro 2.5G Wired LAN SMBUS slave address	0x0	Platform discrete NIC slave address Note:

#	Parameter	Platform	Settings
1	Platform vPro 2.5G Wired LAN		
	Platform vPro 2.5G Wired LAN Enabled Values: Yes / No This setting enables / disables Discrete Intel® vPro Network adapter support on the platform.	UP4 UP3	No No
	Platform vPro 2.5G Wired LAN slave SMBus Address Values: Hex This setting configures the SMBus address for the Discrete Intel® vPro Network adapter.	UP4 UP3	0x49 0x49

Click on Networking & Connectivity in the left tabs menu> Docking Station is expanded by default:



Table 2-9. - Networking & Connectivity (Sheet 2 of 5)

▼ Intel vPro (TM) for Thunderbolt (TM) 3/ USB-C Dock station 2			
Parameter	Value	Help T	
vPro Dock Enabled	No	YES = Enables communication with, vPro supportir	
vPro 2.5G Wired LAN on dock slave SMBUS Address	0x0	Dock NIC slave address Note: Input needs to be in	
Type-C Port1 Re-Timer I2C Address	0x20	This setting configures the Intel(R) SMBus I2C Add	
Type-C Port2 Re-Timer I2C Address	0x21	This setting configures the Intel(R) SMBus I2C Add	
Type-C Port3 Re-Timer I2C Address	0x22	This setting configures the Intel(R) SMBus I2C Add	
Type-C Port4 Re-Timer I2C Address	0x23	This setting configures the Intel(R) SMBus I2C Add	

#	Parameter	Platform	Settings
2	Intel vPro^(TM) for Thinderbolt 3^(TM) / USB-C Dock Station		
	vPro Dock Enabled This setting enables Intel® vPro communication over supported NIC in a Thunderbolt™ Dock.	UP4 UP3	No No
	vPro 2.5G Wired LAN on dock slave SMBus Address This setting configures the NIC SMBus slave address.	UP4 UP3	0x0 0x0
	Type-C Port1 Re-Timer I2C Address This setting configures Intel® SMBus I2C Address.	UP4 UP3	0x20 0x20
	Type-C Port2 Re-Timer I2C Address This setting configures Intel® SMBus I2C Address.	UP4 UP3	0x21 0x21
	Type-C Port3 Re-Timer I2C Address This setting configures Intel® SMBus I2C Address.	UP4 UP3	0x22 0x22
	Type-C Port4 Re-Timer I2C Address This setting configures Intel® SMBus I2C Address.	UP4 UP3	0x23 0x23

Click on Networking & Connectivity in the left tabs menu> Wired LAN Configuration is expanded by default:



Table 2-9. - Networking & Connectivity (Sheet 3 of 5)

▼ Wired LAN Configuration 3			
Parameter	Value		
LAN Power Well	SLP_LAN#	This setting allows the customer to co	
LAN PHY Power Up Time	100ms	This bit determines how long the dela	
Intel(R) Integrated Wired LAN Enabled	Yes	This setting allows customers to enab	
GbE PCIe Port Select	Port8	This setting allows customers to confi	
GbE PHY SMBus Address	0x64	This is the Intel PHY SMBus address.	
GbE MAC SMBus Address Enabled	Yes	This enables the Intel(R) Integrated W	
GbE MAC SMBus Address	0x70	This setting configures Intel(R) Integri	
PHY Connection	No PHY Connected	This selects which SMBus network is i	
LAN PHY Power Control GPD11 Signal Configuration	Enable as LANPHYPC	This setting allows the user to assign	

#	Parameter	Platform	Settings
3	Wired LAN Configuration		
	LAN Power Well Values: Core Well, Sus Well, ME Well, SLP_LAN - This setting allows customers to configure the power well that will be used by Intel® Integrated LAN. Note: Recommended setting is SLP_LAN#.	UP4 UP3	SLP_LAN# SLP_LAN#
	LAN PHY Power Up Time Values: 50ms, 100ms	UP4 UP3	100ms 100ms
	Intel® Integrated Wired LAN Enable Values: Enabled/Disabled - This setting enables or disables the Intel® Integrated LAN.	UP4 UP3	Enabled Enabled
	GbE PCIe Port Select Values: None, PORT7, PORT8, PORT9 - This setting allows customers to configure the PCIe Port that will Intel® Integrated LAN will operate on.	UP4 UP3	Port 7 Port 7
	GbE PHY SMBus Address This setting configures Intel® Integrated Wired LAN SMBus address to accept SMBus cycles from the MAC. Note: Recommended setting is 64h.	UP4 UP3	0x64 0x64
	GbE SMBus Address Enabled Values: Yes/No - This enables the Intel® Integrated Wired LAN MAC SMBus address. Note: This setting must be enabled if using Intel® Integrated LAN.	UP4 UP3	Yes Yes
	GbE MAC SMBus Address	UP4 UP3	0x70 0x70
	PHY Connection Values: No PHY connected, PHY on SMLink0	UP4 UP3	PHY on SMLink0 PHY on SMLink0
	LAN PHY Power Control GPD11 Signal Configuration Values: GPD11, LANPHYPC - This setting allows the customer to assign the LAN PHY Power Control signal to GbE or as GDP11. Note: If using Intel® Integrated LAN this setting should be set to "Enable as LANPHYPC".	UP4 UP3	LANPHYPC LANPHYPC

Click on Networking & Connectivity in the left tabs menu> Wireless LAN Configuration is expanded by default:



Table 2-9. - Networking & Connectivity (Sheet 4 of 5)

▼ Wireless LAN Configuration 4			
Parameter	Value		
Intel(R) ME CLINK Signal Enabled	Yes	This setting allows customers to enable / dis	
WLAN Microcode	0x9DF0 PULSAR	This setting allows OEMs to configure which	
WLAN Power Well	SLP_WLAN#	-	
On Die CLINK Enabled	Enabled	This setting determines whether the interna	
SLP_WLAN# / GDP9 Signal Con...	Enable as SLP_WLAN#	This setting allows user the to assign the WI	
#	Parameter	Platform	Settings
4	Wireless LAN Configuration		
	CLINK Enabled Values: Yes/No This setting allows customers to enable / disable the Wireless LAN CLINK signal through Intel® CSME firmware. Note: For using Intel® vPro Wireless solutions this should be set to "Yes".	UP4 UP3	No No
	WLAN Microcode This setting allow OEMs to configure which Intel® Wireless LAN card microcode to load into the firmware image.	UP4 UP3	0xA0F0 0xA0F0
	WLAN Power Well Values: Disabled, Sus Well, ME Well, SLP_M# SPDA, SLP_WLAN# This setting allows OEMs to configure the power well that will be used by Intel® Wireless LAN. WLAN Sleep via SLP_WLAN# (default) Note: Recommended setting is SLP_WLAN#.	UP4 UP3	SLP_WLAN# SLP_WLAN#
	On Die CLINK Enabled Values: Enabled/Disabled This setting determines if the internal CNVi / On-die CLINK port is enabled.	UP4 UP3	Enabled Enabled
	SLP_WLAN# / GPD9 Signal Configuration Values: SLP_WLAN#, GPD9 This setting allows the customer to assign the WLAN Power Control signal to WLAN or as GDP9. Note: If using Intel® Wireless LAN this setting should be set to "Enable as SLP_WLAN#".	UP4 UP3	Enable as SLP_WLAN# Enabled as SLP_WLAN #
Click on Networking & Connectivity in the left tabs menu> Time Sensitive Networking Configuration is expanded by default:			
▼ Time Sensitive Networking Configuration 5			
Parameter	Value		
Time Sensitive Networking	TSN Disabled	This setting allows customers to enable / di	
TSN GbE Port Select	None	This setting allows customers to configure t	



Table 2-9. - Networking & Connectivity (Sheet 5 of 5)

#	Parameter	Platform	Settings
5	Time Sensitive Networking Configuration		
	Time Sensitive Networking Values: TSN Enable / TSN Disabled Note: Time Sensitive Networking and Wired LAN are mutually exclusive only one of these features can be enabled on the platform.	UP4 UP3	Disabled Disabled
	TSN GbE PCIe Port Select Values: None, TSN PORT6, TSN PORT 7 - This setting allows customers to configure the PCIe port that TSN will operate on. Note: The Intel® Integrated LAN and TSN GbE are mutually exclusive.	UP4 UP3	None None



Table 2-10. - Internal PCH Buses (Sheet 1 of 5)

Click on Internal PCH Buses in the left tabs menu> PCH Timer Configuration is expanded by default:			
<div> <div>▼ PCH Timer Configuration</div> <div>1</div> </div>			
Parameter		Value	
PCH clock output stable to PROCPWRGD high (tPCH45)		1ms	This setting configures the m
PCIe Power Stable Timer (tPCH33)		Disabled	This setting configures the er
PROCPWRGD and SYS_PWROK high to SUS_STAT# de-assertion (tPCH46)		1ms	This setting configures the m
APWROK Timing		2ms	This soft strap determines th
Over Clocking Watchdog Self Start Enable		OC WDT Disabled	This setting affect whether th
#	Parameter	Platform	Settings
1	PCH Timer Configuration		
	PCH clock output stable to PROCPWRGD high (tPCH45) Values: 100ms, 50ms, 5ms, 1ms - This setting configures the minimum timing from XCK_PLL locked to CPUPWRGD high. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	1ms 1ms
	PCIe Power Stable Timer (tPCH33) Values: Enabled/Disabled - This setting configures the enables / disables the t36 timer. When enabled PCH will count 99ms from PWROK assertion before PLTRST# is de-asserted. Note: The recommended setting is "Disabled".	UP4 UP3	Disabled Disabled
	PROCPWRGD and SYS_PWROK high to SUS_STAT# de-assertion (tPCH46) Values: 1ms, 2ms, 5ms - This setting configures the minimum timing from CPUPWRGD assertion to SUS_STAT#. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	1ms 1ms
	APWROK Timing Values: 2ms, 4ms, 8ms, 15ms - This soft strap determines the time between the SLP_A# pin de-asserting and the APWROK timer expiration. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	2ms 2ms
	Over Clocking Watchdog Self Start Enable Values: OC WDT Disabled, OC WDT 3 Second Timeout, OC WDT 5 Second Timeout, OC WDR 10 Second Timeout, OC WDT 15 Second Timeout, OC WDT 30 Second Timeout, OC WDT 45 Second Timeout, OC WDT 60 Second Timeout - This setting affect whether the Over Clocking Watchdog Timer is enabled to automatically start on Host power cycle	UP4 UP3	OC WDT Disabled OC WDT Disabled
Click on Internal PCH Buses in the left tabs menu> SMBus / SMLink Configuration is expanded by default:			



Table 2-10. - Internal PCH Buses (Sheet 2 of 5)

▼ SMBus / SMLink Configuration 2			
Parameter	Value		
Intel(R) SMLink0 MCTP Address Enabled	No	This setting enables / disables the Intel(R) SMLink0 MCTP	
Intel(R) SMLink0 MCTP Address	0x0	This setting configures the Intel(R) SMLink0 MCTP Address	
Intel(R) SMBus ASD Address	0x0	This setting configures the Intel(R) SMBus Alert Sending	
Intel(R) SMBus ASD Address Enabled	No	This setting enables / disables the Intel(R) SMBus Alert Sending	
Intel(R) SMBus Subsystem Vendor and Device ID for ASF	0x0	This setting configures the Intel(R) SMBus Subsystem Vendor and Device ID for ASF	
Intel(R) SMBus I2C Address	0x0	This setting configures the Intel(R) SMBus I2C Address.	
Intel(R) SMBus I2C Address Enabled	No	This setting enables / disables the Intel(R) SMBus I2C Address.	
Intel(R) SMBus MCTP Address	0x0	This setting configures the Intel(R) SMBus MCTP Address.	
Intel(R) SMBus MCTP Address Enabled	No	This setting enables / disables the Intel(R) SMBus MCTP Address.	
SMBus / SMLink TCO Slave Connection	Intel(R) SMBus	This setting configures the TCO Slave connection to the SMBus / SMLink	
SMLink0 Enabled	Yes	This setting enables / disables SMLink0 interface. For further details see	
SMLink0 Frequency	1 MHz	This setting determines the frequency at which the SMLink0 interface	
SMLink1 I2C Target Address	0x0	This setting configures SMLink1 I2C Target Address. For further details see	
SMLink1 I2C Target Address Enabled	No	This setting configures SMLink1 I2C Target Address. For further details see	
SMLink1 GP Target Address	0x0	This setting configures SMLink1 GP Target Address. For further details see	
SMLink1 GP Target Address Enabled	No	This setting enables / disables SMLink1 GP Target Address. For further details see	
SMLink1 Enabled	No	This setting enables / disables SMLink1 interface. For further details see	
SMLink1 MCTP Address	0x0	This setting configures the Intel(R) SMBus MCTP Address.	
SMLink1 MCTP Address Enabled	No	This setting enables / disables the Intel(R) SMBus MCTP Address.	
SMLink1 Frequency	100 KHz	This setting determines the frequency at which the SMLink1 interface	
Intel(R) SMBus ASD Mode Configuration	Enable as GPP_C2	This setting determines the native mode of operation for the Intel(R) SMBus ASD	
SMLink0 I2C Address	0x0	This setting configures the SMLink0 I2C Address. Note: This setting is only used for testing.	
SMLink0 I2C Address Enabled	No	This setting enables / disables the SMLink0 I2C Address. Note: This setting is only used for testing.	

#	Parameter	Platform	Settings
2	SMBus / SMLink Configuration		
	Intel® SMLink0 MCTP Address This setting configures the Intel® SMLink0 MCTP Address. Note: This setting is only used for testing.	UP4 UP3	0x0 0x0
	Intel® SMLink0 MCTP Address Enabled Value: Yes/No This setting configures the Intel® SMLink0 MCTP Address. Note: This setting is only used for testing.	UP4 UP3	No No
	Intel® SMBus ASD Address - This setting configures the Intel® SMBus Alert Sending device Address. For details see Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	0x0 0x0



Table 2-10. - Internal PCH Buses (Sheet 3 of 5)

#	Parameter	Platform	Settings
	Intel® SMBus ASD Address Enabled Values: Yes/No - This setting enables / disables the Intel® SMBus Alert Sending device. For details see Tiger Lake LP SPI Programming guide for further details.	UP4 UP3	No No
	Intel® SMBus Subsystem Vendor & device ID for ASF - This setting configures the Intel® SMBus Subsystem Vendor & device ID for ASF. For details see Tiger Lake LP SPI Programming guide further details.	UP4 UP3	0x0 0x0
	Intel® SMBus I2C Address - This setting configures the Intel® SMBus I2C Address. Note: This setting is only used for testing purposes. The recommended setting is "0000000".	UP4 UP3	0x0 0x0
	Intel® SMBus I2C Address Enabled Values: Yes/No - This setting enables / disables the Intel® SMBus I2C Address. Note: This setting is only used for testing purposes. The recommended setting is "No".	UP4 UP3	No No
	Intel® SMBus MCTP Address - This setting configures the Intel® SMBus MCTP Address. Note: This setting is only used for testing purposes. The default setting is "0000000".	UP4 UP3	0x0 0x0
	Intel® SMBus MCTP Address Enabled Values: Yes/No - This setting enables / disables the Intel® SMBus MCTP Address. Note: This setting is only used for testing purposes. The recommended setting is "No".	UP4 UP3	No No
	SMBus / SMLink TCO Slave Connection Values: Intel® SMBus, SMLink0 - This setting configures the TCO Slave connection to either the Intel® SMBus or SMLink0. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	Intel® SMBus Intel® SMBus
	SMLink0 Enabled Values: Yes/No - This setting enables / disables SMLink0 interface. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	Yes Yes
	SMLink0 Frequency Values: 100KHz, 400KHz, 1 MHz - This setting determines the frequency at which the SMLink0 will operate. Note: The recommended setting is "1MHz".	UP4 UP3	1 MHz 1 MHz
	SMLink1 I2C Target Address - This setting configures SMLink1 I2C Target Address. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	0x0 0x0
	SMLink1 I2C Target Address Enabled Values: Yes/No - This setting configures SMLink1 I2C Target Address. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	No No
	SMLink1 GP Target Address - This setting configures SMLink1 GP Target Address. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	0x0 0x0
	SMLink1 GP Target Address Enabled Values: Yes/No - This setting enables / disables SMLink1 GP Target Address interface. For further details see Tiger Lake LP Platform Controller Hub EDS. Note: This setting must be set to "Yes" if using PCH / MCP Thermal reporting.	UP4 UP3	Yes Yes
	SMLink1 Enabled Values: Yes/No - This setting enables / disables SMLink1 interface. For further details see Tiger Lake LP Platform Controller Hub EDS. Note: This setting must be set to "Yes" if using PCH / MCP Thermal reporting.	UP4 UP3	Yes Yes
	SMLink1 MCTP Address - This setting configures the SMLink1 MCTP Address. Note: This setting is only used for testing purposes. The default setting is "0000000".	UP4 UP3	0x0 0x0
	SMLink1 MCTP Address Enabled Values: Yes/No - This setting enables / disables the SMLink1 MCTP Address. Note: This setting is only used for testing purposes. The recommended setting is "No".	UP4 UP3	No No
	SMLink1 Frequency Values: 100KHz, 400KHz, 1 MHz - This setting determines the frequency at which the SMLink1 will operate. Note: The recommended setting is "100KHz".	UP4 UP3	100 KHz 100 KHz
	Intel® SMBus ASD Mode Configuration This setting determines the native mode of operation for the Intel® SMBus ASD signal.	UP4 UP3	Enable as GPP_C2 Enable as GPP_C2



Table 2-10. - Internal PCH Buses (Sheet 4 of 5)

#	Parameter	Platform	Settings
	SMLink0 I2C Target Address - This setting configures SMLink0 I2C Target Address. For further details see Rocket Lake LP Platform Controller Hub EDS.	UP4 UP3	0x0 0x0
	SMLink0 I2C Target Address Enabled Values: Yes/No - This setting configures SMLink0 I2C Target Address. For further details see Rocket Lake LP Platform Controller Hub EDS.	UP4 UP3	No No

Click on Internal PCH Buses in the left tabs menu> DMI Configuration is expanded by default:

▼ DMI Configuration

3

Parameter	Value	Help Te
DMI Lane Reversal	No	This setting allow the DMI Lane signals to be revers
DMI Port Staggering Enabled	Yes	This setting configures DMI for Port Staggering. For

#	Parameter	Platform	Settings
3	DMI Configuration		
	DMI Lane Reversal Values: Yes/No - This setting allows the DMI Lane signals to be reversed. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	No No
	DMI Port Staggering Values: Yes/No - This setting configures DMI for Port Staggering. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	Yes Yes

Click on Internal PCH Buses in the left tabs menu> OPI Configuration is expanded by default:

▼ OPI / DMI Configuration

4

Parameter	Value	Help 1
OPI / DMI Link Speed	4 GT/s	This setting configures the OPI Link Speed. For furt
OPI /DMI Link Voltage	0.95 Volts	This setting configures the OPI Link Voltage. For fur
OPI / DMI Link Width	4 Lanes	This setting configures the OPI Link Width. For furtl

#	Parameter	Platform	Settings
4	OPI / DMI Configuration		
	OPI Link Speed Values: GT2/GT4 - This setting configures the OPI / DMI Link Speed. For further details see Tiger Lake PCH EDS.	UP4 UP3	2 GT/s 4 GT/s
	OPI Link Voltage Values: 0.85 Volts, 0.95 Volts, 1.05 Volts - This setting configures the OPI / DMI Link Voltage. For further details see Tiger Lake PCH EDS.	UP4 UP3	0.95 Volts 0.95 Volts
	OPI Link Width Values: 1 Lanes, 2 Lanes, 4 Lanes, 8 Lanes - This setting configures the OPI / DMI Link Width. For further details see Tiger Lake PCH EDS.	UP4 UP3	8 Lanes 8 Lanes

Click on Internal PCH Buses in the left tabs menu> eSPI Configuration is expanded by default:



Table 2-10. - Internal PCH Buses (Sheet 5 of 5)

<div> <div>▼ eSPI Configuration</div> <div>5</div> </div>			
Parameter		Value	
eSPI / EC Bus Frequency		20MHz	Indicates the maximum
eSPI / EC Maximum I/O Mode		Single	Indicates the maximum
eSPI / EC CRC Check Enabled		Yes	This setting enables CR
eSPI / EC Max Outstanding Request for Master Attached Flash Channel		2	This setting determines
eSPI / EC Slave Attached Flash Multiple Outstanding Requests Enable		Single Outstanding Request	This setting enabled mu
eSPI / EC Slave Attached Flash Channel OOO Enable		In-Order SAF Requests	This setting enables Ou

#	Parameter	Platform	Settings
5	eSPI Configuration		
	eSPI / EC Bus Frequency Value: 20MHz, 25MHz, 33MHz, 50MHz Indicates the maximum frequency of the eSPI bus that is supported by the eSPI Master and platform configuration (trace length, number of Slaves, etc.). The actual frequency of the eSPI bus will be the minimum of this field and the Slave's maximum frequency advertised in its General Capabilities register.	UP4 UP3	20MHz 20MHz
	eSPI / EC Maximum I/O Mode Values: Single, Single and Dual, Single and Quad, Single Dual and Quad Indicates the maximum IO Mode (Single/Dual/Quad) of the eSPI bus that is supported by the eSPI Master and specific platform configuration. The actual IO Mode of the eSPI bus will be the minimum of this field and the Slave's maximum IO Mode advertised in its General Capabilities register.	UP4 UP3	Single Single
	eSPI / EC CRC Check Enabled Values: Yes/No This setting enables CRC checking on eSPI Slave 0 channel.	UP4 UP3	No No
	eSPI / EC Max Outstanding Request for Master Attached Flash Channel Values: 1/2 This setting determines the Maximum outstanding requests on the eSPI / EC Master Attached Flash Channel.	UP4 UP3	2 2
	eSPI / EC Slave Attached Flash Multiple Outstanding Requests Enable Values: Single Outstanding Request/Multiple Outstanding Requests This setting enabled multiple outstanding requests for the eSPI / EC Slave Attached Flash device.	UP4 UP3	Single Outstanding Request Single Outstanding Request
	eSPI / EC Slave Attached Flash Channel OOO Enable Values: In-Order SAF Requests/Out-of-Order SAF Requests This setting enables Out or Order requests on the eSPI / EC Slave Attached Flash device.	UP4 UP3	In-Order SAF Requests In-Order SAF Requests



Table 2-11. - Power (Sheet 1 of 2)

Click on Power in the left tabs menu> Platform Power is expanded by default:

▼ Platform Power

1

Parameter	Value	
SLP_S5# / GPD10 Signal Config...	Enable as SLP_S5#	This setting allows the user to assign
SLP_S3# / GPD4 Signal Configu...	Enable as SLP_S3#	This setting allows the user to assign
SLP_S4# / GPD5 Signal Configu...	Enable as SLP_S4#	This setting allows the user to assign
SLP_A# / GPD6 Signal Configur...	Enable as SLP_A#	This setting allows the user to assign
SLP_S0# Tunnel	Disabled	This setting Enables / Disables the tur

#	Parameter	Platform	Settings
1	Platform Power		
	SLP_S3# / GPD4 Signal Configuration Values: SLP_S3#, GPD4 - This setting allows the customer to assign the SLP_S3# Power Control signal as SLP_S3# or as GDP4. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	SLP_S3# SLP_S3#
	SLP_S4# / GPD5 Signal Configuration Values: SLP_S4#, GPD5 - This setting allows the customer to assign the SLP_S4# Power Control signal as SLP_S4# or as GDP5. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	SLP_S4# SLP_S4#
	SLP_S5# / GPD10 Signal Configuration Values: SLP_S5#, GPD10 - This setting allows the customer to assign the SLP_S5# Power Control signal as SLP_S5# or as GDP10. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	SLP_S5# SLP_S5#
	SLP_A# / GPD6 Signal Configuration Values: SLP_A#, GPD6 - This setting allows the customer to assign the SLP_A# Power Control signal as SLP_A# or as GDP6. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	SLP_A# SLP_A#
	SLP_S0# Tunnel This setting Enables / Disables the tunneling of the SLP_S0# pin over ESPI to the EC when in ESPI mode.	UP4 UP3	Disabled Disabled

Click on Power in the left tabs menu> Deep Sx is expanded by default:

▼ Deep Sx

2

Parameter	Value	Help Text
Deep Sx Enabled	Yes	This requires the target platform to support Deep SX state

#	Parameter	Platform	Settings
2	Deep Sx		
	Deep Sx Enabled Values: Yes/ No - This setting enables / disables support for Deep Sx operation. For further details see Tiger Lake LP Platform Controller Hub EDS. Note: Support for Deep Sx is board design dependent.	UP4 UP3	Yes Yes

Click on Power in the left tabs menu> PCH Thermal Reporting is expanded by default:



Table 2-11. - Power (Sheet 2 of 2)

▼ PCH Thermal Reporting 3			
Parameter		Value	
Thermal Power Reporting Enabled		Yes	This setting enabled a or



Table 2-12. - Integrated Sensor Hub (Sheet 1 of 2)

Click on Integrated Sensor Hub in the left tabs menu> Integrated Sensor Hub is expanded by default:

▼ Integrated Sensor Hub

1

Parameter	Value	Help Text
Integrated Sensor Hub Supported	No	This setting allows customers to disable ISH on the platform.
Integrated Sensor Hub Initial Power State	Disabled	This setting allows customers to determine the power up state for ISH.

#	Parameter	Platform	Settings
1	Integrated Sensor Hub		
	Integrated Sensor Hub Supported Values: Yes/No This setting allows customers to disable ISH on the platform.	UP4 UP3	No No
	Integrated Sensor Hub Power Up State Values: Enabled/Disabled Field is enabled for editing if "Integrated Sensor Hub Supported" field above is set to "Yes". This setting allows customers to determine the power up state for ISH.	UP4 UP3	Disabled Disabled

Click on Integrated Sensor Hub in the left tabs menu> ISH Image is expanded by default:

▼ ISH Image

2

Parameter	Value	Help Text
Length	0x40000	Total size (in bytes) of the ISH code partition including reserved space. It is recommended to be at least 256kb.
ISH Input File		Path to your ISH firmware binary file.
Version		-

#	Parameter	Platform	Settings
2	ISH Image		
	Length - Total size (in bytes) of the ISH code partition including reserved space. It is recommended to be at least 256kb.		
	Input File	UP4 UP3	ISH Binary (Optional)
	Version - This displays the version of ISH		


Click on Integrated Sensor Hub in the left tabs menu> ISH Data is expanded by default:

▼ ISH Data

3

Parameter	Value	Help Text
PDT Binary File		Path to your PDT binary file

#	Parameter	Platform	Settings
---	-----------	----------	----------

**Table 2-12. - Integrated Sensor Hub (Sheet 2 of 2)**

3	Integrated Sensor Hub - ISH Data		
	PDT Binary File	UP4 UP3	Path for PDT Binary file Path for PDT Binary file



Table 2-13. - Camera

Click on Camera in the left tabs menu> IPU Security is expanded by default:

▼ IPU Security

1

Parameter	Value	
Secure Touch	Disabled	When set, CAMERA_MASK register bits per
FW Secure Mode	Enabled	If enabled, access blockers in IS and PS a
Secure Touch Camera Mask	0xFF	Camera mask bits per CSI port. When SE

#	Parameter	Platform	Settings
1	IPU Security		
	Secure Touch Values: Enabled / Disabled When set, CAMERA_MASK register bits per CSI port are used to mask the data of cameras. When cleared, camera data is not masked.	UP4 UP3	Disabled Disabled
	FW Secure Mode Values: Enabled / Disabled If enabled, access blockers in IS and PS are enabled, and FW is read from IMR. Must be enabled for FW authentication flow and execution of authenticated FW.	UP4 UP3	Enabled Enabled
	Secure Touch Camera Mask Values: Hex Input Camera mask bits per CSI port. When SECURE_TOUCH is set each set bit masks a CSI port for secure touch. When SECURE_TOUCH is cleared this register has no impact on the CSI ports.	UP4 UP3	0xFF 0xFF



Table 2-14. - Debug (Sheet 1 of 5)

Click on Debug in the left tabs menu> Intel® ME Firmware Debugging Overrides is expanded by default:

▼ IDLM

1

Parameter	Value	H
IDLM Binary		This allows an IDLM binary to be merged in
IDLM Token		If this setting is enabled the Intel (R) Trace

#	Parameter	Platform	Settings
1	IDLM		
	IDLM Binary This allows an IDLM binary to be merged into output image built by Intel® FIT.	UP4 UP3	IDLM Binary (Optional)

Click on Debug in the left tabs menu> Delayed Authentication Mode Configuration is expanded by default:

▼ Delayed Authentication Mode Configuration

2

Parameter	Value	
Delayed Authentication Mode Enabled	No	This setting enables Delayed Authentication Mod

#	Parameter	Platform	Settings
2	Delayed Authentication Mode Configuration		
	Delayed Authentication Mode Enabled Values: Yes/No - This setting enable / disables Delayed Authentication Mode on the platform.	UP4 UP3	No No

Click on Debug in the left tabs menu> Intel® Trace Hub Technology is expanded by default:

▼ Intel(R) Trace Hub Technology

3

Parameter	Value	
Intel(R) Trace Hub Binary		This loads the Intel(R) Trace Hub
Intel(R) Trace Hub Emergency Mode Enabled	No	When enabled, Intel(R) ME progr
PMC Hub Debug Messages Enabled	Yes	This setting enables PMC FW trac
Unlock Token		This allows the OEM to input an U

#	Parameter	Platform	Settings
3	Intel® Trace Hub Technology		



Table 2-14. - Debug (Sheet 2 of 5)

	Intel® Trace Hub Binary - This loads the Intel® Trace Hub binary that will be merged into the output image generated by the Intel® FIT tool.	UP4 UP3	Trace Hub Binary Trace Hub Binary
	Intel® Trace Hub Emergency Mode Enabled Values: Yes/No - This setting enable / disables Intel® Trace Hub in the firmware base image.	UP4 UP3	No No
	PMC Debug Messages Enabled Values: Yes/No - This setting enables/disables the PMC debug messages.	UP4 UP3	Yes Yes
	Unlock Token This allows the OEM to input an Unlock Token binary file for closed chassis debug.	UP4 UP3	Unlock Token Binary (Optional)

Click on Debug in the left tabs menu> Intel® ME Debugging Overrides is expanded by default:

▼ Intel(R) ME Firmware Debugging Overrides

Parameter	Value	
Debug Override Pre-Production Silicon	0x0	Allows the OEM t
Debug Override Production Silicon	0x0	Allows the OEM t
Intel(R) ME Reset Behavior	Intel(R) ME will Halt	This setting deter
Enable Intel(R) ME Reset Capture on CLR_RST#	No	This setting confi
Firmware ROM Bypass	No	This setting enab
AFS Idle Flash Reclaim Enabled	Yes	This controls ena

#	Parameter	Platform	Settings
4	Intel® ME Firmware Debugging Overrides		
	Debug Override Pre-Production Silicon - Allows the OEM to control FW features to assist with pre-production platform debugging. This control has no effect if used on production silicon. Bit 0: Disable DRAM_INIT_DONE (default timeout 60 seconds) Bit 1: Disable Host Reset Timer Bit 2: Disable CPU_RESET_DONE timeout Bit 3: Reserved Bit 4: Disable Intel® ME Power Gating Bit 5: Reserved Bit 6: Secure Boot debug hook. Used to shorten wait time before ENF shutdown. Bit 7: Force real FPFs on preproduction (default is to use flash) Bit 8: Secure Boot debug hook. Used to reduce S3 or FFS optimization tries. Bit 9: Reserved Bit 10: Override power package to always enter M3. Note: Certain options do not work when the descriptor is locked.	UP4 UP3	0x00000007 0x00000007
	Debug Override Production Silicon - Allows the OEM to control FW features to assist with production platform debugging. Bit 0: Extend DRAM_INIT_DONE timeout to 30 minutes (default timeout 15 seconds) Bit 1: Disable Host Reset Timer Bit 2: Disable CPU_RESET_DONE timeout Note: Certain options do not work when the descriptor is locked.	UP4 UP3	0x00000000 0x00000000



Table 2-14. - Debug (Sheet 3 of 5)

	Intel® ME Reset Behavior Values: Intel® ME will Halt / Intel® Alternate image boot This setting determines Intel® ME behavior when boot image errors are encountered. Warning: This setting should be used for debug purposes only. Note: This may block normal Firmware functional flows.	UP4 UP3	Intel® ME will Halt Intel® ME will Halt
	Enable Intel® ME Reset Capture on CLR_RST#	UP4 UP3	No No
	Firmware ROM Bypass Values: Yes/No - This setting enables / disables firmware ROM bypass. Note: This setting only has affect when the firmware being used has ROM Bypass code present.	UP4 UP3	No No
	ASF Idle Flash Reclaim Enabled Values: Yes / No This controls enabling / disable the Intel® AFS Idle flash reclaim capabilities. Note: This setting should be used for debug purposes only.	UP4 UP3	Yes Yes

Click on Debug in the left tabs menu> Direct Connection Interface Configuration is expanded by default:

▼ Direct Connect Interface Configuration

5

Parameter	Value	
Intel(R) DCI DbC Interface Enabled	No	This setting enables / disables the DCI in
DCI OOB over USB3 Port1 Enabled	Yes	This setting determines if the USB port t
DCI OOB over USB3 Port2 Enabled	Yes	This setting determines if the USB port t
DCI OOB over USB3 Port3 Enabled	No	This setting determines if the USB port t
DCI OOB over USB3 Port4 Enabled	No	This setting determines if the USB port t

#	Parameter	Platform	Settings
5	Direct Connection Interface Configuration Note: When any of the DCI BSSB USB3 Port interfaces are enabled the associated USB3 port selection control will be greyed out under the USB3 Port Configuration settings section under the Flex I/O tab		
	Intel® DCI DbC Interface Enabled Values: Yes/No - This setting enables / disables the Intel® DCI DbC interface.	UP4 UP3	Yes Yes
	DCI OOB over USB3 Port1 Enabled Values: Yes / No This setting determines if the USB port being enabled for DCI OOB. If disabled it will block DCI OOB connection. Note: When this setting is enabled the corresponding USB3 Combo Port in the Flex I/O Tab will be Grayed out.	UP4 UP3	Yes Yes
	DCI OOB over USB3 Port 2 Enabled Values: Yes / No This setting determines if the USB port being enabled for DCI OOB. If disabled it will block DCI OOB connection. Note: When this setting is enabled the corresponding USB3 Combo Port in the Flex I/O Tab will be Grayed out.	UP4 UP3	Yes Yes



Table 2-14. - Debug (Sheet 4 of 5)

	DCI OOB over USB3 Port 3 Enabled Values: Yes / No This setting determines if the USB port being enabled for DCI OOB. If disabled it will block DCI OOB connection. Note: When this setting is enabled the corresponding USB3 Combo Port in the Flex I/O Tab will be Grayed out.	UP4 UP3	No No												
	DCI OOB over USB3 Port 4 Enabled Values: Yes / No This setting determines if the USB port being enabled for DCI OOB. If disabled it will block DCI OOB connection. Note: When this setting is enabled the corresponding USB3 Combo Port in the Flex I/O Tab will be Grayed out.	UP4 UP3	No No												
Click on Debug in the left tabs menu> eSPI Feature Overrides is expanded by default:															
<div>▼ eSPI Feature Overrides <div>6</div></div>															
<table><tr><th>Parameter</th><th>Value</th><th></th></tr><tr><td>eSPI / EC Low Frequency Debug Override</td><td>No</td><td>When enabled this setting will divide e</td></tr></table>				Parameter	Value		eSPI / EC Low Frequency Debug Override	No	When enabled this setting will divide e						
Parameter	Value														
eSPI / EC Low Frequency Debug Override	No	When enabled this setting will divide e													
#	Parameter	Platform	Settings												
<div>6</div>	eSPI Feature Overrides														
	eSPI / EC Low Frequency Debug Override When enabled this setting will divide eSPI clock frequency by 8. Note: This setting should only be used for debugging purposes. Leaving this set to "Yes" will impact eSPI performance on the platform.	UP4 UP3	No No												
Click on Debug in the left tabs menu> Early USB DBC Type-A Configuration is expanded by default:															
<div>▼ Early USB DBC over Type-A Configuration <div>7</div></div>															
<table><tr><th>Parameter</th><th>Value</th><th></th></tr><tr><td>Enable early USB2 DbC connection</td><td>No</td><td>This setting enables a delay during Int</td></tr><tr><td>USB2 DbC port enable</td><td>No USB2 Ports</td><td>This setting dedicates USB2 STD-A po</td></tr><tr><td>USB Connectors Associated USB3 Port enable</td><td>No USB3 Ports</td><td>This setting disables USB3 lanes on S1</td></tr></table>				Parameter	Value		Enable early USB2 DbC connection	No	This setting enables a delay during Int	USB2 DbC port enable	No USB2 Ports	This setting dedicates USB2 STD-A po	USB Connectors Associated USB3 Port enable	No USB3 Ports	This setting disables USB3 lanes on S1
Parameter	Value														
Enable early USB2 DbC connection	No	This setting enables a delay during Int													
USB2 DbC port enable	No USB2 Ports	This setting dedicates USB2 STD-A po													
USB Connectors Associated USB3 Port enable	No USB3 Ports	This setting disables USB3 lanes on S1													
#	Parameter	Platform	Settings												
<div>7</div>	Early USB DBC Type-A Configuration														
	Enabled early USB2 DbC connection Values: Yes / No This setting enabled a delay during Intel® ME firmware bring-up to allow USB2 DbC connection to be established	UP4 UP3	No No												
	USB2 DbC port enable This setting determines which USB2 ports are enabled for Early DbC debugging.	UP4 UP3	No USB2 Ports No USB2 Ports												



Table 2-15. - CPU Straps (Sheet 1 of 2)

Click on CPU Straps in the left tabs menu> CPU Straps are expanded by default:			
<div> <div>▼ CPU Straps</div> <div>1</div> </div>			
Parameter	Value		
Number of Active Cores	All Cores Active	This setting controls the number of activ	
Disable Hyperthreading	No	This setting control enabling / disabling	
BIST Initialization	No	This setting determines if BIST will be ru	
Flex Ratio	0x0	This setting controls the maximum proce	
Processor Boot at P1 Frequency	Yes	Processor Boot at P1 Frequency	
JTAG Power Disable	No JTAG Power on C10 and Lo...	This setting determines if JTAG power w	
SVID Presence	SVID is present	This setting determine if SVID rails are p	
Platform IMON	Enabled	This strap should be left at the recomme	
VCC Aux Present	No	This setting determines if VCC Aux exist	
VCC IN SVID VR Address	0x0	This setting determines the VCC IN SVID	
VCC IN SVID VR Type	SVID	This setting determines the VCC IN SVID	
VCC ST PG Present	No	This setting determines if VCC ST PG is	
VCC STG PG Present	No	This setting determines if VCC STG PG is	
VCCIN Aux Level LP	1.8v	This setting determines the VCCIN Aux L	
IA VR Offset VID	Above 1.52v Not Allowed	This setting determines if output higher	
#	Parameter	Platform	Settings
1	CPU Straps - CPU Straps		
	Number of Active Cores Values: All, 1, 2, 3, 4, 5, 6, 7, 8 This setting controls the number of active processor cores. Note: This strap is intended for debugging purposes only. See BIOS Spec for more details on enabling or disabling processor cores.	UP4 UP3	All Cores Active All Cores Active
	Disable Hyperthreading Values: Yes/No This setting controls enabling or disabling of Hyper threading. Note: This strap is intended for debugging purposes only. See BIOS Spec for more details on enabling / disabling Hyperthreading.	UP4 UP3	No No



Table 2-15. - CPU Straps (Sheet 2 of 2)

	BIST Initialization Values: Yes/No This setting determines if BIST will be run at platform reset after BIOS requested actions. Note: This strap is intended for debugging purposes only.	UP4 UP3	No No
	Flex Ratio This setting controls the maximum processor non-turbo ratio. Note: This strap is intended for debugging purposes only. See BIOS Spec for more details on maximum processor non-turbo ratio configuration.	UP4 UP3	0x0 0x0
	Processor Boot at P1 Frequency Values: Yes/No This setting determines if the processor will operate at maximum frequency at power-on and boot. Note: This strap is intended for debugging purposes only.	UP4 UP3	Yes Yes
	JTAG Power Disable Values: Yes - JTAG Power on C10 and Lower/No - No Power on C10 and Lower This setting determines if JTAG power will be maintained on C10 or lower power states. Note: This strap is intended for debugging purposes only.	UP4 UP3	No JTAG Power on C10 and Lower No JTAG Power on C10 and Lower
	SVID Presence Value: SVID Present/SVID Not Present This setting determines if SVID rails are present on the platform. See Processor EDS for details.	UP4 UP3	SVID Present SVID Present
	Platform IMON Value: Enabled/Disabled Note: This strap should be left at the recommended default setting.	UP4 UP3	Enabled Enabled
	VCC Aux Present Value: Yes/No This setting determines if VCC Aux exists as a separate VR.	UP4 UP3	Yes Yes
	VCCIN SVID Address This setting determines the VCCIN SVID Address. See Processor EDS for details. Note: This strap should be left at the recommended default setting.	UP4 UP3	0x0 0x0
	VCC SVID VR Type Values: SVID/Fixed VR This setting determines the VCC IN SVID VR Type. See Processor EDS for details.	UP4 UP3	SVID SVID
	VCC ST PG Present Values: Yes/No This setting determines if VCC ST PG is present on the platform.	UP4 UP3	No No
	VCC STG PG Present Values: Yes/No This setting determines if VCC STG PG is present on the platform.	UP4 UP3	No No
	VCCIN Aux Level LP Values: 1.8v/1.65v This setting determines the VCCIN Aux Level LP Voltage. Note: On UP4 based MCP this setting can be configured to 1.65v. On the UP3 MCP types set to 1.8v	UP4 UP3	1.65v or 1.8v 1.8v
	IA VR Offset VID Values: Above 1.52v Not Allowed/Above 1.52v Allowed This setting determines if output higher than 1.52v is allowed for 8 or higher core count processors.	UP4 UP3	Above 1.52v Not Allowed Above 1.52v Not Allowed



Table 2-16. - Flex I/O Straps (Sheet 1 of 15)

Click on Flex I/O in the left tabs menu> PCIe Lane Reversal Configuration is expanded by default:

▼ PCIe Lane Reversal Configuration

1

Parameter	Value	
PCIe Controller 1 Lane Reversal...	No	This setting allows the PCIe lanes on C
PCIe Controller 2 Lane Reversal...	No	This setting allows the PCIe lanes on C
PCIe Controller 3 Lane Reversal...	Yes	This setting allows the PCIe lanes on C

#	Parameter	Platform	Settings
1	PCIe Lane Reversal Configuration		
	PCIe Controller 1 Lane Reversal Enabled Values: Yes/ No - This setting allows the PCIe lanes on Controller 1 to be reversed. Note: Refer to EDS for PCIe supported port configurations.	UP4 UP3	No No
	PCIe Controller 2 Lane Reversal Enabled Values: Yes/ No - This setting allows the PCIe lanes on Controller 2 to be reversed. Note: Refer to EDS for PCIe supported port configurations.	UP4 UP3	No No
	PCIe Controller 3 Lane Reversal Enabled Values: Yes/ No - This setting allows the PCIe lanes on Controller 3 to be reversed. Note: Refer to EDS for PCIe supported port configurations.	UP4 UP3	Yes Yes

Click on Flex I/O in the left tabs menu> PCIe Port Configuration is expanded by default:

▼ PCIe Port Configuration

2

Parameter	Value	
PCIe Controller 1 (Port 1-4)	4x1	This setting controls PCIe Port con
PCIe Controller 2 (Port 5-8)	1x4	This setting controls PCIe Port con
PCIe Controller 3 (Port 9-12)	1x4	This setting controls PCIe Port con

#	Parameter	Platform	Settings
2	PCIe Port Configuration		
	PCIe Controller 1 (Port 1-4) Values: 4x1, (1x2, 2x1), 2x2, 1x4 - This setting controls PCIe Port configurations for PCIe Controller 1. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	4x1 4x1
	PCIe Controller 2 (Port 5-8) Values: 4x1, (1x2, 2x1), 2x2, 1x4 - This setting controls PCIe Port configurations for PCIe Controller 2. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	4x1 1x2, 2x1

Note: On UP4 only lanes 7 and 8 are available for use.



Table 2-16. - Flex I/O Straps (Sheet 2 of 15)

	PCIe Controller 3 (Port 9-12) Values: 4x1, (1x2, 2x1), 2x2, 1x4 - This setting controls PCIe Port configurations for PCIe Controller 3. For further details see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	1x4 1x4									
Click on Flex I/O in the left tabs menu> SATA / PCIe Combo Port Configuration is expanded by default:												
<div>▼ SATA / PCIe Combo Port Configuration 3</div> <table><thead><tr><th>Parameter</th><th>Value</th><th></th></tr></thead><tbody><tr><td>SATA / PCIe Combo Port 0</td><td>PCIe</td><td>This setting configu</td></tr><tr><td>SATA / PCIe Combo Port 1</td><td>GPIO Polarity PCIe</td><td>This setting configu</td></tr></tbody></table>				Parameter	Value		SATA / PCIe Combo Port 0	PCIe	This setting configu	SATA / PCIe Combo Port 1	GPIO Polarity PCIe	This setting configu
Parameter	Value											
SATA / PCIe Combo Port 0	PCIe	This setting configu										
SATA / PCIe Combo Port 1	GPIO Polarity PCIe	This setting configu										
#	Parameter	Platform	Settings									
3	SATA / PCIe Combo Port Configuration											
	SATA / PCIe Combo Port 0 Values: SATA, PCIe, GPIO Polarity PCIe, GPIO Polarity SATA - This setting configures the PCIe port to operate as either: PCIe Port 11 or SATA Port 0 For further details on Flex I/O see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	PCIe PCIe									
	SATA / PCIe Combo Port 1 Values: SATA, PCIe, GPIO Polarity PCIe, GPIO Polarity SATA - This setting configures the PCIe port to operate as either: PCIe Port 12 or SATA Port 1 For further details on Flex I/O see Tiger Lake LP Platform Controller Hub EDS.	UP4 UP3	GPIO Polarity PCIe GPIO Polarity PCIe									
Click on Flex I/O in the left tabs menu> USB3 Port Configuration is expanded by default:												



Table 2-16. - Flex I/O Straps (Sheet 3 of 15)

<div> <div>▼ USB3 Port Configuration</div> <div>4</div> </div>			
Parameter	Value	Description	
USB3 / PCIe Combo Port 0	USB3	This setting configures the PCIe port to operate as either a PCIe Port 0 or USB3 Port 0	
USB3 / PCIe Combo Port 1	USB3	This setting configures the PCIe port to operate as either a PCIe Port 1 or USB3 Port 1	
USB3 / PCIe Combo Port 2	USB3	This setting configures the PCIe port to operate as either a PCIe Port 2 or USB3 Port 2	
USB3 / PCIe Combo Port 3	USB3	This setting configures the PCIe port to operate as either a PCIe Port 3 or USB3 Port 3	
USB3 Port 1 Connector Type Selection	Type A	This setting configures the physical connector type for USB3 Port 1	
USB3 Port 2 Connector Type Selection	Type A	This setting configures the physical connector type for USB3 Port 2	
USB3 Port 3 Connector Type Selection	Type C	This setting configures the physical connector type for USB3 Port 3	
USB3 Port 4 Connector Type Selection	Type C	This setting configures the physical connector type for USB3 Port 4	
USB3 Port 1 Initialization Speed	USB3.1 Gen1 LBPM	This setting determines USB3 Port 1 speed during initialization	
USB3 Port 2 Initialization Speed	USB3.1 Gen1 LBPM	This setting determines USB3 Port 2 speed during initialization	
USB3 Port 3 Initialization Speed	USB3.1 Gen1 LBPM	This setting determines USB3 Port 3 speed during initialization	
USB3 Port 4 Initialization Speed	USB3.1 Gen1 LBPM	This setting determines USB3 Port 4 speed during initialization	
USB3 Port 1 Speed Capability	USB 3.1 Gen2	This setting determines the USB3 Port 1 speed capability	
USB3 Port 2 Speed Capability	USB 3.1 Gen2	This setting determines the USB3 Port 2 speed capability	
USB3 Port 3 Speed Capability	USB 3.1 Gen2	This setting determines the USB3 Port 3 speed capability	
USB3 Port 4 Speed Capability	USB 3.1 Gen2	This setting determines the USB3 Port 4 speed capability	
USB Type AB Mode Select	USB Type AB HW Select	This setting determines how the USB Type A port operates	
#	Parameter	Platform	Settings
4	USB3 Port Configuration		
	USB3 / PCIe Combo Port 0 Values: PCIe (or GbE), USB3 - This setting configures the PCIe port to operate as either: PCIe Port 1 or USB3 Port 1 For further details on Flex I/O see Tiger Lake LP Platform Controller Hub EDS. Note: If DCI BSSB for this USB3 Combo port it will be Grayed out.	UP4 UP3	USB3 USB3



Table 2-16. - Flex I/O Straps (Sheet 4 of 15)

	USB3 / PCIe Combo Port 1 Values: PCIe (or GbE), USB3 - This setting configures the PCIe port to operate as either: PCIe Port 2 or USB3 Port 2 For further details on Flex I/O see Tiger Lake LP Platform Controller Hub EDS. Note: If DCI BSSB for this USB3 Combo port it will be Grayed out.	UP4 UP3	USB3 USB3
	USB3 / PCIe Combo Port 2 Values: PCIe (or GbE), USB3 - This setting configures the PCIe port to operate as either: PCIe Port 3 or USB3 Port 3 For further details on Flex I/O see Tiger Lake LP Platform Controller Hub EDS. Note: If DCI BSSB for this USB3 Combo port it will be Grayed out.	UP4 UP3	PCIe PCIe
	USB3 / PCIe Combo Port 3 Values: PCIe (or GbE), USB3 - This setting configures the PCIe port to operate as either: PCIe 4 or USB3 Port 4 For further details on Flex I/O see Tiger Lake LP Platform Controller Hub EDS. Note: If DCI BSSB for this USB3 Combo port it will be Grayed out.	UP4 UP3	PCIe PCIe
	USB3 Port 1 Connector Type Select This setting configures the physical connector type to be used for USB 3.0 / 3.1 Port 1.	UP4 UP3	Type-A Type-A
	USB3 Port 2 Connector Type Select This setting configures the physical connector type to be used for USB 3.0 / 3.1 Port 2.	UP4 UP3	Type-A Type-A
	USB3 Port 3 Connector Type Select This setting configures the physical connector type to be used for USB 3.0 / 3.1 Port 3.	UP4 UP3	Type-C Type-C
	USB3 Port 4 Connector Type Select This setting configures the physical connector type to be used for USB 3.0 / 3.1 Port 4.	UP4 UP3	Type-C Type-C
	USB3 Port 1 Initialization Speed Select This setting determines USB3 Port 1 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	USB3 Port 2 Initialization Speed Select This setting determines USB3 Port 2 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	USB3 Port 3 Initialization Speed Select This setting determines USB3 Port 3 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	USB3 Port 4 Initialization Speed Select This setting determines USB3 Port 4 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	USB3 Port 1 Speed Capability This setting determines the USB3 Port 1 speed capabilities. Note: When a USB 3.2 Gen 2x1 (10 Gb/s) capable port is configured to USB 3.2 Gen 1x1 (5 Gb/s) speed using the soft strap, the port may still send 10 Gb/s compliance patterns if the USB compliance test (TD1.4, and TD1.7) is run on the port.	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2
	USB3 Port 2 Speed Capability This setting determines the USB3 Port 2 speed capabilities. Note: When a USB 3.2 Gen 2x1 (10 Gb/s) capable port is configured to USB 3.2 Gen 1x1 (5 Gb/s) speed using the soft strap, the port may still send 10 Gb/s compliance patterns if the USB compliance test (TD1.4, and TD1.7) is run on the port.	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2



Table 2-16. - Flex I/O Straps (Sheet 5 of 15)

	USB3 Port 3 Speed Capability This setting determines the USB3 Port 3 speed capabilities. Note: When a USB 3.2 Gen 2x1 (10 Gb/s) capable port is configured to USB 3.2 Gen 1x1 (5 Gb/s) speed using the soft strap, the port may still send 10 Gb/s compliance patterns if the USB compliance test (TD1.4, and TD1.7) is run on the port.	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2
	USB3 Port 4 Speed Capability This setting determines the USB3 Port 4 speed capabilities. Note: When a USB 3.2 Gen 2x1 (10 Gb/s) capable port is configured to USB 3.2 Gen 1x1 (5 Gb/s) speed using the soft strap, the port may still send 10 Gb/s compliance patterns if the USB compliance test (TD1.4, and TD1.7) is run on the port.	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2
	USB Type AB Mode Select This setting determines how the USB Type AB connector switching is handled.	UP4 UP3	USB Type AB SW Select USB Type AB SW Select

Click on Flex I/O in the left tabs menu> USB2 Port Configuration is expanded by default:

▼ USB2 Port Configuration 5

Parameter	Value	
USB2 Port 1 Connector Type Se...	Type C	This setting configures the phys
USB2 Port 2 Connector Type Se...	Express Card / M.2 S2	This setting configures the phys
USB2 Port 3 Connector Type Se...	Type A / Type C	This setting configures the phys
USB2 Port 4 Connector Type Se...	Type A / Type C	This setting configures the phys
USB2 Port 5 Connector Type Se...	Type C	This setting configures the phys
USB2 Port 6 Connector Type Se...	Type C	This setting configures the phys
USB2 Port 7 Connector Type Se...	Type C	This setting configures the phys
USB2 Port 8 Connector Type Se...	Type A / Type C	This setting configures the phys
USB2 Port 9 Connector Type Se...	Type A / Type C	This setting configures the phys
USB2 Port 10 Connector Type S...	Express Card / M.2 S2	This setting configures the phys

#	Parameter	Platform	Settings
5	Flex I/O - USB2 Port Configuration		
	USB2 Port 1 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 1.	UP4 UP3	Type-C Type-C
	USB2 Port 2 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 2.	UP4 UP3	Type A / Type C Express Card / M.2 S2
	USB2 Port 3 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 3.	UP4 UP3	Type A / Type C Type A / Type C
	USB2 Port 4 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 4.	UP4 UP3	Type A / Type C Type A / Type C



Table 2-16. - Flex I/O Straps (Sheet 6 of 15)

	USB2 Port 5 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 5.	UP4 UP3	Type-C Type-C
	USB2 Port 6 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 6.	UP4 UP3	Type-C Type-C
	USB2 Port 7 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 7.	UP4 UP3	Type A / Type C Type-C
	USB2 Port 8 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 8.	UP4 UP3	Type A / Type C Type A / Type C
	USB2 Port 9 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 9.	UP4 UP3	Type A / Type C Type A / Type C
	USB2 Port 10 Connector Type Select This setting configures the physical connector type to be used for USB2 Port 10.	UP4 UP3	Express Card / M.2 S2 Express Card / M.2 S2
Click on Flex I/O in the left tabs menu> Type-C Subsystem Configuration is expanded by default:			




Table 2-16. - Flex I/O Straps (Sheet 7 of 15)

Type-C Subsystem Configuration 6		
Parameter	Value	
IO Manageability Engine Binary File		This loads the Type-C Subsystem IO Manageability Engine
IO Manageability Engine Enabled	Yes	This setting enables\ disables the Type-C Subsystem IO M
IO Manageability Engine Length	0x12000	Set the length of IOM sub partition.
IO Manageability Engine version		-
IO Manageability Engine OEM configuration Binary File		This loads the Type-C Subsystem IO Manageability Engine
PHY Binary File		This loads the Type-C Subsystem PHY binary that will be r
PHY Manifest Enabled	Yes	This setting enables\ disables the Type-C Subsystem MG I
PHY Length	0x10000	Set the length of MG PHY sub partition.
PHY version		-
Thunderbolt(TM)/USB4(TM) Binary File		This loads the Type-C Subsystem Thunderbolt(TM)/USB4(
Thunderbolt(TM)/USB4(TM) Binary file Length	0x40000	Set the length of Thunderbolt(TM) sub partition.
Thunderbolt(TM)/USB4(TM) version		-
Tcss - Partial Update Enabled	Disabled	This setting enables partial update for TCSS partitions
Type-C Subsystem Port Enable Mask	0xF	This setting determines the Type-C Subsystem Port Enabl
Type-C Port 1 Configuration	No Restrictions	This setting determines the configuration of Type-C Port 1
Type-C Port 2 Configuration	No Restrictions	This setting determines the configuration of Type-C Port 2
Type-C Port 3 Configuration	No Restrictions	This setting determines the configuration of Type-C Port 3
Type-C Port 4 Configuration	No Restrictions	This setting determines the configuration of Type-C Port 4
Type-C Port 1 Speed Capability	USB 3.1 Gen2	This setting determines the Type-C Port 1 speed capabiliti
Type-C Port 2 Speed Capability	USB 3.1 Gen2	This setting determines the Type-C Port 2 speed capabiliti
Type-C Port 3 Speed Capability	USB 3.1 Gen2	This setting determines the Type-C Port 3 speed capabiliti
Type-C Port 4 Speed Capability	USB 3.1 Gen2	This setting determines the Type-C Port 4 speed capabiliti
Type-C Port 1 Initialization Speed Select	USB3.1 Gen1 LBPM	This setting determines Type-C Port 1 speed during platfo
Type-C Port 2 Initialization Speed Select	USB3.1 Gen1 LBPM	This setting determines Type-C Port 2 speed during platfo
Type-C Port 3 Initialization Speed Select	USB3.1 Gen1 LBPM	This setting determines Type-C Port 3 speed during platfo
Type-C Port 4 Initialization Speed Select	USB3.1 Gen1 LBPM	This setting determines Type-C Port 4 speed during platfo
Type-C Port 1 Connector Type Select	Type C	This setting configures the physical connector type to be u
Type-C Port 2 Connector Type Select	Type C	This setting configures the physical connector type to be u
Type-C Port 3 Connector Type Select	Type C	This setting configures the physical connector type to be u
Type-C Port 4 Connector Type Select	Type C	This setting configures the physical connector type to be u
xDCI Split Die Configuration	xDCI Split Die Enabled	This setting determines if xDCI Split die configuration is er



Table 2-16. - Flex I/O Straps (Sheet 8 of 15)

#	Parameter	Platform	Settings
6	Type-C Subsystem Configuration		
	IO Manageability Engine Binary File - This loads the IO Manageability binary that will be merged into the output image generated by the Intel® FIT.	UP4 UP3	IOM Binary IOM Binary
	IO Manageability Engine Enabled Values: Yes/No This setting enables / disables the Type-C Subsystem IO Manageability Engine on the platform.	UP4 UP3	Yes Yes
	IO Manageability Engine Length - This displays the length of the IO Manageability binary. Note: This value will be automatically populated by Intel® FIT during image build.		
	IO Manageability Engine Version - This displays the version of IO Manageability binary.		
	PHY Binary File - This loads the MG PHY binary that will be merged into the output image generated by the Intel® FIT.	UP4 UP3	PHY Binary PHY Binary
	PHY Manifest Enabled Values: Yes/No This setting enables / disables the NPHY on the platform.	UP4 UP3	Yes Yes
	PHY Length - This displays the length of the PHY binary. Note: This value will be automatically populated by Intel® FIT during image build.		
	PHY Version - This displays the version of PHY binary.		
	Thunderbolt™/USB4™ Binary File Values: Yes/No This setting enables Anti-Roll back for the Type-C Subsystem Thunderbolt™/USB4™ binary.	UP4 UP3	TBT Binary TBT Binary
	Thunderbolt™/USB4™ Length - This displays the length of the Thunderbolt™/USB4™ binary. Note: This value will be automatically populated by Intel® FIT during image build.		
	Thunderbolt™/USB4™ Version - This displays the version of Thunderbolt™/USB4™ binary.		
	Tcss - Partial Update Enabled Values: Enabled/Disabled This setting enabled partial firmware update of the TCSS partitions.	UP4 UP3	Disabled Disabled
	Type-C Subsystem Port Enable Mask This setting determines the Type-C Subsystem Port Enable Mask	UP4 UP3	0xF 0xF
	Type-C Subsystem Authentication Enabled Values: Yes/No This setting enables / disables firmware authentication for the Type-C Subsystem on power-up.	UP4 UP3	Yes Yes
	Type-C Port 1 Configuration Value: No Restrictions/DP Fixed Connection/No Thunderbolt This setting determines the configuration for Type-C Port 1	UP4 UP3	No Restrictions No Restrictions
	Type-C Port 2 Configuration Value: No Restrictions/DP Fixed Connection/No Thunderbolt This setting determines the configuration for Type-C Port 2	UP4 UP3	No Restrictions No Restrictions
	Type-C Port 3 Configuration Value: No Restrictions/DP Fixed Connection/No Thunderbolt This setting determines the configuration for Type-C Port 3	UP4 UP3	No Restrictions No Restrictions
	Type-C Port 4 Configuration Value: No Restrictions/DP Fixed Connection/No Thunderbolt This setting determines the configuration for Type-C Port 4	UP4 UP3	No Restrictions No Restrictions



Table 2-16. - Flex I/O Straps (Sheet 9 of 15)

	Type-C Port 1 Speed Capability Values: USB 3.1 Gen2/USB 3.1 Gen1 This setting determines the Type-C Port 1 speed capability	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2
	Type-C Port 2 Speed Capability Values: USB 3.1 Gen2/USB 3.1 Gen1 This setting determines the Type-C Port 2 speed capability	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2
	Type-C Port 3 Speed Capability Values: USB 3.1 Gen2/USB 3.1 Gen1 This setting determines the Type-C Port 3 speed capability	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2
	Type-C Port 4 Speed Capability Values: USB 3.1 Gen2/USB 3.1 Gen1 This setting determines the Type-C Port 4 speed capability	UP4 UP3	USB 3.1 Gen2 USB 3.1 Gen2
	Type-C Port 1 Initialization Speed Select Values: USB3.1 Gen1 LBPM/USB3.1 Gen2 skip LBPM This setting determines Type-C Port 1 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	Type-C Port 2 Initialization Speed Select Values: USB3.1 Gen1 LBPM/USB3.1 Gen2 skip LBPM This setting determines Type-C Port 2 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	Type-C Port 3 Initialization Speed Select Values: USB3.1 Gen1 LBPM/USB3.1 Gen2 skip LBPM This setting determines Type-C Port 3 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	Type-C Port 4 Initialization Speed Select Values: USB3.1 Gen1 LBPM/USB3.1 Gen2 skip LBPM This setting determines Type-C Port 4 speed during platform power-up.	UP4 UP3	USB3.1 Gen1 LBPM USB3.1 Gen1 LBPM
	Type-C Port 1 Connector Type Select This setting configures the physical connector type to be used for Type-C Port 1.	UP4 UP3	Type-C Type-C
	Type-C Port 2 Connector Type Select This setting configures the physical connector type to be used for Type-C Port 2.	UP4 UP3	Type-C Type-C
	Type-C Port 3 Connector Type Select This setting configures the physical connector type to be used for Type-C Port 3.	UP4 UP3	Type-C Type-C
	Type-C Port 4 Connector Type Select This setting configures the physical connector type to be used for Type-C Port 4.	UP4 UP3	Type-C Type-C
	xDCl Split Die Configuration Values: xDCI Split Die Enabled, xDCI Split Die Disabled	UP4 UP3	xDCl Split Die Enabled xDCl Split Die Enabled

Click on Flex I/O in the left tabs menu> Thunderbolt Configuration is expanded by default:

Thunderbolt Configuration

7

Parameter	Value	Help
Thunderbolt Enable	Yes	This setting determines if the Thunderbolt inte

#	Parameter	Platform	Settings
7	Thunderbolt Configuration		
	Thunderbolt Enable Values: Yes/No This setting determines if the Thunderbolt ^(tm) interface is enabled on the platform.	UP4 UP3	Yes Yes

Click on Flex I/O in the left tabs menu> Power Delivery PD Controller Configuration is expanded by default:



Table 2-16. - Flex I/O Straps (Sheet 10 of 15)

▼ Power Delivery PD Controller Configuration 8		
Parameter	Value	
PMC-PD controller USB-C Mode Enabled	PMC / SMBus	This bit defines how the PMC interfaces with the type C components on the board
Re-timer Power Gating Enabled	No	Indicates whether platform Re-timer power gating is enabled.
Type-C port 1 Enabled	Yes	Indicates whether the associated Type-C port is enabled.
USB2 Port Number associated for Type-C Port 1	USB2 Port 1	USB2 port number for the associated Type-C port
USB3 Port Number associated for Type-C Port 1	Type-C Port 1	USB3 port number for the associated Type-C port
Type-C Port 1 Re-Timer Present	Yes	Indicates whether a re-timer is present for the associated Type-C port.
Type-C Port 1 Re-timer Configuration Enabled	No	Indicates whether the associated re-timer requires configuration. Enabled = config
Type-C Port 1 Re-timer SMBus Address	0x40	SMBus address for the associated re-timer.
Type C Port 1 SMBus Address	0x50	SMBus address for the associated type C port
Type-C port 2 Enabled	Yes	Indicates whether the associated Type-C port is enabled
USB2 Port Number associated for Type-C Port 2	USB2 Port 5	USB2 port number for the associated Type-C port
USB3 Port Number associated for Type-C Port 2	Type-C Port 2	USB3 port number for the associated Type-C port
Type-C Port 2 Re-Timer Present	Yes	Indicates whether a re-timer is present for the associated Type-C port.
Type-C Port 2 Re-timer Configuration Enabled	No	Indicates whether the associated re-timer requires configuration. Enabled = config
Type-C Port 2 Re-timer SMBus Address	0x41	SMBus address for the associated re-timer
Type-C Port 2 SMBus Address	0x51	SMBus address for the associated Type-C port
Type-C port 3 Enabled	Yes	Indicates whether the associated Type-C port is enabled
USB2 Port Number associated for Type-C Port 3	USB2 Port 6	USB2 port number for the associated Type-C port
USB3 Port Number associated for Type-C Port 3	Type-C Port 3	USB3 port number for the associated Type-C port
Type-C Port 3 Re-Timer Present	Yes	Indicates whether a re-timer is present for the associated Type-C port.
Type-C Port 3 Re-timer Configuration Enabled	No	Indicates whether the associated re-timer requires configuration. Enabled = config
Type-C Port 3 Re-timer SMBus Address	0x42	SMBus address for the associated re-timer
Type-C Port 3 SMBus Address	0x52	SMBus address for the associated Type-C port
Type-C port 4 Enabled	Yes	Indicates whether the associated Type-C port is enabled
USB2 Port Number associated for Type-C Port 4	USB2 Port 7	USB2 port number for the associated Type-C port
USB3 Port Number associated for Type-C Port 4	Type-C Port 4	USB3 port number for the associated Type-C port
Type-C Port 4 Re-Timer Present	Yes	Indicates whether a re-timer is present for the associated Type-C port.
Type-C Port 4 Re-timer Configuration Enabled	No	Indicates whether the associated re-timer requires configuration. Enabled = config
Type-C Port 4 Re-timer SMBus Address	0x43	SMBus address for the associated re-timer
Type-C Port 4 SMBus Address	0x53	SMBus address for the associated Type-C port
Type-C Port 1 Re-Timer Configuration Type	1 Re-Timer	This setting determines the number of Re-Timers being use for Type-C Port 1.
Type-C Port 2 Re-Timer Configuration Type	1 Re-Timer	This setting determines the number of Re-Timers being use for Type-C Port 2.
Type-C Port 3 Re-Timer Configuration Type	1 Re-Timer	This setting determines the number of Re-Timers being use for Type-C Port 3.
Type-C Port 4 Re-Timer Configuration Type	1 Re-Timer	This setting determines the number of Re-Timers being use for Type-C Port 4.
8	Power Delivery PD Controller Configuration	



Table 2-16. - Flex I/O Straps (Sheet 11 of 15)

	PMC-PD controller USB-C Mode Enabled Values: 0: PMC interfaces with an eSPI connected agent via eSPI OOB 1: PMC interfaces with PD chips/Re-timer via ALERT# pin which triggers SMBus transactions. This bit defines how the PMC interfaces with the Type-C components on the board. Notes: 1. This setting is greyed and not configurable for LP based SKUs. for LP SKUs, PMC interfaces with PD chips/Re-timer via ALERT# pin. 2. if user selection is 0 where PMC interfaces with an eSPI connected agent, all of the below parameters are N/A and will be grayed out.	UP4 UP3	PMC / SMBus PMC / SMBus
	Re-timer Power Gating Enabled Values: Yes / No This setting indicates whether platform Re-timer power gating is enabled.	UP4 UP3	No No
	Type-C port 1 Enabled Values: Yes / No This setting indicates whether the associated Type-C port1 is enabled. Note: This setting is only available for configuration when PMC-PD controller USB-C Mode Enabled parameter is set to 1.	UP4 UP3	Yes Yes
	USB2 Port Number associated for Type-C Port 1 Values: USB2 Port 1,USB2 Port 2,USB2 Port 3,USB2 Port 4,USB2 Port 5,USB2 Port 6,USB2 Port 7,USB2 Port 8,USB2 Port 9,USB2 Port 10 This indicates the USB2 port number for the associated Type-C port1. Notes: 1. This parameter is applicable only when Type-C port 1 Enabled is set to yes. 2. Once user selects USB2 port number associated with Type-C port1,the respective USB2 port connector selection will be greyed out and auto set to Type-C under the USB2 Port Configuration section. example: if USB2 Port number associated for Type-C Port 1 is set to "USB2 Port 2" ,Parameter under Flex I/O->USB2 Port Configuration->USB2 Port 2 Connector Type Select will be grayed out and auto set to "Type C". 3. OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5)	UP4 UP3	USB2 Port 1 USB2 Port 1
	USB3 Port number associated for Type-C Port 1 Values: USB3 Port 1,USB3 Port 2,USB3 Port 3,USB3 Port 4 This indicates the USB3 port number for the associated Type-C port1. Notes: 1. This parameter is applicable only when Type-C port 1 Enabled is set to yes. 2. Once user selects USB3 port number associated with Type-C port1,the respective USB3 port connector selection will be greyed out and auto set to Type-C under the USB3 Port Configuration section. example: if USB Port number associated for Type-C Port 1 is set to "USB3 Port 6" ,Parameter under Flex I/O->USB3 Port Configuration->USB3 Port 6 Connector Type Select will be grayed out and auto set to "Type C". 3. OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5)	UP4 UP3	USB3 Port 1 USB3 Port 1
	Type-C Port 1 Re-timer Present Values: Yes / No This indicates whether a re-timer is present for the associated Type-C port.	UP4 UP3	Yes Yes



Table 2-16. - Flex I/O Straps (Sheet 12 of 15)

Type-C Port 1 Re-timer Configuration Enabled Values: Yes / No Indicates whether the associated re-timer requires configuration. Yes = configuration done via PMC; No = configuration done via PD Controller.	UP4 UP3	No No
Type-C Port 1 Re-timer SMBus Address Value: Hex This indicates the SMBus address for the associated re-timer.	UP4 UP3	0x40 0x40
Type-C Port 1 SMBus Address Value: Hex This indicates the SMBus address for the associated Type-C port. Note: OEMs are recommended to set unique SMBus address allocation for Type-C port and Re-timer associated.	UP4 UP3	0x20 0x50
Type-C port 2 Enabled Values: Yes / No This setting indicates whether the associated Type-C port is enabled. Note: This setting is only available for configuration when PMC-PD controller USB-C Mode Enabled parameter is set to 1.	UP4 UP3	Yes Yes
USB2 Port Number associated for Type-C Port 2 Values: USB2 Port 1,USB2 Port 2,USB2 Port 3,USB2 Port 4,USB2 Port 5,USB2 Port 6,USB2 Port 7,USB2 Port 8,USB2 Port 9,USB2 Port 10 This indicates the USB2 port number for the associated Type-C port. Notes: <ol style="list-style-type: none"> 1. This parameter is applicable only when Type-C port 2 Enabled is set to yes. 2. Once user selects USB2 port number associated with Type-C port2,the respective USB2 port connector selection will be greyed out and auto set to Type-C under the USB2 Port Configuration section. example: if USB2 Port number associated for Type-C Port 2 is set to "USB2 Port 2" ,Parameter under Flex I/O->USB2 Port Configuration->USB2 Port 2 Connector Type Select will be grayed out and auto set to "Type C". 3. OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5) 	UP4 UP3	USB2 Port 5 USB2 Port 5
USB3 Port number associated for Type-C Port 2 Values: USB3 Port 1,USB3 Port 2,USB3 Port 3,USB3 Port 4 This indicates the USB3 port number for the associated Type-C port. Notes: <ol style="list-style-type: none"> 1. This parameter is applicable only when Type-C port 2Enabled is set to yes. 2. Once user selects USB3 port number associated with Type-C port2,the respective USB3 port connector selection will be greyed out and auto set to Type-C under the USB3 Port Configuration section. example: if USB Port number associated for Type-C Port 2is set to "USB3 Port 6" ,Parameter under Flex I/O->USB3 Port Configuration->USB3 Port 6 Connector Type Select will be grayed out and auto set to "Type C". 3. OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5) 	UP4 UP3	USB3 Port 2 USB3 Port 2
Type-C Port 2 Re-timer Present Values: Yes / No This indicates whether a re-timer is present for the associated Type-C port.	UP4 UP3	Yes Yes
Type-C Port 2 Re-timer Configuration Enabled Values: Yes / No Indicates whether the associated re-timer requires configuration. Yes = configuration done via PMC; No = configuration done via PD Controller.	UP4 UP3	No No



Table 2-16. - Flex I/O Straps (Sheet 13 of 15)

Type-C Port 2 Re-timer SMBus Address Value: Hex This indicates the SMBus address for the associated re-timer.	UP4 UP3	0x41 0x41
Type-C Port 2 SMBus Address Value: Hex This indicates the SMBus address for the associated Type-C port. Note: OEMs are recommended to set unique SMBus address allocation for Type-C port and Re-timer associated.	UP4 UP3	0x24 0x51
Type-C port 3 Enabled Values: Yes / No This setting indicates whether the associated Type-C port is enabled. Note: This setting is only available for configuration when PMC-PD controller USB-C Mode Enabled parameter is set to 1.	UP4 UP3	Yes Yes
USB2 Port Number associated for Type-C Port 3 Values: USB2 Port 1,USB2 Port 2,USB2 Port 3,USB2 Port 4,USB2 Port 5,USB2 Port 6,USB2 Port 7,USB2 Port 8,USB2 Port 9,USB2 Port 10 This indicates the USB2 port number for the associated Type-C port. Notes: <ol style="list-style-type: none"> This parameter is applicable only when Type-C port 3 Enabled is set to yes. Once user selects USB2 port number associated with Type-C port3 ,the respective USB2 port connector selection will be greyed out and auto set to Type-C under the USB2 Port Configuration section. example: if USB2 Port number associated for Type-C Port 3 is set to "USB2 Port 2" ,Parameter under Flex I/O->USB2 Port Configuration->USB2 Port 2 Connector Type Select will be grayed out and auto set to "Type C". OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5) 	UP4 UP3	USB2 Port 6 USB2 Port 6
USB3 Port number associated for Type-C Port 3 Values: USB3 Port 1,USB3 Port 2,USB3 Port 3,USB3 Port 4 This indicates the USB3 port number for the associated Type-C port. Notes: <ol style="list-style-type: none"> This parameter is applicable only when Type-C port 3 Enabled is set to yes. Once user selects USB3 port number associated with Type-C port3,the respective USB3 port connector selection will be greyed out and auto set to Type-C under the USB3 Port Configuration section. example: if USB Port number associated for Type-C Port 3 is set to "USB3 Port 6" ,Parameter under Flex I/O->USB3 Port Configuration->USB3 Port 6 Connector Type Select will be grayed out and auto set to "Type C". OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5) 	UP4 UP3	USB3 Port 3 USB3 Port 3
Type-C Port 3 Re-timer Present Values: Yes / No This indicates whether a re-timer is present for the associated Type-C port.	UP4 UP3	Yes Yes
Type-C Port 3 Re-timer Configuration Enabled Values: Yes / No Indicates whether the associated re-timer requires configuration. Yes = configuration done via PMC; No = configuration done via PD Controller.	UP4 UP3	No No
Type-C Port 3 Re-timer SMBus Address Value: Hex This indicates the SMBus address for the associated re-timer.	UP4 UP3	0x42 0x42



Table 2-16. - Flex I/O Straps (Sheet 14 of 15)

Type-C Port 3 SMBus Address Value: Hex This indicates the SMBus address for the associated Type-C port. Note: OEMs are recommended to set unique SMBus address allocation for Type-C port and Re-timer associated.	UP4 UP3	0x23 0x52
Type-C port 4 Enabled Values: Yes / No This setting indicates whether the associated Type-C port is enabled. Note: This setting is only available for configuration when PMC-PD controller USB-C Mode Enabled parameter is set to 1.	UP4 UP3	No Yes
USB2 Port Number associated for Type-C Port 4 Values: USB2 Port 1,USB2 Port 2,USB2 Port 3,USB2 Port 4,USB2 Port 5,USB2 Port 6,USB2 Port 7,USB2 Port 8,USB2 Port 9,USB2 Port 10 This indicates the USB2 port number for the associated Type-C port. Notes: <ol style="list-style-type: none"> 1. This parameter is applicable only when Type-C port 4 Enabled is set to yes. 2. Once user selects USB2 port number associated with Type-C port4,the respective USB2 port connector selection will be greyed out and auto set to Type-C under the USB2 Port Configuration section. example: if USB2 Port number associated for Type-C Port 4 is set to "USB2 Port 2" ,Parameter under Flex I/O->USB2 Port Configuration->USB2 Port 2 Connector Type Select will be grayed out and auto set to "Type C". 3. OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5) 	UP4 UP3	USB2 Port 7 USB2 Port 7
USB3 Port number associated for Type-C Port 4 Values: USB3 Port 1,USB3 Port 2,USB3 Port 3,USB3 Port 4 This indicates the USB3 port number for the associated Type-C port. Notes: <ol style="list-style-type: none"> 1. This parameter is applicable only when Type-C port 4 Enabled is set to yes. 2. Once user selects USB3 port number associated with Type-C port4,the respective USB3 port connector selection will be greyed out and auto set to Type-C under the USB3 Port Configuration section. example: if USB Port number associated for Type-C Port 4 is set to "USB3 Port 6" ,Parameter under Flex I/O->USB3 Port Configuration->USB3 Port 6 Connector Type Select will be grayed out and auto set to "Type C". 3. OEMs are recommended to configure different USB-C connectors with increasing port numbers (TCP0_*, TCP1_*, TCP2_*, TCP3_*), should be paired with increasing number of USB2 ports from PCH. (this is needed to make split xDCI controller work functionally)E.g. (TCP0_*, USB2*_1), (TCP1_*, USB2*_3), (TCP2_*, USB2*_4), (TCP3_*, USB2*_5) 	UP4 UP3	USB3 Port 4 USB3 Port 4
Type-C Port 4 Re-timer Present Values: Yes / No This indicates whether a re-timer is present for the associated Type-C port.	UP4 UP3	No Yes
Type-C Port 4 Re-timer Configuration Enabled Values: Yes / No Indicates whether the associated re-timer requires configuration. Yes = configuration done via PMC; No = configuration done via PD Controller.	UP4 UP3	No No
Type-C Port 4 Re-timer SMBus Address Value: Hex This indicates the SMBus address for the associated re-timer.	UP4 UP3	0x0 0x43
Type-C Port 4 SMBus Address Value: Hex This indicates the SMBus address for the associated Type-C port. Note: OEMs are recommended to set unique SMBus address allocation for Type-C port and Re-timer associated.	UP4 UP3	0x0 0x53



Table 2-16. - Flex I/O Straps (Sheet 15 of 15)

	Type-C Port 1 Connector Type Select Values: 1 Re-Timer, 2 Re-Timers This setting determines the number of Re-Timers being used for Type-C Port 1	UP4 UP3	1 Re-Timer 1 Re-Timer
	Type-C Port 2 Connector Type Select Values: 1 Re-Timer, 2 Re-Timers This setting determines the number of Re-Timers being used for Type-C Port 2	UP4 UP3	1 Re-Timer 1 Re-Timer
	Type-C Port 3 Connector Type Select Values: 1 Re-Timer, 2 Re-Timers This setting determines the number of Re-Timers being used for Type-C Port 3	UP4 UP3	1 Re-Timer 1 Re-Timer
	Type-C Port 4 Connector Type Select Values: 1 Re-Timer, 2 Re-Timers This setting determines the number of Re-Timers being used for Type-C Port 4	UP4 UP3	1 Re-Timer 1 Re-Timer



Table 2-17. - GPIO (Sheet 1 of 20)

Click on GPIO in the left tabs menu> ME Feature Pins is expanded by default:

▼

ME Feature Pins

1

Parameter	Value	
Intel(R) Precise Touch and Stylus Reset GPIO Select	None	Configure Intel(R) Precise Touch and Stylus Reset GPIO.
Intel(R) Precise Touch and Stylus Interrupt GPIO Select	None	Configure Intel(R) Precise Touch and Stylus Interrupt GPIO.

#	Parameter	Platform	Settings
1	ME Feature Pins		
	Intel® Precise Touch and Stylus Reset GPIO Select Configure Intel® Precise Touch and Stylus Reset GPIO.	UP4 UP3	None None
	Intel® Precise Touch and Stylus Interrupt GPIO Select Configure Intel® Precise Touch and Stylus Interrupt GPIO.	UP4 UP3	None None

Click on GPIO in the left tabs menu> Touch Controller Pins is expanded by default:

▼

Touch Controller Pins

2

Parameter	Value	
GPP_E_1	GPIO	-
GPP_E_2	GPIO	-
GPP_E_10	GPIO	-
GPP_E_11	GPIO	-
GPP_E_12	GPIO	-
GPP_E_13	GPIO	-

#	Parameter	Platform	Settings
2	Touch Controller Pins		
	GPP_E_1	UP4 UP3	GPIO GPIO
	GPP_E_2	UP4 UP3	GPIO GPIO
	GPP_E_10	UP4 UP3	GPIO GPIO
	GPP_E_11	UP4 UP3	GPIO GPIO
	GPP_E_12	UP4 UP3	GPIO GPIO
	GPP_E_13	UP4 UP3	GPIO GPIO

Click on GPIO in the left tabs menu> GPIO VCCIO Voltage Control is expanded by default:



Table 2-17. - GPIO (Sheet 2 of 20)

▼ GPIO VCCIO Voltage Control 3			
Parameter	Value		
GPP_A0 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A1 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A2 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A3 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A4 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A5 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A6 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A7 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A8 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A9 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A10 Individual Voltage Sel...	1.8Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A11 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A12 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A13 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A14 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A15 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A16 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A17 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A18 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A19 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A20 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A21 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A22 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
GPP_A23 Individual Voltage Sel...	3.3Volts	This setting controls the VCCIO voltage for the GPP_	
#	Parameter	Platform	Settings
3	GPIO VCCIO Voltage Control <i>Warning:</i> Incorrectly configuring GPIO voltages may result in MCP damage. The voltage settings below are for the specific RVPs noted under the Platform column. Customers should check their schematics to verify that the appropriate voltages are configured.		
#	Parameter	Platform	Settings
	GPP_A0 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A0 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts



Table 2-17. - GPIO (Sheet 3 of 20)

#	Parameter	Platform	Settings
	GPP_A1 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A1 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A2 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A3 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A4 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A5 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A6 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A6 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A7 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A7 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A8 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A8 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A9 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A9 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A10 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A10 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_A11 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A11 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A12 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A12 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A13 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A13 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A14 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A14 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A15 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A15 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A16 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A16 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A17 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A17 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A18 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A18 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 4 of 20)

#	Parameter	Platform	Settings
	GPP_A19 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A19 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A20 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A20 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A21 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A21 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A22 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A22 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_A23 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_A23 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 5 of 20)

GPP_B0 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B1 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B2 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B3 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B4 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B5 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B6 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B7 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B8 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B9 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B10 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B11 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B12 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B13 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B14 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B15 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B16 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B17 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B18 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for the
GPP_B19 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B20 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B21 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B22 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the
GPP_B23 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for the

#	Parameter	Platform	Settings
	GPP_B0 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B0 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B1 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B1 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B2 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 6 of 20)

#	Parameter	Platform	Settings
	GPP_B3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B3 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B4 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B5 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B6 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B6 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B7 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B7 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B8 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B8 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B9 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B9 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B10 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B10 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B11 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B11 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B12 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B12 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B13 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B13 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B14 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B14 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_B15 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B15 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B16 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B16 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B17 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B17 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B18 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B18 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B19 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B19 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B20 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B20 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 7 of 20)

#	Parameter	Platform	Settings
	GPP_B21 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B21 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B22 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B22 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_B23 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_B23 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts

GPP_C0 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C1 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C2 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C3 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C4 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C5 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C6 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C7 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C8 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C9 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C10 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C11 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C12 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C13 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C14 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C15 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C16 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C17 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C18 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C19 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C20 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C21 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage fo
GPP_C22 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo
GPP_C23 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage fo



Table 2-17. - GPIO (Sheet 8 of 20)

#	Parameter	Platform	Settings
	GPP_C0 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C0 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C1 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C1 GPIO pin.	UP4 UP3	3.3 Volts 1.8 Volts
	GPP_C2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C2 GPIO pin.	UP4 UP3	1.8 Volts 3.3 Volts
	GPP_C3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C3 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C4 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C5 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C6 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C6 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C7 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C7 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C8 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C8 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C9 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C9 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C10 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C10 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C11 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C11 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C12 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C12 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C13 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C13 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C14 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C14 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C15 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C15 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C16 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C16 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C17 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C17 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts



Table 2-17. - GPIO (Sheet 9 of 20)

#	Parameter	Platform	Settings
	GPP_C18 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C18 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C19 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C19 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_C20 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C20 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C21 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C21 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C22 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C22 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_C23 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_C23 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 10 of 20)

GPP_D0 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D1 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D2 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D3 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D4 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D5 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D6 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D7 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D8 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D9 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D10 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D11 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D12 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D13 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D14 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D15 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D16 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_D17 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D18 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_D19 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for

#	Parameter	Platform	Settings
	GPP_D0 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D0 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_D1 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D1 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_D2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D2 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_D3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D3 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_D4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D4 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts



Table 2-17. - GPIO (Sheet 11 of 20)

#	Parameter	Platform	Settings
	GPP_D5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D5 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D6 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D6 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D7 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D7 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D8 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D8 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D9 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D9 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D10 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D10 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D11 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D11 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D12 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D12 GPIO pin.	UP4 UP3	1.8 Volts 3.3 Volts
	GPP_D13 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D13 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D14 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D14 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D15 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D15 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D16 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D16 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_D17 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D17 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_D18 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D18 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_D19 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_D19 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts



Table 2-17. - GPIO (Sheet 12 of 20)

GPP_E0 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E1 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E2 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E3 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E4 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E5 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E6 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E7 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E8 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E9 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E10 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E11 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E12 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E13 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E14 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E15 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E16 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_E17 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E18 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E19 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E20 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E21 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E22 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_E23 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for

#	Parameter	Platform	Settings
	GPP_E0 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E0 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E1 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E1 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E2 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts



Table 2-17. - GPIO (Sheet 13 of 20)

#	Parameter	Platform	Settings
	GPP_E3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E3 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E4 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E5 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E6 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E6 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E7 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E7 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E8 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E8 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E9 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E9 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E10 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E10 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E11 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E11 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E12 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E12 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E13 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E13 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E14 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E14 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E15 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E15 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E16 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E16 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E17 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E17 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_E18 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E18 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E19 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E19 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E20 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E20 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 14 of 20)

#	Parameter	Platform	Settings
	GPP_E21 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E21 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_E22 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E22 GPIO pin.	UP4 UP3	1.8 Volts 3.3 Volts
	GPP_E23 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_E23 GPIO pin.	UP4 UP3	1.8 Volts 3.3 Volts
	GPP_F0 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F1 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F2 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F3 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F4 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F5 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F6 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F7 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F8 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F9 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F10 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F11 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F12 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F13 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F14 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F15 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F16 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F17 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F18 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F19 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F20 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F21 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F22 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
	GPP_F23 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for



Table 2-17. - GPIO (Sheet 15 of 20)

#	Parameter	Platform	Settings
	GPP_F0 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F0 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F1 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F1 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F2 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F3 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F4 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F5 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F6 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F6 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F7 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F7 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F8 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F8 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F9 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F9 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F10 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F10 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F11 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F11 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F12 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F12 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F13 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F13 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F14 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F14 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F15 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F15 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F16 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F16 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F17 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F17 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts



Table 2-17. - GPIO (Sheet 16 of 20)

#	Parameter	Platform	Settings
	GPP_F18 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F18 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_F19 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F19 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F20 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F20 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F21 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F21 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F22 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F22 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_F23 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_F23 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 17 of 20)

GPP_H0 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H1 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H2 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H3 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H4 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H5 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H6 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H7 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H8 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H9 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H10 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H11 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H12 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H13 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H14 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H15 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H16 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H17 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H18 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H19 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for
GPP_H20 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H21 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H22 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for
GPP_H23 Individual Voltage Select	1.8Volts	This setting controls the VCCIO voltage for

#	Parameter	Platform	Settings
	GPP_H0 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H1 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H1 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H2 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H3 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts



Table 2-17. - GPIO (Sheet 18 of 20)

#	Parameter	Platform	Settings
	GPP_H3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H4 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H5 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H5 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H6 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H6 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H7 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H7 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H8 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H8 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H9 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H9 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H10 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H10 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H11 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H11 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H12 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H12 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H13 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H13 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts
	GPP_H14 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H14 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H15 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H15 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H16 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H16 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H17 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H17 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H18 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H18 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H19 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H19 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts
	GPP_H20 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H20 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts



Table 2-17. - GPIO (Sheet 19 of 20)

#	Parameter	Platform	Settings									
	GPP_H21 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H21 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts									
	GPP_H22 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H22 GPIO pin.	UP4 UP3	1.8 Volts 1.8 Volts									
	GPP_H23 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_H23 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts									
<table><tr><td>GPP_T2 Individual Voltage Select</td><td>3.3Volts</td><td>This setting controls the VCCIO voltage for</td></tr><tr><td>GPP_T3 Individual Voltage Select</td><td>3.3Volts</td><td>This setting controls the VCCIO voltage for</td></tr></table>				GPP_T2 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for	GPP_T3 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for			
GPP_T2 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for										
GPP_T3 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for										
#	Parameter	Platform	Settings									
	GPP_T2 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_T2 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts									
	GPP_T3 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_T3 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts									
<table><tr><td>GPP_U4 Individual Voltage Select</td><td>3.3Volts</td><td>This setting controls the VCCIO voltage for</td></tr><tr><td>GPP_U5 Individual Voltage Select</td><td>3.3Volts</td><td>This setting controls the VCCIO voltage for</td></tr><tr><td>Intel(R) HD Audio Voltage Select</td><td>1.8Volts</td><td>This setting controls configures the VCCIO v</td></tr></table>				GPP_U4 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for	GPP_U5 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for	Intel(R) HD Audio Voltage Select	1.8Volts	This setting controls configures the VCCIO v
GPP_U4 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for										
GPP_U5 Individual Voltage Select	3.3Volts	This setting controls the VCCIO voltage for										
Intel(R) HD Audio Voltage Select	1.8Volts	This setting controls configures the VCCIO v										
#	Parameter	Platform	Settings									
	GPP_U4 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_U4 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts									
	GPP_U5 Individual Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for the GPP_U5 GPIO pin.	UP4 UP3	3.3 Volts 3.3 Volts									
	Intel® HD Audio Voltage Select Values: 3.3Volts / 1.8Volts This setting configures the VCCIO voltage for all of the Intel® HD Audio GPIO pins.	UP4 UP3	1.8 Volts 1.8 Volts									

▼ Thunderbolt LSx/BSSB-LS Configuration

4

Parameter	Value	
Thunderbolt LSx/BSSB-LS 0 VCCIO	TX VCCIO	This setting configures Thun
Thunderbolt LSx/BSSB-LS 1 VCCIO	TX VCCIO	This setting configures Thun
Thunderbolt LSx/BSSB-LS 2 VCCIO	TX VCCIO	This setting configures Thun
Thunderbolt LSx/BSSB-LS 3 VCCIO	TX VCCIO	This setting configures Thun



Table 2-17. - GPIO (Sheet 20 of 20)

#	Parameter	Platform	Settings
4	Thunderbolt LSx/BSSB-LS Configuration		
	Thunderbolt LSx/BSSB-LS 0 VCCIO Values: TX VCCIO / Legacy VCCIO This setting configured Thunderbolt LSx/BSSB-LS 0 VCCIO.	UP4 UP3	TX VCCIO TX VCCIO
	Thunderbolt LSx/BSSB-LS 1 VCCIO Values: TX VCCIO / Legacy VCCIO This setting configured Thunderbolt LSx/BSSB-LS 0 VCCIO.	UP4 UP3	TX VCCIO TX VCCIO
	Thunderbolt LSx/BSSB-LS 2 VCCIO Values: TX VCCIO / Legacy VCCIO This setting configured Thunderbolt LSx/BSSB-LS 0 VCCIO.	UP4 UP3	TX VCCIO TX VCCIO
	Thunderbolt LSx/BSSB-LS 3 VCCIO Values: TX VCCIO / Legacy VCCIO This setting configured Thunderbolt LSx/BSSB-LS 0 VCCIO.	UP4 UP3	TX VCCIO TX VCCIO



Table 2-18. - Intel® Precise Touch and Stylus

Click on Intel® Precise Touch and Stylus in the left tabs menu> Intel® Integrated Touch and Stylus Configuration is expanded by default:			
#	Parameter	Platform	Settings
1	IntegratedTouchConfiguration		
	Intel® Precise Touch and Stylus Controller 1 Maximum Frequency Values: 17MHz, 30MHz, 48MHz This setting allows customers to set an upper limit on the frequency for Intel® Precise Touch and Stylus transactions for the Touch Controller 1 interface.	UP4 UP3	30MHz 30MHz
	Intel® Precise Touch and Stylus Enabled Values: Yes / No This setting enables the Intel® Precise Touch and Stylus feature.	UP4 UP3	No No



Table 2-19. - Download and Execute

Click on Download and Execute in the left tabs menu> DnX Image is expanded by default:			
<div> <div>▼ DnX Image</div> <div>1</div> </div>			
Parameter	Value		
Platform ID	0x0	DnX Image attribute. Ignored before FPFs lock. After FPFs lock, I	
OEM ID	0x0	DnX Image attribute. Ignored before FPFs lock. After FPFs lock, I	
BuildEnabled	No	Should Intel FIT build a DnX image	
OutputFileName	\$DestDir\dnx.bin	-	
DnX image private sign key path.		The path to the private key to use to sign the DnX image. This s	
#	Parameter	Platform	Settings
1	Dnx Image		
	Platform ID Value: Hex This configures the Platform ID that DnX uses to verify the image is correct for the platform. Before FPFs are fused, this field is ignored and DnX will accept any image. After FPS lock, only images with this Platform ID will be accepted by DnX. Caution: Ensure that the Platform ID value is correctly populated prior to close of manufacturing on the platform.	UP4 UP3	0 0
	OEM ID Value: Hex This configures the OEM ID that DnX uses to verify the image is correct for the platform. Before FPFs fused, this field is ignored and DnX will accept any image. After FPF lock, only images with this OEM ID will be accepted by DnX. Caution: Ensure that the OEM ID value is correctly populated prior to close of manufacturing on the platform.	UP4 UP3	0 0
	BuildEnabled Value: Binary Yes / No This setting determines if the Intel® FIT tool should build a DnX image	UP4 UP3	No No
	OutputFileName Value: Binary File This setting allow the OEM to designate the DnX binary name for the output file.	UP4 UP3	dnx.bin dnx.bin
	DnX image private sign key path This designates the path to the private key to use to sign the DnX image. This setting is only configurable when OEM signing is enabled (See Platform Integrity / OemPublicKeyHash).	UP4 UP3	- -
Click on Download and Execute in the left tabs menu> DnX Fuses is expanded by default:			



Table 2-19. - Download and Execute

<div> <div>▼ DnX Fuses</div> <div>2</div> </div>			
Parameter		Value	
DnX Enabled		Yes	DnX permanent enable/disable FPF
OEM Platform ID		0x0	This setting allows OEMs to configure
OEM Vendor ID		0x0	This setting allows OEMs to configure

2	DnX Fuses			
	DnX Enabled Value: Yes / No This setting enables / disables DnX. Caution: Setting this option to No will permanently DnX on the platform hardware.		UP4 UP3	Yes Yes
	Platform ID Value: Hex This configures the Platform ID that DnX uses to verify the image is correct for the platform. Before FPFs are fused, this field is ignored and DnX will accept any image. After FPS lock, only images with this Platform ID will be accepted by DnX. Caution: Ensure that the Platform ID value is correctly populated prior to close of manufacturing on the platform.		UP4 UP3	0 0
	OEM ID Value: Hex This configures the OEM ID that DnX uses to verify the image is correct for the platform. Before FPFs fused, this field is ignored and DnX will accept any image. After FPF lock, only images with this OEM ID will be accepted by DnX. Caution: Ensure that the OEM ID value is correctly populated prior to close of manufacturing on the platform.		UP4 UP3	0 0



Table 2-20. - FW Update Image Build

Click on FW Update Image Build in the left tabs menu> ME Image is expanded by default:

▼ ME Image

1

Parameter	Value	
ME Binary File		This loads the Embedded Controller binary

#	Parameter	Platform	Settings
	The FW Update Image Build tab allows users to build firmware update image binaries based on one or several of the following elements combined together: Intel® ME, PMC, OEM KM, IOM, MG, TBT, ISH, iUnit, PCHC and GBST		
1	ME Image		
	ME Binary Image Values: Binary File This loads the Embedded Controller binary that will be merged into the FWUpdate image generated by the Intel® FIT tool.	UP4 UP3	ME Binary ME Binary

Click on FW Update Image Build in the left tabs menu> PMC Image is expanded by default:

▼ PMC Image

2

Parameter	Value	
PMC Max Length	0x20000	-
PMC Binary File		This loads the PMC binary that will be merged

#	Parameter	Platform	Settings
2	PMC Image		
	PMC Max Length		
	PMC Binary Image Values: Binary File This loads the PMC binary that will be merged into the FWUpdate image generated by the Intel® FIT tool.	UP4 UP3	PMC Binary PMC Binary

Click on FW Update Image Build in the left tabs menu> OEM KM Image is expanded by default:

▼ OEM KM Image

3

Parameter	Value	
OEM KM	Enabled	This setting Enables / Disables OEM KM in
OEM KM Max Length	0x1000	-
OEM Key Manifest Binary File		This loads the OEM Key manifest binary m



Table 2-20. - FW Update Image Build

#	Parameter	Platform	Settings												
3	OEM KM Image														
	OEM KM Values: Enabled/Disabled This setting Enables / Disables OEM KM in the FWUpdate image.	UP4 UP3	Enabled Enabled												
	OEM KM Max Length														
	OEM Key Manifest Binary File Values: Binary File This loads the OEM Key manifest binary merged into the output image generated by the Intel® FIT tool.	UP4 UP3	OEM KM Binary OEM KM Binary												
Click on FW Update Image Build in the left tabs menu> IOM Image is expanded by default:															
<div>▼ IOM Image4</div> <table><thead><tr><th>Parameter</th><th>Value</th><th></th></tr></thead><tbody><tr><td>IOM</td><td>Enabled</td><td>This setting Enables / Disables IOM in the FWUpdate image.</td></tr><tr><td>IO Manageability Engine Max Length</td><td>0xC000</td><td>-</td></tr><tr><td>IO Manageability Engine Binary File</td><td></td><td>This loads the IO Manageability Engine binary merged into the output image generated by the Intel® FIT tool.</td></tr></tbody></table>				Parameter	Value		IOM	Enabled	This setting Enables / Disables IOM in the FWUpdate image.	IO Manageability Engine Max Length	0xC000	-	IO Manageability Engine Binary File		This loads the IO Manageability Engine binary merged into the output image generated by the Intel® FIT tool.
Parameter	Value														
IOM	Enabled	This setting Enables / Disables IOM in the FWUpdate image.													
IO Manageability Engine Max Length	0xC000	-													
IO Manageability Engine Binary File		This loads the IO Manageability Engine binary merged into the output image generated by the Intel® FIT tool.													
#	Parameter	Platform	Settings												
4	IOM Image														
	IOM Values: Enabled/Disabled This setting Enables / Disables IOM in the FWUpdate image.	UP4 UP3	Enabled Enabled												
	IO Manageability Engine Max Length														
	IO Manageability Engine Binary File Values: Binary File This loads the IO Manageability binary merged into the output image generated by the Intel® FIT tool.	UP4 UP3	IOM Binary IOM Binary												
Click on FW Update Image Build in the left tabs menu> MG Image is expanded by default:															
<div>▼ PHY Image5</div> <table><thead><tr><th>Parameter</th><th>Value</th><th></th></tr></thead><tbody><tr><td>PHY</td><td>Enabled</td><td>This setting Enables / Disables NPHY in the FWUpdate image.</td></tr><tr><td>PHY Max Length</td><td>0x10000</td><td>-</td></tr><tr><td>PHY Binary File</td><td></td><td>This loads the NPHY binary merged into the output image generated by the Intel® FIT tool.</td></tr></tbody></table>				Parameter	Value		PHY	Enabled	This setting Enables / Disables NPHY in the FWUpdate image.	PHY Max Length	0x10000	-	PHY Binary File		This loads the NPHY binary merged into the output image generated by the Intel® FIT tool.
Parameter	Value														
PHY	Enabled	This setting Enables / Disables NPHY in the FWUpdate image.													
PHY Max Length	0x10000	-													
PHY Binary File		This loads the NPHY binary merged into the output image generated by the Intel® FIT tool.													
#	Parameter	Platform	Settings												



Table 2-20. - FW Update Image Build

5	PHY Image														
	PHY Values: Enabled/Disabled This setting Enables / Disables NPHY in the FWUpdate image.	UP4 UP3	Enabled Enabled												
	PHY Max Length														
	PHY Binary File Values: Binary File This loads the NPHY binary merged into the output image generated by the Intel® FIT tool.	UP4 UP3	NPHY Binary NPHY Binary												
Click on FW Update Image Build in the left tabs menu> TBT Image is expanded by default:															
Thunderbolt(TM)/USB4(TM) Image 6															
<table><tr><th>Parameter</th><th>Value</th><th>Help</th></tr><tr><td>Thunderbolt(TM)/USB4(TM)</td><td>Enabled</td><td>This setting Enables / Disables Thunderbolt</td></tr><tr><td>Thunderbolt(TM)/USB4(TM) Max Length</td><td>0x40000</td><td>-</td></tr><tr><td>Thunderbolt(TM)/USB4(TM) Binary File</td><td></td><td>This loads the Thunderbolt(TM) binary mer</td></tr></table>				Parameter	Value	Help	Thunderbolt(TM)/USB4(TM)	Enabled	This setting Enables / Disables Thunderbolt	Thunderbolt(TM)/USB4(TM) Max Length	0x40000	-	Thunderbolt(TM)/USB4(TM) Binary File		This loads the Thunderbolt(TM) binary mer
Parameter	Value	Help													
Thunderbolt(TM)/USB4(TM)	Enabled	This setting Enables / Disables Thunderbolt													
Thunderbolt(TM)/USB4(TM) Max Length	0x40000	-													
Thunderbolt(TM)/USB4(TM) Binary File		This loads the Thunderbolt(TM) binary mer													
#	Parameter	Platform	Settings												
6	TBT Image														
	Thunderbolt(TM)/USB4(TM) Values: Enabled/Disabled This setting Enables / Disables Thunderbolt(TM)/USB4(TM) in the FWUpdate image.	UP4 UP3	Enabled Enabled												
	Thunderbolt(TM)/USB4(TM) Max Length														
	Thunderbolt(TM)/USB4(TM) Binary File Values: Binary File This loads the Thunderbolt(TM)/USB4(TM) binary merged into the output image generated by the Intel® FIT tool.	UP4 UP3	TBT Binary TBT Binary												
Click on FW Update Image Build in the left tabs menu> ISH Image is expanded by default:															
ISH Image 7															
<table><tr><th>Parameter</th><th>Value</th><th>Help</th></tr><tr><td>ISH</td><td>Enabled</td><td>This setting Enables / Disables ISH in the F</td></tr><tr><td>ISH Max Length</td><td>0x40000</td><td>-</td></tr><tr><td>ISH Binary File</td><td></td><td>This loads the ISH binary merged into the</td></tr></table>				Parameter	Value	Help	ISH	Enabled	This setting Enables / Disables ISH in the F	ISH Max Length	0x40000	-	ISH Binary File		This loads the ISH binary merged into the
Parameter	Value	Help													
ISH	Enabled	This setting Enables / Disables ISH in the F													
ISH Max Length	0x40000	-													
ISH Binary File		This loads the ISH binary merged into the													
#	Parameter	Platform	Settings												
7	ISH Image														



Table 2-20. - FW Update Image Build

	ISH Values: Enabled/Disabled This setting Enables / Disables ISH in the FWUpdate image.	UP4 UP3	Enabled Enabled												
	ISH Max Length														
	ISH Binary File Values: Binary File This loads the ISH binary merged into the output image generated by the Intel® FIT tool.	UP4 UP3	ISH Binary ISH Binary												
Click on FW Update Image Build in the left tabs menu> IUNIT Image is expanded by default:															
<div><div>▼ IUNIT Image</div><div>8</div></div>															
<table><tr><th>Parameter</th><th>Value</th><th></th></tr><tr><td>Iunit</td><td>Enabled</td><td>This setting Enables / Disables IUNIT in the</td></tr><tr><td>IUnit Max Length</td><td>0xA000</td><td>-</td></tr><tr><td>IUnit Binary File</td><td></td><td>This loads the Iuint binary merged into the</td></tr></table>				Parameter	Value		Iunit	Enabled	This setting Enables / Disables IUNIT in the	IUnit Max Length	0xA000	-	IUnit Binary File		This loads the Iuint binary merged into the
Parameter	Value														
Iunit	Enabled	This setting Enables / Disables IUNIT in the													
IUnit Max Length	0xA000	-													
IUnit Binary File		This loads the Iuint binary merged into the													
#	Parameter	Platform	Settings												
8	IUNIT Image														
	IUnit Values: Enabled/Disabled This setting Enables / Disables IUNIT in the FWUpdate image.	UP4 UP3	Enabled Enabled												
	IUnit Max Length														
	IUnit Binary File Values: Binary File This loads the IUnit binary merged into the output image generated by the Intel® FIT tool.	UP4 UP3	IUnit Binary IUnit Binary												
Click on FW Update Image Build in the left tabs menu> PCHC Image is expanded by default:															
<div><div>▼ PCHC Image</div><div>9</div></div>															
<table><tr><th>Parameter</th><th>Value</th><th></th></tr><tr><td>PCH Configuration Max Length</td><td>0x1000</td><td>-</td></tr><tr><td>PCH Configuration File</td><td></td><td>This loads the PCH Configuration binary merged into tl</td></tr></table>				Parameter	Value		PCH Configuration Max Length	0x1000	-	PCH Configuration File		This loads the PCH Configuration binary merged into tl			
Parameter	Value														
PCH Configuration Max Length	0x1000	-													
PCH Configuration File		This loads the PCH Configuration binary merged into tl													
#	Parameter	Platform	Settings												
9	PCHC Image														
	PCH Configuration Max Length														
	Values: Binary File This loads the PCHC binary merged into the output image generated by the Intel® FIT tool.	UP4 UP3	PCHC Binary PCHC Binary												
Click on FW Update Image Build in the left tabs menu> GBST Image is expanded by default:															



Table 2-20. - FW Update Image Build

▼ GBST Image 10			
Parameter		Value	
GBST		Enabled	This setting Enables / Disables GBST Con
GBST Max Length		0x1000	-
GBST File			This loads the GBST Condifuration binary
#	Parameter	Platform	Settings
10	GBST Image		
	GBST Configuration Enable Values: Enabled/Disabled This setting Enables / Disables GBST in the FWUpdate image.	UP4 UP3	Disabled Disabled
	GBST Configuration Max Length		
	Values: Binary File This loads the GBST binary merged into the output image generated by the Intel® FIT tool. Note: The GBST sub-partition is used to enabling FuSa safety standards and is not applicable for client platforms.	UP4 UP3	GBST Binary (Optional) GBST Binary (Optional)



Table 2-21. - Intel® FIT - Build Image

The screenshot shows the Intel Flash Image Tool interface. A red circle with the number 1 points to the 'Build' button in the top toolbar. A red circle with the number 2 points to the 'Firmware Region' section in the main configuration area. A red circle with the number 3 points to the console output at the bottom of the window.

Flash Layout

- Flash Settings
- Intel(R) ME Kernel
- Intel(R) AMT
- Platform Protection
- Integrated Clock Controller
- Networking & Connectivity
- Internal PCH Buses
- Power
- Integrated Sensor Hub
- Camera
- Debug
- CPU Straps
- Flex I/O
- GPIO
- Intel(R) Precise Touch And Stylus
- Download and Execute
- FW Update Image Build

Firmware Region

Parameter	Value	Help Text
OEM Section Binary		This loads the OEM Section binary that will be merged into the output image generated by the In...

BIOS Region


Parameter	Value	Help Text
Length	0	-
BIOS Binary File		This loads the BIOS binary that will be merged into the output image generated by the Intel (R) ...

Ifwi: Intel(R) Me and Pmc Region

Parameter	Value	Help Text
Intel(R) ME Binary File		This loads the Intel(R) ME binary that will be merged into the output image generated by the Int...
Major Version	0	This displays Major revision number of the currently loaded Intel(R) ME binary.
Minor Version	0	This displays Minor revision number of the currently loaded Intel(R) ME binary.
Hotfix Version	0	This displays Hot-Fix revision number of the currently loaded Intel(R) ME binary.

11/20/2019 08:35:15
Using vsccommn.bin with timestamp 20:10:49 05/01/2019 GMT
Command Line: C:\Users\jlwhismo\Desktop\TGL_FIT\Windows32\fit.exe
Log file written to fit.log

1	Green Build button Can also select CTRL+B, or Build> Build Image from the menu bar along the top of the screen
2	Console shows status of build and path where saved
3	Console shows status of build and path where saved



3 Programming SPI Flash Devices and Checking Firmware Status

Now that the Flash image file has been created, it can be programmed into the SPI Flash device(s) of the target machine. For platforms that don't boot, a Flash Chip Programmer will be required. For platforms that can boot to DOS or Windows*, the Intel® FPT can be used.

3.1 Flash Burner/Programmer

The specific use of a Flash burner/programmer is beyond the scope of this document. Here are some general steps that may be followed:

1. Navigate to your **Output Directory** (as specified in Table 2-2) where your generated SPI Flash image(s) are saved. It is assumed that this image file is named **outimage.bin**.

If two total SPI Flash devices were specified during the build process, then additional image files will be saved, one for each SPI Flash devices. These files are assumed to be named **outimage(1).bin** and **outimage(2).bin**.

2. Utilize a Flash burner/programmer to program the image(s). For multiple SPI Flash devices, the images are numbered sequentially to correspond to the first and second SPI Flash devices accordingly.

3.1.1 In-Circuit SPI Flash Programming for CRB

Mobile CRBs have the SPI Flash devices soldered down. As a result, to program the SPI Flash for mobile CRBs, follow these steps:

1. Leave CRB powered on.
2. Connect Flash Programmer (such as DediProg SF600) header to connector **J3F3** which is labelled "**SPI TPM**". Make sure to line up pin 1 on the header.
3. Program the first image [outimage(1).bin] to the CRB.
4. In Dediprog software, select application memory chip 2 button and load second image if created.
5. Program the second image [outimage(2).bin] to the CRB if created.
6. Once programming is complete, disconnect the Flash Programmer header. Power off and unplug CRB. Remove cell coin battery, wait approximately 10 seconds. Replace cell coin battery, plug CRB back in and power on.

3.2 Flash Programming Tool (Intel® FPT)

Intel® FPT can be used to substitute for a Flash burner/programmer, provided the system is capable of booting to a DOS or Windows* OS.

Note: Intel® FPT will automatically disable the Intel® ME or EFI prior to flashing the image to the platform.



3.2.1 Intel® FPT Windows* Version

The Windows* OS versions supported by Intel® FPT are: Windows* PE 64, Windows* 7, Windows* 8/8.1. There are two versions of Intel® FPT for Windows*: a 32-bit version and a 64-bit version. Most Windows* OS, Windows* 7 (32-bit or 64-bit), Windows* 8/8.1 (32-bit or 64-bit) can use Windows* version of Intel® FPT. However, Windows* OS which do not support 32 bit compatible mode (Win PE 64-bit) **must use** Intel® FPT Windows* 64-bit version due to compatibility issues.

Use the following steps to program the SPI Flash devices,

1. Navigate to your **Output Directory** (as specified in [Table 2-2](#)) where your generated SPI Flash image(s) are saved. It is assumed that this image file is named **outimage.bin**. Copy this image file to Intel® FPT directory located at "(root)\Tools\System Tools\Flash Programming Tool\Windows".
2. Boot the target system to Windows* and open a Command Prompt window. In this window, change to the Intel® FPT directory and at the prompt type:

```
fptw.exe -i
```

The system should respond with the number of SPI Flash device available. For example:

```
--- Flash devices Found ---
W25Q64BV ID:0xEF4017 Size: 8192KB (65536Kb)
W25Q64BV ID:0xEF4017 Size: 8192KB (65536Kb)
```

Note: If the SPI Flash device does not currently contain a descriptor it may report only a single device.

3. Program the SPI Flash image to the Flash device(s) by issuing the following command at the prompt:

```
fptw.exe -f outimage.bin
```

If the programming was successful, then the following message will be shown.

```
FPT Operation Passed
```


If the programming was **NOT** successful, then repeat this step to try again. If programming problems persist, then check the SPI Flash devices and platform hardware.

4. Use fptw.exe -greset to perform a G3 power cycle. Next go to [Section 3.3](#) to check the Intel® ME Firmware status.

3.3 Checking Intel® ME Firmware Status

Use the following steps to check the platform health and Intel® CSME FW status,

1. Copy the file **MEInfo.exe** in the "(root)\Tools\System Tools\MEInfo\DOS" directory to the root directory of a bootable USB key.



2. Boot the target system and use F2 or Del to enter the BIOS setup menu. Load default values for BIOS (on Intel® CRBs press F3 to load default values). Save and reboot (on Intel® CRBs press F4 and select Yes).
3. Boot the target system to DOS and change to the root directory of the bootable USB key. At the DOS prompt type:

```
MEInfo.exe -fwsts
```

The system should respond with a message similar to below.

```
Intel® MEInfo Version: 15.0.0.xxxx
Copyright(C) 2005 - 2017, Intel Corporation. All rights reserved.

FW Status Register1: 0x1E000255
FW Status Register2: 0x60002306
FW Status Register3: 0x00000300
FW Status Register4: 0x00004001
FW Status Register5: 0x00000101
FW Status Register6: 0x03C00FC9

Current State: Normal
ManufacturingMode: Enabled
FlashPartition: Valid
OperationalState: M0 with UMA
InitComplete: Complete
BUPLoadState: Success
ErrorCode: No Error
ModeOfOperation: Normal
Phase: HOSTCOMM Module
ICC: Valid OEM data, ICC programmed
SPI Flash Log: Not Present
ME File System Corrupted: No
FPF and ME Config Status: Not committed
```

As in the above example if there are NO errors shown, then

- your platform's health is good
- Intel® CSME FW has successfully initialized
- Intel® CSME FW is operating normally

Note: This section is only intended to show how to use the MEInfo.exe tool for checking firmware status. For full usage and capabilities of the MEInfo.exe tool, please see the System Tools User Guide.



3.4 Common Bring Up Issues and Troubleshooting Table

Table 3-1. Common Bring Up Issues and Troubleshooting Table


Problem / Issue	Solution / Workaround
System does not boot to DOS	By default, the system will boot to EFI Shell. To boot to DOS, <ol style="list-style-type: none"> 1. Enter BIOS menu, then go to the 'Boot' screen 2. Change 'Boot Option #1' to be your USB key (ensure USB key is formatted to be DOS bootable) 3. Press 'F4' to save settings and reboot
Hear 3 beeps when platform powers on	Possible device is disconnected or device not found, check <ul style="list-style-type: none"> • platform power and MCP fan power connectors • DIMM memory modules (if applicable for memory down modules) • USB devices (keyboard, mouse, USB key) may be plugged into inactive USB port • missing/incorrect jumpers • missing or poorly socketed MCP
No display on monitor	Ensure Corporate FW SKU supports integrated graphics. Try external graphics card.
USB device not detected or does not work	USB device may be plugged into inactive USB port
System does not boot (Post Code 00)	Incorrect Flash image – possible reasons: <ul style="list-style-type: none"> • wrong FW selected during Flash image build process • wrong Flash size selected Re-build image with correct settings and re-flash using Flash burner.

§ §

A Appendix — Flash Configurations

This chapter covers only the basic information needed for clock control parameter programming. For a more detailed treatment of Mainstream - Mobile Family clocks, see Intel® Tiger Lake PCH-H / LP Clocks and Intel® Converged Security and Management Engine — Platform Compliancy Guide for ME Hardware.

Figure A-1. Configuration “A” — Desktop/Server/Workstation or Mobile



§ §



B Appendix — Intel® ICCS SKU Support Matrix

The following table describes ICC features supported for specific PCH SKU, clock range (maximum and minimum), spread mode supported by Tiger Lake-LP SKUs.

Note: Please refer to Tiger Lake-H/LP Platform Controller Hub (PCH) External Design Specification (EDS) for details about Tiger Lake-H/LP Chipset Clock architecture

In below tables,

Min = Clock Div Max (minimum allowed frequency)

Max = Clock Div Min (maximum allowed frequency)

B.1 Intel® ICCS SKU Matrix - TGP-LP

Note: ICC SKU is divided into 2 categories: Basic and Enhanced. Mark "x" indicates category supported by PCH SKU.

Table B-1. Intel® ICCS SKU Matrix - TGP-LP

PCH SKU	Basic	Enhanced
Premium Y		x
Premium U		x
Base U		x
Features Supported	Standard Clock Configuration	Standard Clock Configuration Adaptive Clock Configuration
Pre-Defined ICC profile supported	Standard	Standard Adaptive
Clock Range Supported	[Min-Max] = 100 MHz.	BCLK [Min-Max] = 98 - 100 MHz.
SSC Supported	Down SSC: 0 - 0.5%	Down SSC: 0 - 0.5%



C Appendix — Boot Guard Configuration

C.1 Boot Guard Profiles

The following table describes the profiles available for Boot Guard Configuration.

Table C-1. Profile Description

Index	Profile Name	F	V	M	ENF	PBE	Description
0	Boot Guard Profile - No_FVME	0	0	0	00	0	This configuration will invoke Boot Guard during boot with neither Verification nor Measurement. For platforms with all the required Boot Guard components but do not wish to enable Boot Guard boot block verification protection.
3	Boot Guard VM	0	1	1	00	1	When Verification and Measured are desired and the asset protection is provided by TPM protection.
4	Boot Guard FVE	1	1	0	11	1	Strict Verification enforcement.
5	Boot Guard FVME	1	1	1	11	1	Strict Verification and Measured enforcement. Prevents unverified IBB from running.

C.2 Enforcement Policies

Table C-2. Enforcement Policy Description

Error Enforcement Policy (ENF)	Enforcement Mode Name	Description
0	Unrestricted Mode	Infinite time before shutdown – don't shutdown the platform, let everything run normally.
1	Remediation Mode	30 minutes before shutdown – enough time to remediate the system, e.g. update BIOS or other data on flash via host tools.
2	Reserved	
3	Restricted Mode	0 minutes before shutdown – instant shutdown policy.



C.3 OEM Profile Parameters

Table C-3. Profile Parameters Description

Parameter	Description	Settings
Force Boot Guard ACM Enabled (F)	Force Boot Guard Boot determines if the platform starts the Force Boot Guard Boot timer. If it successfully starts it indicates success. When the Force Boot Guard timer stops, it starts the Protect Bios Environment timer, if indicated by the boot policy restrictions. Anchor ACM then jumps to the Initial Boot Block (IBB) with the Force Boot Guard Boot time stopped and the Protect BIOS enable timer running.	false - Allow the CPU to jump to the legacy reset vector if the Boot Guard Module cannot be successfully loaded. (default) true - Force the Boot Guard ACM to execute.
Verified Boot Enabled (V)	Boot Guard cryptographically verifies the platform Initial Boot Block (IBB) using the boot policy key. On successful verification, Boot Guard executes Initial Boot Block (IBB) using the boot policy key. If the verification fails, Anchor signals or enters Remediation.	false - Platform does not perform verified boot (default) true - Platform performs verified boot
Measured Boot Enabled (M)	Boot Guard measures the Initial Boot Block (IBB) into the TPM. Boot Guard perform no verification that the IBB is correct or from the platform manufacturer. The Skylake implementation of Boot Guard will support measurements into TPM or Intel's Platform Trust Technology.	false - Platform does not perform measured boot (default) true - Platform performs measured boot
Protect Bios Environment Enabled (PBE)	Platform manufacturer may want Initial boot block to be protected between verification/ measurement and execution from attacks on buses and non-CPU components. Boot Guard accomplishes this by allowing the initial boot block to be verified and executed in LLC in NEM if PBE is enabled.	false - Take no actions to control the environment during execution of the BIOS components (default) true - Takes actions to control the environment during the execution of the BIOS components.
Error Enforcement Policy (ENF)	Boot Guard invokes the Enforcement Policy when a fatal error is encountered. The action taken by ENF is determined by the OEM set persistent policies. Like, <ul style="list-style-type: none"> • Allowing platform to continue to boot • Immediate Shutdown • Shutdown with Timeout intervals When the ENF logic is invoked, PTT or TPM also disconnects.	See Section C-2 for details.



D Appendix — Intel® Platform Trust Technology

D.1 Intel® Platform Trust Technology

The following table describes the platform configurations supported by Intel® Platform Trust Technology.

Table D-1. Intel® Platform Trust Technology Configuration table

Configuration	Platform Protection> Intel® PTT Configuration Intel® PTT initial power up state	Platform Protection> Intel® PTT Configuration Intel® PTT Supported	Platform Protection> Intel® PTT Configuration Intel® PTT Supported [FPF]	Description
Intel® PTT Permanently Disabled in HW via FPF	Disabled	No	No	After the End of Manufacturing command, this setting will permanently set into the FPFs contained in the MCP. If disabled, the specific MCP can never be enabled for Intel® PTT.
Intel® PTT Permanently Disabled in base firmware image	Disabled	No	Yes	This setting allows Intel® PTT to be set to disabled without disabling the MCP FPFs. This is the recommended option to permanently disable Intel® PTT on a platform.
Intel® PTT Ship State Disabled in base firmware image	Disabled	Yes	Yes	Intel® PTT initially shipped in disabled mode, can be enabled by BIOS command.
Intel® PTT Enabled	Enabled	Yes	Yes	This is the recommended option to enable Intel® PTT on a platform.



E Appendix — Integrated Sensor Hub (ISH) Public Key Settings

The following table describes the configuration matrix required for ISH configuration for the Intel® FIT tool. Please see System Tools User Guide within ME kit, Manufacturing Test with Intel® Converged Security and Management Engine (Intel® ME) Firmware 12 and Intel® Integrated Sensor Solution on Tiger Lake Mobile, Tiger Lake Desktop, (CDI # WIP) for additional details.

CLSMNF = Close Manufacturing switch used with Intel® Flash Programming Tool (FPT)

PV = Production Version

For additional information on FPT see System Tools User Guide included with ME kit under system tools folder.

Table E-1. ISH Public Key Settings

Firmware	MCP	FPF Automatic Commit	FPF MEI command after CLSMNF (Yes/No)	FPF MEI command before CLSMNF (Yes/No)
Pre-production	Production	No	No - Not a valid combination	No - Not a valid combination
Production (PV not set)	Pre-production	No	Yes	No
Production (PV not set)	Production	No	Yes	No
Pre-production	Pre-production	No	Yes	No
Production (PV not set)	Production	Yes	No	No

Note: The Intel® FIT allows integration of binary files within Integrated Sensor Hub section under ISH Image and ISH Data. The Intel® FIT does not generate or create the required files. The table above lists configuration combinations that can be used.





F Appendix — RVP Platform Specific Settings

The following table describes the configuration matrix of RVP specific settings in the Intel® FIT XML.

Table F-1. RVP Settings

RVP Type	Intel® FIT XML setting in StrapsDifferences section	Value
UP4	PCH_Strap_SPI_ClockGateEnable_Diff	0x1
	PCH_Strap_SPI_PowerGateEnable_Diff	0x1
	PCH_Strap_DMI_DMI_CAUM_Diff	0x1
	PCH_Strap_DMI_DMI_TLPFTM_Diff	0x1
	PCH_Strap_DMI_OPDMI_PAD_Diff	0x5
	PCH_Strap_thc0_fuse_ClockGateEnable_Diff	0x1
	PCH_Strap_thc0_fuse_PowerGateEnable_Diff	0x1
	PCH_Strap_thc1_fuse_ClockGateEnable_Diff	0x1
	PCH_Strap_thc1_fuse_PowerGateEnable_Diff	0x1
	PCH_Strap_FIA_LOSL5_Diff	0x0
	PCH_Strap_FIA_LOSL4_Diff	0x0
	PCH_Strap_GBE_Xtal_clk_frequency_Diff	0x1
	PMC_Strap_pmc_smip_CPWRG_RST_WTDIS_Diff	0x1
	PMC_Strap_pmc_smip_SPE_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_SPD_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_TRSB_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_PNCRA5_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_PNCRA4_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_ADC_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_RTC1_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_SMT6_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_SMT5_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_SMT4_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_DTS1_DIS_STRAP_Diff	0x1
	PMC_Strap_pmc_smip_WI_SSTRAP_IVR_ENABLE_Diff	0x1
	PMC_Strap_pmc_smip_VCCIO_FIVR_DIS_Diff	0x1
	PMC_Strap_pmc_smip_DEF_CPU_BCLK_CFG_Diff	0x2
	PMC_Strap_pmc_smip_PHY_VID_Diff	0x7
	PMC_Strap_pmc_smip_vPro_Host_Enabled_Diff	0x0
	CPU_Strap_DTI_Diff	0x28

